

Tabulars with reledmac

September 5, 2015

Abstract

This file provides example of using tabular environments with *reledmac*. We use `edtabularl`, `edtabularc` and `edtabularr`, with `marginal`, `critical` and `familiar` notes. We also use optional arguments of `\pstart`.

1 Left align

1	linea prima	linea prima	sidenote l
2	linea secunda	linea secunda ¹	
3	linea tertia	linea tertia	
4	linea quarta	linea quarta	
5	linea quinta	linea quinta ¹	
6	linea sexta	linea sexta	

2 Center align

7	linea prima	linea prima	sidenote c
8	linea secunda	linea secunda ²	
9	linea tertia	linea tertia	
10	linea quarta	linea quarta	
11	linea quinta	linea quinta ²	
12	linea sexta	linea sexta	

3 Right align

13	linea prima	linea prima	sidenote r
----	-------------	-------------	------------

¹familiar footnote A.

²familiar footnote A.

¹familiar footnote B.

²familiar footnote B.

3 tertia] critical note A

9 tertia] critical note A

4 quarta] critical note B

10 quarta] critical note B

14	linea secunda	linea secunda ³
15	linea tertia	linea tertia
16	linea quarta	linea quarta
17	linea quinta	linea quinta ³
18	linea sexta	linea sexta

³familiar footnote A.

³familiar footnote B.

15 tertia] critical note A

16 quarta] critical note B