The fithesis3 class for the typesetting of theses written at the Masaryk University in Brno

Daniel Marek, Jan Pavlovič, Vít Novotný, Petr Sojka

September 7, 2015

Abstract

This document details the design and the implementation of the fithesis3 document class. It contains technical information for anyone who wishes to extend the class with their locale or style files. Users who only wish to use the class are advised to consult the guides distributed along with the class, which only document the parts of the public API relevant to the given style files.

Contents

1 Required classes and packages **4**

2 Public API **4**
2.1 Options . . . 4
2.2 The \thesissetup macro . . . 4
2.2.1 The basePath key . . . 5
2.2.2 The logoPath key . . . 5
2.2.3 The stylePath key . . . 5
2.2.4 The localePath key . . . 5
2.2.5 The declaration key . . . 7
2.2.6 The gender key . . . 7
2.2.7 The author key . . . 7
2.2.8 The id key . . . 8
2.2.9 The type key . . . 8
2.2.10 The university key . . . 8
2.2.11 The faculty key . . . 9
2.2.12 The department key . . . 9
2.2.13 The departmentEn key . . . 9
2.2.14 The programme key . . . 10
2.2.15 The programmeEn key . . . 10
2.2.16 The field key . . . 10
2.2.17 The fieldEn key . . . 10

2.2.18 The universityLogo key . . . 11
2.2.19 The facultyLogo key . . . 11
2.2.20 The style key . . . 11
2.2.21 The styleInheritance key . . . 11
2.2.22 The locale key . . . 12
2.2.23 The localeInheritance key . . . 12
2.2.24 The date key . . . 13
2.2.25 The place key . . . 14
2.2.26 The title key . . . 14
2.2.27 The TeXtitle key . . . 14
2.2.28 The titleEn key . . . 15
2.2.29 The TeXtitleEn key . . . 15
2.2.30 The keywords key . . . 15
2.2.31 The TeXkeywords key . . . 15
2.2.32 The keywordsEn key . . . 15
2.2.33 The TeXkeywordsEn key . . . 16
2.2.34 The abstract key . . . 16
2.2.35 The abstractEn key . . . 16
2.2.36 The advisor key . . . 16
2.2.37 The thanks key . . . 16
2.2.38 The assignment key . . . 17
2.2.39 The autoLayout key . . . 17
2.3 The \thesislong macro . . . 17

3 Private API **18**
3.1 Main routine . . . 18
3.2 File manipulation macros . . . 19
3.3 String manipulation macros . . . 20
3.4 General purpose macros . . . 21
3.5 Locale files . . . 22
3.5.1 Interface . . . 22
3.5.2 English locale files . . . 23
3.5.2.1 The locale/fithesis-english.def file . . . 23
3.5.2.2 The locale/mu/fithesis-english.def file . . . 24
3.5.2.3 The locale/mu/law/fithesis-english.def file . . . 24
3.5.2.4 The locale/mu/fsps/fithesis-english.def file . . . 24
3.5.2.5 The locale/mu/fss/fithesis-english.def file . . . 24
3.5.2.6 The locale/mu/econ/fithesis-english.def file . . . 25
3.5.2.7 The locale/mu/med/fithesis-english.def file . . . 25
3.5.2.8 The locale/mu/fi/fithesis-english.def file . . . 25
3.5.2.9 The locale/mu/phil/fithesis-english.def file . . . 26
3.5.2.10 The locale/mu/ped/fithesis-english.def file . . . 26
3.5.2.11 The locale/mu/sci/fithesis-english.def file . . . 26
3.5.3 Czech locale files . . . 27
3.5.3.1 The locale/fithesis-czech.def file . . . 27
3.5.3.2 The locale/mu/fithesis-czech.def file . . . 28

3.5.3.3 The locale/mu/law/fithesis-czech.def file . . . 28
3.5.3.4 The locale/mu/fsps/fithesis-czech.def file . . 29
3.5.3.5 The locale/mu/fss/fithesis-czech.def file . . . 29
3.5.3.6 The locale/mu/econ/fithesis-czech.def file . . 29
3.5.3.7 The locale/mu/med/fithesis-czech.def file . . . 29
3.5.3.8 The locale/mu/fi/fithesis-czech.def file 30
3.5.3.9 The locale/mu/phil/fithesis-czech.def file . . 30
3.5.3.10 The locale/mu/ped/fithesis-czech.def file . . . 31
3.5.3.11 The locale/mu/sci/fithesis-czech.def file . . . 31
3.5.4 Slovak locale files 32
3.5.4.1 The locale/fithesis-slovak.def file 32
3.5.4.2 The locale/mu/fithesis-slovak.def file 33
3.5.4.3 The locale/mu/law/fithesis-slovak.def file . . 34
3.5.4.4 The locale/mu/fsps/fithesis-slovak.def file . . 34
3.5.4.5 The locale/mu/fss/fithesis-slovak.def file . . 34
3.5.4.6 The locale/mu/econ/fithesis-slovak.def file . . 35
3.5.4.7 The locale/mu/med/fithesis-slovak.def file . . 35
3.5.4.8 The locale/mu/fi/fithesis-slovak.def file . . . 35
3.5.4.9 The locale/mu/phil/fithesis-slovak.def file . . 36
3.5.4.10 The locale/mu/ped/fithesis-slovak.def file . . 37
3.5.4.11 The locale/mu/sci/fithesis-slovak.def file . . 37
3.6 Style files 37
3.6.1 Interface 37
3.6.2 Base style files 38
3.6.2.1 The style/fithesis-base.sty file 38
3.6.2.2 The style/mu/fithesis-base.sty file 38
3.6.2.3 The style/mu/fithesis-10.clo file 52
3.6.2.4 The style/mu/fithesis-11.clo file 53
3.6.2.5 The style/mu/fithesis-12.clo file 54
3.6.3 The style files of the Faculty of Informatics 61
3.6.3.1 The style/mu/fithesis-fi.sty file 61
3.6.4 The style files of the Faculty of Science 63
3.6.4.1 The style/mu/fithesis-sci.sty file 63
3.6.5 The style files of the Faculty of Arts 69
3.6.5.1 The style/mu/fithesis-phil.sty file 69
3.6.6 The style files of the Faculty of Education 70
3.6.6.1 The style/mu/fithesis-ped.sty file 70
3.6.7 The style files of the Faculty of Social Studies 71
3.6.7.1 The style/mu/fithesis-fss.sty file 71
3.6.8 The style files of the Faculty of Law 72
3.6.8.1 The style/mu/fithesis-law.sty file 72
3.6.9 The style files of the Faculty of Economics and Administration 73
3.6.9.1 The style/mu/fithesis-econ.sty file 73
3.6.10 The style files of the Faculty of Medicine 76
3.6.10.1 The style/mu/fithesis-med.sty file 76
3.6.11 The style files of the Faculty of Sports Studies 79

3.6.11.1 The style/mu/fithesis-fss.sty file 79

1 Required classes and packages

The class loads the `rapport3` base class and the following packages:

- `keyval` – Adds support for parsing comma-delimited lists of key-value pairs.
- `etoolbox` – Adds support for expanding code after the preamble using the `\AtPreamble` hook.
- `ifxetex` – Used to detect the XeTeX engine.
- `ifluatex` – Used to detect the LuaTeX engine.
- `inputenc` – Used to enable the input UTF-8 encoding. This package does not get loaded under the XeTeX and LuaTeX engines.

The `hyperref` package is also conditionally loaded during the expansion of the `\thesis@load` macro (see Section 3.1). Other packages may be required by the style files (see Section 3.6) you are using.

```
\ProvidesClass{fithesis3}[\thesis@version]
\LoadClass[a4paper]{rapport3}
\RequirePackage{keyval}
\RequirePackage{etoolbox}
\RequirePackage{ifxetex}
\RequirePackage{ifluatex}
\ifxetex\else\ifluatex\else
  \RequirePackage[utf8]{inputenc}
\fi\fi
```

2 Public API

2.1 Options

Any `[`⟨*options*⟩`]` passed to the class will be handed down to the loaded style files. The supported options are therefore documented in the subsections of Section 3.6 dedicated to the respective style files.

2.2 The `\thesissetup` macro

`\thesissetup` The main public macro is the `\thesissetup{`⟨*keyvals*⟩`}` command, where *keyvals* is a comma-delimited list of key-value pairs as defined by the `keyval` package. This macro needs to be included prior to the beginning of a LaTeX document. When used, the *keyvals* are processed.

Note that the values passed to the `\thesissetup` public macro may only contain one paragraph of text. If you wish to set multiple paragraphs of text as the value, you need to use the `\thesislong` public macro (see Section 2.3).

```
\def\thesissetup#1{%
  \setkeys{thesis}{#1}}
```

2.2.1 The basePath key

\thesis@basepath

The {⟨basePath=*path*⟩} pair sets the *path* containing the class files. The *path* is prepended to every other path (\thesis@logopath, \thesis@stylepath and \thesis@localepath) used by the class. If non-empty, the *path* gets normalized to *path/*. The normalized *path* is stored within the \thesis@basepath macro, whose implicit value is fithesis/.

```
\def\thesis@basepath{fithesis/}
\define@key{thesis}{basePath}{%
  \ifx\thesis@empty#1\thesis@empty%
    \def\thesis@basepath{}%
  \else%
    \def\thesis@basepath{#1/}%
  \fi}
```

\thesis@logopath

2.2.2 The logoPath key

The {⟨logoPath=*path*⟩} pair sets the *path* containing the logo files, which is used by the style files to load the university and faculty logos. The *path* is normalized using the \thesis@subdir macro and stored within the \thesis@logopath macro, whose implicit value is \thesis@basepath followed by logo/\thesis@university/. By default, this expands to fithesis/logo/mu/.

```
\def\thesis@logopath{\thesis@basepath logo/\thesis@university/}
\define@key{thesis}{logoPath}{%
  \def\thesis@logopath{\thesis@subdir#1%
    \empty\empty\empty\empty}}
```

\thesis@stylepath

2.2.3 The stylePath key

The {⟨stylePath=*path*⟩} pair sets the *path* containing the style files. The *path* is normalized using the \thesis@subdir macro and stored within the \thesis@stylepath macro, whose implicit value is \thesis@basepath style/. By default, this expands to fithesis/style/.

```
\def\thesis@stylepath{\thesis@basepath style/}
\define@key{thesis}{stylePath}{%
  \def\thesis@stylepath{\thesis@subdir#1%
    \empty\empty\empty\empty}}
```

\thesis@localepath

2.2.4 The localePath key

The {⟨localePath=*path*⟩} pair sets the *path* containing the locale files. The *path* is normalized using the \thesis@subdir macro and stored within the

\thesis@localepath macro, whose implicit value is \thesis@basepath followed by locale/. By default, this expands to fithesis/locale/.

```
\def\thesis@localepath{\thesis@basepath locale/}
\define@key{thesis}{localePath}{%
  \def\thesis@localepath{\thesis@subdir#1%
    \empty\empty\empty\empty}}
```

\thesis@subdir The \thesis@subdir macro returns / unchanged, coerces ., .., /*path*, ./*path* and ../*path* to ./, ../, /*path*/, ./*path*/ and ../*path*/, respectively, and prefixes any other *path* with \thesis@basepath.

```
\def\thesis@subdir#1#2#3#4\empty{%
  \ifx#1\empty%           <empty> -> <basepath>
    \thesis@basepath
  \else
    \if#1/%
      \ifx#2\empty%             / -> /
        /%
      \else%              /<path> -> /<path>/
        #1#2#3#4/%
      \fi
    \else%
      \if#1.%
        \ifx#2\empty%           . -> ./
          ./%
        \else
          \if#2.%
            \ifx#3\empty%      .. -> ../
              ../%
            \else
              \if#3/%   ../<path> -> ../<path>/
                ../#4/%
              \else
                \thesis@basepath#1#2#3#4/%
              \fi
            \fi
          \else
            \if#2/%      ./<path> -> ./<path>/
              ./#3#4/%
            \else
              \thesis@basepath#1#2#3#4/%
            \fi
          \fi
        \fi
      \else
        \thesis@basepath#1#2#3#4/%
      \fi
    \fi%
  \fi}
```

\thesis@def The \thesis@def[⟨*key*⟩]{⟨*name*⟩} macro defines the \thesis@*name* macro to ex-

pand to either «*key*», if specified, or to «*name*». The macro serves to provide placeholder strings for macros with no default value.

```
\newcommand{\thesis@def}[2][]{%
  \expandafter\def\csname thesis@#2\endcsname{%
    <<\ifx\thesis@empty#1\thesis@empty#2\else#1\fi>>}}
```

\thesis@declaration

2.2.5 The `declaration` key

The {⟨`declaration`=*text*⟩} pair sets the declaration *text* to be included into the document. The *text* is stored within the `\thesis@declaration` macro, whose implicit value is `\thesis@@{declaration}`.

```
\def\thesis@declaration{\thesis@@{declaration}}
\long\def\KV@thesis@declaration#1{%
  \long\def\thesis@declaration{#1}}
```

\ifthesis@woman

2.2.6 The `gender` key

The {⟨`gender`=*char*⟩} pair sets the author's gender to either a male, if *char* is the character `m`, or to a female. The gender can be tested using the `\ifthesis@woman` ... `\else` ... `\fi` conditional. The implicit gender is male.

```
\newif\ifthesis@woman\thesis@womanfalse
\define@key{thesis}{gender}{%
  \def\thesis@male{m}%
  \def\thesis@arg{#1}%
  \ifx\thesis@male\thesis@arg%
    \thesis@womanfalse%
  \else%
    \thesis@womantrue%
  \fi}
```

\thesis@author

2.2.7 The `author` key

The {⟨`author`=*name*⟩} pair sets the author's full name to *name*. The *name* is parsed using the `\thesis@parseAuthor` macro and stored within the following macros:

\thesis@parseAuthor

\thesis@author

- `\thesis@author` – The full name of the author.

\thesis@author@head

- `\thesis@author@head` – The first space-delimited part of the name. This corresponds to the author's first name.

\thesis@author@tail

- `\thesis@author@tail` – The full name without the first space-delimited part of the name. This corresponds to the author's surname.

```
\def\thesis@parseAuthor#1{%
  \def\thesis@author{#1}%
  \def\thesis@author@head{\expandafter\expandafter\expandafter%
```

```
    \@gobble\thesis@head#1 \relax}%
  \def\thesis@author@tail{\thesis@tail#1 \relax}}
\thesis@def{author}%
\thesis@def[author]{author@head}%
\thesis@def[author]{author@tail}%
\define@key{thesis}{author}{%
  \thesis@parseAuthor{#1}}
```

\thesis@id

2.2.8 The id key

The {⟨id=*identifier*⟩} pair sets the identifier of the thesis author to *identifier*. This usually corresponds to the unique identifier of the author within the information system of the given university.

```
\thesis@def{id}
\define@key{thesis}{id}{%
  \def\thesis@id{#1}}
```

\thesis@type

2.2.9 The type key

The {⟨type=*type*⟩} pair sets the type of the thesis to *type*. The following types of theses are recognized:

The thesis type	The value of *type*
Bachelor's thesis	bc
Master's thesis	mgr
Doctoral thesis	d
Rigorous thesis	r

The *type* is stored within the \thesis@type macro, whose implicit value is bc. For the ease of testing of the thesis type via \ifx conditions within style and locale files, the \thesis@bachelors, \thesis@masters, \thesis@doctoral and \thesis@rigorous macros containing the corresponding *type* values are available as a part of the private API.

\thesis@bachelors
\thesis@masters
\thesis@doctoral
\thesis@rigorous

```
\def\thesis@bachelors{bc}
\def\thesis@masters{mgr}
\def\thesis@doctoral{d}
\def\thesis@rigorous{r}
\let\thesis@type\thesis@bachelors
\define@key{thesis}{type}{%
  \def\thesis@type{#1}}
```

\thesis@university

2.2.10 The university key

The {⟨university=*identifier*⟩} pair sets the identifier of the university, at which the thesis is being written, to *identifier*. The *identifier* is stored within the

\thesis@university macro, whose implicit value is mu. This value corresponds to the Masaryk University in Brno.

```
\def\thesis@university{mu}
\define@key{thesis}{university}{%
  \def\thesis@university{#1}}
```

\thesis@faculty

2.2.11 The faculty key

The {⟨faculty=*identifier*⟩} pair sets the faculty, at which the thesis is being written, to *domain*. The following faculty *identifier*s are recognized at the Masaryk University in Brno:

The faculty	The *domain* name
The Faculty of Informatics	fi
The Faculty of Science	sci
The Faculty of Law	law
The Faculty of Economics and Administration	econ
The Faculty of Social Studies	fss
The Faculty of Medicine	med
The Faculty of Education	ped
The Faculty of Arts	phil
The Faculty of Sports Studies	fsps

The *identifier* is stored within the \thesis@faculty macro, whose implicit value is fi.

```
\def\thesis@faculty{fi}
\define@key{thesis}{faculty}{%
  \def\thesis@faculty{#1}}
```

\thesis@department

2.2.12 The department key

The {⟨department=*name*⟩} pair sets the name of the department, at which the thesis is being written, to *name*. Unlike the university and faculty identifiers, the department *name* is only used for typesetting and it should therefore be specified in plain language with optional TEX macros. The *name* is stored within the \thesis@department macro.

```
\thesis@def{department}
\define@key{thesis}{department}{%
  \def\thesis@department{#1}}
```

\thesis@departmentEn

2.2.13 The departmentEn key

The {⟨departmentEn=*name*⟩} pair sets the English name of the department, at which the thesis is being written, to *name*. The *name* is stored within the \thesis@departmentEn macro.

```
\thesis@def{departmentEn}
\define@key{thesis}{departmentEn}{%
  \def\thesis@departmentEn{#1}}
```

\thesis@programme

2.2.14 The `programme` key

The {⟨programme=*name*⟩} pair sets the name of the author's study programme to *name*. Unlike the university and faculty identifiers, the programme *name* is only used for typesetting and it should therefore be specified in plain language with optional TEX macros. The *name* is stored within the `\thesis@programme` macro.

```
\thesis@def{programme}
\define@key{thesis}{programme}{%
  \def\thesis@programme{#1}}
```

\thesis@programmeEn

2.2.15 The `programmeEn` key

The {⟨programmeEn=*name*⟩} pair sets the English name of the author's study programme to *name*. The *name* is stored within the `\thesis@programmeEn` macro.

```
\thesis@def{programmeEn}
\define@key{thesis}{programmeEn}{%
  \def\thesis@programmeEn{#1}}
```

\thesis@field

2.2.16 The `field` key

The {⟨field=*name*⟩} pair sets the name of the author's field of study to *name*. Unlike the university and faculty identifiers, the *name* of the field of study is only used for typesetting and it should therefore be specified in plain language with optional TEX macros. The *name* is stored within the `\thesis@field` macro.

```
\thesis@def{field}
\define@key{thesis}{field}{%
  \def\thesis@field{#1}}
```

\thesis@fieldEn

2.2.17 The `fieldEn` key

The {⟨fieldEn=*name*⟩} pair sets the English name of the author's field of stufy to *name*. The *name* is stored within the `\thesis@fieldEn` macro.

```
\thesis@def{fieldEn}
\define@key{thesis}{fieldEn}{%
  \def\thesis@fieldEn{#1}}
```

\thesis@universityLogo

2.2.18 The universityLogo key

The {⟨universityLogo=*filename*⟩} pair sets the filename of the logo file to be used as the university logo to *filename*. The *filename* is stored within the \thesis@universityLogo macro, whose implicit value is fithesis-base. The fithesis- prefix serves to prevent package clashes with other similarly named files within the TEX directory structure. The logo file is loaded from the \thesis@logopath\thesis@universityLogo path.

```
\def\thesis@universityLogo{fithesis-base}
\define@key{thesis}{universityLogo}{%
  \def\thesis@universityLogo{#1}}
```

\thesis@facultyLogo

2.2.19 The facultyLogo key

The {⟨facultyLogo=*filename*⟩} pair sets the filename of the logo file to be used as the faculty logo to *filename*. The *filename* is stored within the \thesis@facultyLogo macro, whose implicit value is fithesis-\thesis@faculty. The fithesis- prefix serves to prevent package clashes with other similarly named files within the TEX directory structure. The logo file is loaded from the \thesis@logopath\thesis@facultyLogo path.

```
\def\thesis@facultyLogo{fithesis-\thesis@faculty}
\define@key{thesis}{facultyLogo}{%
  \def\thesis@facultyLogo{#1}}
```

\thesis@style

2.2.20 The style key

The {⟨style=*filename*⟩} pair sets the filename of the style file to be used to *filename*. The *filename* is stored within the \thesis@style macro, whose implicit value is \thesis@university/fithesis-\thesis@faculty. When the *filename* is an empty token string, no style files will be loaded during the main routine (see Section 3.1).

```
\def\thesis@style{\thesis@university/fithesis-\thesis@faculty}
\define@key{thesis}{style}{%
  \def\thesis@style{#1}}
```

\thesis@style@inheritance

2.2.21 The styleInheritance key

The {⟨styleInheritance=*bool*⟩} pair either enables, if *bool* is true or unspecified, or disables the inheritance for style files. The setting affects the function of the \thesis@requireStyle macro (see Section 3.2) and can be tested using the \ifthesis@style@inheritance ... \else ... \fi conditional. Inheritance is enabled for style files by default.

```
\newif\ifthesis@style@inheritance\thesis@style@inheritancetrue
\define@key{thesis}{styleInheritance}[true]{%
  \begingroup
```

```
\def\@true{true}%
\def\@arg{#1}%
\ifx\@true\@arg
  \endgroup\thesis@style@inheritancetrue
\else
  \endgroup\thesis@style@inheritancefalse
\fi}
```

\thesis@locale

2.2.22 The `locale` key

The {⟨locale=*name*⟩} pair sets the name of the main locale to *name*. The *name* is stored within the \thesis@locale macro, whose implicit value is the main language of either the babel or the polyglossia package, or english, when undefined. When the *name* is an empty token string, no locale files will be loaded during the main routine (see Section 3.1).

```
\def\thesis@locale{%
  % Babel / polyglossia detection
  \ifx\languagename\undefined%
  english\else\languagename\fi}
\define@key{thesis}{locale}{%
  \def\thesis@locale{#1}}
```

\ifthesis@english

The English locale is special. Several parts of the document will typically be typeset in both the current locale and English. However, if the current locale is English, this would result in duplicity. To avoid this, the \ifthesis@english ...\else ...\fi conditional is made available for testing, whether or not the current locale is English.

```
\def\ifthesis@english{
  \expandafter\def\expandafter\@english\expandafter{\string%
  \english}%
  \expandafter\expandafter\expandafter\def\expandafter%
  \expandafter\expandafter\@locale\expandafter\expandafter%
  \expandafter{\expandafter\string\csname\thesis@locale\endcsname}%
  \expandafter\csname\expandafter i\expandafter f\ifx\@locale%
  \@english%
    true%
  \else%
    false%
  \fi\endcsname}
```

\thesis@locale@inheritance

2.2.23 The `localeInheritance` key

The {⟨localeInheritance=*bool*⟩} pair either enables, if *bool* is true or unspecified, or disables the inheritance. The setting affects the function of the \thesis@requireLocale macro (see Section 3.2) and can be tested using the \ifthesis@locale@inheritance ...\else ...\fi conditional. Inheritance is enabled for locale files by default.

```
\newif\ifthesis@locale@inheritance\thesis@locale@inheritancetrue
\define@key{thesis}{localeInheritance}[true]{%
  \begingroup
  \def\@true{true}%
  \def\@arg{#1}%
  \ifx\@true\@arg
    \endgroup\thesis@locale@inheritancetrue
  \else
    \endgroup\thesis@locale@inheritancefalse
  \fi}
```

2.2.24 The date key

The {⟨date=*date*⟩} pair sets the date of the thesis defence to *date*, where *date* is a string in the YYYY/MM/DD format, where YYYY stands for full year, MM stands for month and DD stands for day. The *date* is parsed and stored using the

\thesis@parseDate

\thesis@parseDate macro within the following macros:

\thesis@date

- \thesis@date – The entire *date*

\thesis@year

- \thesis@year – The YYYY part of *date*

\thesis@month

- \thesis@month – The MM part of *date*

\thesis@day

- \thesis@day – The DD part of *date*

\thesis@season

- \thesis@season – Expands to either:
  - winter if MM < 7.
  - summer if MM ≥ 7.

\thesis@academicYear

- \thesis@academicYear – The academic year of the given semester:
  - YYYY/YYYY$+1$ in case of a summer semester
  - YYYY-1/YYYY in case of a winter semester

To set up the default values, the \thesis@parseDate macro is called with the fully expanded \the\year/\the\month/\the\day string.

```
\def\thesis@parseDate#1/#2/#3|{{
  % Basic info
  \gdef\thesis@date{#1/#2/#3}%
  \gdef\thesis@year{#1}%
  \gdef\thesis@month{#2}%
  \gdef\thesis@day{#3}%

  % Season and academic year
  \newcount\@year \expandafter\@year \thesis@year \relax%
  \newcount\@month\expandafter\@month\thesis@month\relax%
  \ifnum\@month<7%
    \gdef\thesis@season{winter}%
```

```
    \advance\@year-1\edef\@yearA{\the\@year}%
    \advance\@year 1\edef\@yearB{\the\@year}%
  \else%
    \gdef\thesis@season{summer}%
                      \edef\@yearA{\the\@year}%
    \advance\@year 1\edef\@yearB{\the\@year}%
  \fi%
  \global\edef\thesis@academicYear{\@yearA/\@yearB}}}

\edef\thesis@date{\the\year/\the\month/\the\day}%
\expandafter\thesis@parseDate\thesis@date|%

\define@key{thesis}{date}{{%
  \edef\@date{#1}%
  \expandafter\thesis@parseDate\@date|}}
```

`\thesis@place` **2.2.25 The `place` key**

The {⟨`place`=*place*⟩} pair sets the location of the faculty, at which the thesis is being prepared, to *place*. The *place* is stored within the `\thesis@place` macro, whose implicit value is `Brno`.

```
\def\thesis@place{Brno}
\define@key{thesis}{place}{%
  \def\thesis@place{#1}}
```

`\thesis@title` **2.2.26 The `title` key**

The {⟨`title`=*title*⟩} pair sets the title of the thesis to *title*. The *title* is stored within the `\thesis@title` macro.

```
\thesis@def{title}
\define@key{thesis}{title}{%
  \def\thesis@title{#1}}
```

`\thesis@TeXtitle` **2.2.27 The `TeXtitle` key**

The {⟨`TeXtitle`=*title*⟩} pair sets the TEX title of the thesis to *title*. The *title* is used, when typesetting the title, whereas `\thesis@title` is a plain text, which gets included in the PDF header of the resulting document. The *title* is stored within the `\thesis@TeXtitle` macro, whose implicit value is `\thesis@title`.

```
\def\thesis@TeXtitle{\thesis@title}
\define@key{thesis}{TeXtitle}{%
  \def\thesis@TeXtitle{#1}}
```

\thesis@titleEn

2.2.28 The titleEn key

The {⟨titleEn=*title*⟩} pair sets the English title of the thesis to *title*. The *title* is stored within the \thesis@titleEn macro.

```
\thesis@def{titleEn}
\define@key{thesis}{titleEn}{%
  \def\thesis@titleEn{#1}}
```

\thesis@TeXtitleEn

2.2.29 The TeXtitleEn key

The {⟨TeXtitleEn=*title*⟩} pair sets the English TEX title of the thesis to *title*. The *title* is used, when typesetting the title, whereas \thesis@titleEn is a plain text, which gets included in the PDF header of the resulting document. The *title* is stored within the \thesis@TeXtitleEn macro, whose implicit value is \thesis@titleEn.

```
\def\thesis@TeXtitleEn{\thesis@titleEn}
\define@key{thesis}{TeXtitleEn}{%
  \def\thesis@TeXtitleEn{#1}}
```

\thesis@keywords

2.2.30 The keywords key

The {⟨keywords=*list*⟩} pair sets the keywords of the thesis to the comma-delimited *list*. The *list* is stored within the \thesis@keywords macro.

```
\thesis@def{keywords}
\define@key{thesis}{keywords}{%
  \def\thesis@keywords{#1}}
```

\thesis@TeXkeywords

2.2.31 The TeXkeywords key

The {⟨TeXkeywords=*list*⟩} pair sets the TEX keywords of the thesis to the comma-delimited *list*. The *list* is used, when typesetting the keywords, whereas \thesis@keywords is a plain text, which gets included in the PDF header of the resulting document. The *list* is stored within the \thesis@TeXkeywords macro.

```
\def\thesis@TeXkeywords{\thesis@keywords}
\define@key{thesis}{TeXkeywords}{%
  \def\thesis@TeXkeywords{#1}}
```

\thesis@keywordsEn

2.2.32 The keywordsEn key

The {⟨keywordsEn=*list*⟩} pair sets the English keywords of the thesis to the comma-delimited *list*. The *list* is stored within the \thesis@keywordsEn macro.

```
\thesis@def{keywordsEn}
\define@key{thesis}{keywordsEn}{%
  \def\thesis@keywordsEn{#1}}
```

\thesis@TeXkeywordsEn

2.2.33 The TeXkeywordsEn key

The {⟨TeXkeywordsEn=*list*⟩} pair sets the English TEX keywords of the thesis to the comma-delimited *list*. The *list* is used, when typesetting the keywords, whereas \thesis@keywordsEn is a plain text, which gets included in the PDF header of the resulting document. The *list* is stored within the \thesis@TeXkeywordsEn macro.

```
\def\thesis@TeXkeywordsEn{\thesis@keywordsEn}
\define@key{thesis}{TeXkeywordsEn}{%
  \def\thesis@TeXkeywordsEn{#1}}
```

\thesis@abstract

2.2.34 The abstract key

The {⟨abstract=*text*⟩} pair sets the abstract of the thesis to *text*. The *text* is stored within the \thesis@abstract macro.

```
\thesis@def{abstract}
\long\def\KV@thesis@abstract#1{%
  \long\def\thesis@abstract{#1}}
```

\thesis@abstractEn

2.2.35 The abstractEn key

The {⟨abstractEn=*text*⟩} pair sets the English abstract of the thesis to *text*. The *text* is stored within the \thesis@abstractEn macro.

```
\thesis@def{abstractEn}
\long\def\KV@thesis@abstractEn#1{%
  \long\def\thesis@abstractEn{#1}}
```

\thesis@advisor

2.2.36 The advisor key

The {⟨advisor=*name*⟩} pair sets the thesis advisor's full name to *name*. The *name* is stored within the \thesis@advisor macro.

```
\thesis@def{advisor}
\define@key{thesis}{advisor}{\def\thesis@advisor{#1}}
```

\thesis@thanks

2.2.37 The thanks key

The {⟨thanks=*text*⟩} pair sets the acknowledgement text to *text*. The *text* is stored within the \thesis@thanks macro.

```
\long\def\KV@thesis@thanks#1{%
  \long\def\thesis@thanks{#1}}
```

\thesis@assignmentFiles

2.2.38 The `assignment` key

The {⟨assignment=*list*⟩} pair sets the comma-delimited list of paths to the PDF files containing the thesis assignment to *list*. The *list* is stored within the \thesis@assignmentFiles macro.

```
\define@key{thesis}{assignment}{%
  \def\thesis@assignmentFiles{#1}}
```

\ifthesis@auto

2.2.39 The `autoLayout` key

The {⟨autoLayout=*bool*⟩} pair either enables, if *bool* is true or unspecified, or disables autolayout. Autolayout injects the \thesis@preamble and \thesis@postamble macros at the beginning and at the end of the document, respectively. The setting can be tested using the \ifthesis@auto ... \else ... \fi conditional. The autolayout is enabled by default.

```
\newif\ifthesis@auto\thesis@autotrue
\define@key{thesis}{autoLayout}[true]{%
  \def\@true{true}%
  \def\@arg{#1}%
  \ifx\@true\@arg%
    \thesis@autotrue%
  \else%
    \thesis@autofalse%
  \fi}
```

\thesis@preamble
\thesis@postamble

The \thesis@postamble and \thesis@preamble macros are defined as empty token strings by default and are subject to redefinition by the style files.

```
\def\thesis@preamble{}
\def\thesis@postamble{}
```

2.3 The `\thesislong` macro

\thesislong

The public macro \thesislong{⟨*key*⟩}{⟨*value*⟩}, where *value* may contain multiple paragraphs of text, can be used as an alternative to the \thesissetup public macro, which only permits a single paragraph as the *value*, for the following *key*s:

- abstract
- abstractEn
- thanks
- declaration

```
\long\def\thesislong#1#2{%
  \csname KV@thesis@#1\endcsname{#2}}
```

3 Private API

3.1 Main routine

\thesis@load

The \thesis@load macro is responsible for preparing the environment for, and consequently loading, the necessary locale and style files. By default, the \thesis@load macro gets expanded at the end of the preamble, but it can be expanded manually prior to that point, if necessary to prevent package clashes. The

\ifthesis@loaded

\ifthesis@loaded semaphore ensures that the expansion is only performed once.

```
\newif\ifthesis@loaded\thesis@loadedfalse
\AtEndPreamble{\thesis@load}
\def\thesis@load{%
  \ifthesis@loaded\else%
    \thesis@loadedtrue
    \makeatletter%
```

First, the main locale is selected and its files are loaded using the \thesis@selectLocale macro.

```
      \ifx\thesis@locale\empty\else
        \thesis@selectLocale{\thesis@locale}
      \fi
```

Consequently, the style files are loaded.

```
      \ifx\thesis@style\empty\else
        \thesis@requireStyle{\thesis@style}
      \fi
```

With the placeholder strings loaded from the locale files, we can now inject metadata into the resulting PDF file. To this end, the hyperref package is conditionally included with the unicode option. Consequently, the following values are assigned to the PDF headers:

- Title is set to \thesis@title.
- Author is set to \thesis@author.
- Keywords is set to \thesis@keywords.
- Creator is set to 2015/08/26 v0.3.21 fithesis3 MU thesis class.

```
       \thesis@require{hyperref}%
      {\hypersetup{unicode,
         pdftitle={\thesis@title},%
         pdfauthor={\thesis@author},%
         pdfkeywords={\thesis@keywords},%
         pdfcreator={\thesis@version},%
     }}%
```

If autolayout is enabled, the \thesis@preamble and \thesis@postamble macros are scheduled for expansion at the beginning and at the end of the document, respectively.

```
    \ifthesis@auto%
      \AtBeginDocument{\thesis@preamble}%
      \AtEndDocument{\thesis@postamble}%
    \fi%
```

`\thesis@pages` Lastly, the `\thesis@pages` macro definition containing the length of the document is scheduled to be included in the auxiliary file.

```
    \AtEndDocument{%
      % Define \thesis@pages for the next run
      \write\@auxout{\noexpand\gdef\noexpand%
        \thesis@pages{\thepage}}}
  \makeatother%
\fi}
```

3.2 File manipulation macros

`\thesis@exists` The `\thesis@exists{`⟨*file*⟩`}{`⟨*tokens*⟩`}` macro is used to test for the existence of a given *file*. If the *file* exists, the macro expands to *tokens*. Otherwise, a class warning is written to the output.

```
\def\thesis@exists#1#2{%
  \IfFileExists{#1}{#2}{%
  \ClassWarning{fithesis3}{File #1 doesn't exist}}}
```

`\thesis@input` The `\thesis@input{`⟨*file*⟩`}` macro inputs the given *file*, if it exists.

```
\def\thesis@input#1{%
  \thesis@exists{#1}{\input{#1}}}
```

`\thesis@require` The `\thesis@require {`⟨*package*⟩`}` expands to `\RequirePackage{`⟨*package*⟩`}`, if the specified *package* has not yet been loaded.

```
\def\thesis@require#1{%
  \@ifpackageloaded{#1}{}{\RequirePackage{#1}}}
```

`\thesis@requireWithOptions` The `\thesis@requireWithOptions{`⟨*package*⟩`}` expands to `\RequirePackageWithOptions{`⟨*package*⟩`}`, if the specified *package* exists and has not yet been loaded.

```
\def\thesis@requireWithOptions#1{\thesis@exists{#1.sty}{%
  \@ifpackageloaded{#1}{}{\RequirePackageWithOptions{#1}}}}
```

`\thesis@requireStyle` If inheritance is enabled for style files, then the `\thesis@requireStyle{`⟨*style*⟩`}` macro sequentially loads each of the following files, provided they exist:

1. `\thesis@stylepath fithesis-base.sty`
2. `\thesis@stylepath\thesis@university/fithesis-base.sty`
3. `\thesis@stylepath` *style*`.sty`

If inheritance is disabled for style files, then only the last listed file is loaded. The `fithesis-` prefix serves to prevent package clashes with other similarly named package files within the TEX directory structure.

```
\def\thesis@requireStyle#1{%
  \ifthesis@style@inheritance%
    \thesis@requireWithOptions{\thesis@stylepath fithesis-base}%
    \thesis@requireWithOptions{\thesis@stylepath\thesis@university%
      /fithesis-base}
  \fi%
  \thesis@requireWithOptions{\thesis@stylepath#1}}
```

`\thesis@requireLocale` If inheritance is enabled for style files, then the `\thesis@requireStyle{`⟨*locale*⟩`}` macro sequentially loads each of the following locale files, provided they exist:

1. `\thesis@localepath fithesis-`*locale*`.def`
2. `\thesis@localepath\thesis@university/fithesis-`*locale*`.def`
3. `\thesis@localepath\thesis@university/\thesis@faculty/fithesis-`*locale*`.def`

If inheritance is disabled for locale files, then only the first listed file is loaded. The `fithesis-` prefix serves to prevent clashes with other similarly named files within the TEX directory structure. To prevent undesirable side effects from locale files being loaded multiple times, the `\thesis@`*locale*`@required` macro is defined as a flag, which prevents future invocations with the same *locale*. The macro can be used within both locale and style files, although the usage within locale files is strongly discouraged to prevent circular dependencies.

```
\def\thesis@requireLocale#1{%
  % Ignore redundant requests
  \expandafter\ifx\csname thesis@#1@required\endcsname\relax%
    \expandafter\def\csname thesis@#1@required\endcsname{}%
      {\makeatletter % Enable requiring from within the document
      \thesis@input{\thesis@localepath fithesis-#1.def}%
      \ifthesis@locale@inheritance%
        \thesis@input{\thesis@localepath\thesis@university/%
          fithesis-#1.def}%
        \thesis@input{\thesis@localepath\thesis@university/%
          \thesis@faculty/fithesis-#1.def}%
      \fi}
  \fi}
```

3.3 String manipulation macros

`\thesis@` The `\thesis@{`⟨*name*⟩`}` macro expands to `\thesis@`*name*, where *name* gets fully expanded and can therefore contain active characters and command sequences.

```
\def\thesis@#1{\csname thesis@#1\endcsname}
```

`\thesis@@` The `\thesis@@{`⟨*name*⟩`}` macro expands to `\thesis@`*locale*`@`*name*, where *locale* corresponds to the name of the current locale. The *name* gets fully expanded and can therefore contain active characters and command sequences.

```
\def\thesis@@#1{\thesis@{\thesis@locale @#1}}
```

\thesis@lower
\thesis@upper

The \thesis@lower and \thesis@upper macros are used for upper- and lowercasing within locale files. To cast the \thesis@*name* macro to the lower- or uppercase, \thesis@lower{*name*} or \thesis@upper{*name*} would be used, respectively. The *name* gets fully expanded and can therefore contain active characters and command sequences.

```
\def\thesis@lower#1{{%
  \let\ea\expandafter%
  \ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\lowercase\ea\ea\ea
  \ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea{\ea\ea\ea\ea\ea\ea\ea\ea\ea
  \ea\ea\ea\ea\ea\ea\@gobble\ea\ea\ea\string\ea\csname\csname the%
  sis@#1\endcsname\endcsname}}}
\def\thesis@upper#1{{%
  \let\ea\expandafter%
  \ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\uppercase\ea\ea\ea
  \ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea\ea{\ea\ea\ea\ea\ea\ea\ea\ea\ea
  \ea\ea\ea\ea\ea\ea\@gobble\ea\ea\ea\string\ea\csname\csname the%
  sis@#1\endcsname\endcsname}}}
```

\thesis@@lower
\thesis@@upper

The \thesis@@lower and \thesis@@upper macros are used for upper- and lowercasing current *locale* strings within style files. To cast the \thesis@*locale*@*name* macro to the lower- or uppercase, \thesis@@lower{*name*} or \thesis@@upper{*name*} would be used, respectively. The *name* gets fully expanded and can therefore contain active characters and command sequences.

```
\def\thesis@@lower#1{\thesis@lower{\thesis@locale @#1}}
\def\thesis@@upper#1{\thesis@upper{\thesis@locale @#1}}
```

\thesis@head
\thesis@tail

The \thesis@head and \thesis@tail macros are used for retrieving a head or a tail of space-separated token sequences, which end with \relax.

```
\def\thesis@head#1 #2{%
  \ifx\relax#2%
    \expandafter\@gobbletwo%
  \else%
    \ #1%
  \fi%
  \thesis@head#2}%
\def\thesis@tail#1 #2{%
  \ifx\relax#2%
    #1%
    \expandafter\@gobbletwo%
  \fi%
  \thesis@tail#2}%
```

3.4 General purpose macros

\thesis@pages

The \thesis@pages macro is defined at the beginning of the second LaTeX run as a part of the main routine (see Section 3.1). During the first run, the macro expands to ??.

```
\ifx\thesis@pages\undefined\def\thesis@pages{??}\fi
```

\thesis@selectLocale

\thesis@selectLocale{⟨*locale*⟩} macro redefines the \thesis@locale macro to *locale*, loads the locale files of *locale* and switches to the hyphenation patterns of *locale*.

```
\def\thesis@selectLocale#1{%
  \edef\thesis@locale{#1}%
  \thesis@requireLocale{\thesis@locale}%
  \expandafter\language\csname l@\thesis@locale\endcsname}
```

3.5 Locale files

Locale files contain macro definitions for various locales. They live in the locale/ subtree and they are loaded during the main routine (see Section 3.1).

When creating a new locale file, it is advisable to create one self-contained dtx file, which is then partitioned into locale files via the docstrip tool based on the respective ins file. A macro \file{⟨*filename*⟩} is available for the sectioning of the documentation of various files within the dtx file. For more information about dtx files and the docstrip tool, consult the dtxtut, docstrip, doc and ltxdoc manuals.

\file

Mind that the name of the locale is also used to load hyphenation patterns, which is why it shouldn't be arbitrary. To see the names of the hyphenation patterns, consult the hyph-utf8 manual.

3.5.1 Interface

The union of locale files loaded via the locale file inheritance scheme (see the definition of the \thesis@requireLocale macro in Section 3.2) needs to globally define the following macros:

- \thesis@*locale*@universityName – The name of the university
- \thesis@*locale*@facultyName – The name of the faculty
- \thesis@*locale*@assignment – The instructions to replace the current page with the official thesis assignment
- \thesis@*locale*@declaration – The thesis declaration text
- \thesis@*locale*@fieldTitle – The title of the field of study entry
- \thesis@*locale*@advisorTitle – The title of the advisor entry
- \thesis@*locale*@authorTitle – The title of the author entry
- \thesis@*locale*@abstractTitle – The title of the abstract section
- \thesis@*locale*@keywordsTitle – The title of the keywords section
- \thesis@*locale*@thanksTitle – The title of the acknowledgement section
- \thesis@*locale*@declarationTitle – The title of the declaration section

- `\thesis@`*locale*`@idTitle` – The title of the thesis author's identifier field
- `\thesis@`*locale*`@winter` – The name of the winter semester
- `\thesis@`*locale*`@summer` – The name of the summer semester
- `\thesis@`*locale*`@semester` – The full name of the current semester
- `\thesis@`*locale*`@typeName` – The name of the thesis type

where *locale* is the name of the locale.

3.5.2 English locale files

3.5.2.1 The `locale/fithesis-english.def` file

This is the base file of the English locale. It defines all the private macros mandated by the locale file interface.

```
\ProvidesFile{fithesis/locale/fithesis-english.def}[2015/06/26]

% Placeholders
\gdef\thesis@english@universityName{University name}
\gdef\thesis@english@facultyName{Faculty name}
\gdef\thesis@english@assignment{Replace this page with a copy
  of the official signed thesis assignment.}
\gdef\thesis@english@declaration{Declaration text ...}

% Miscellaneous
\gdef\thesis@english@fieldTitle{Field of study}
\gdef\thesis@english@advisorTitle{Advisor}
\gdef\thesis@english@authorTitle{Author}
\gdef\thesis@english@abstractTitle{Abstract}
\gdef\thesis@english@keywordsTitle{Keywords}
\gdef\thesis@english@thanksTitle{Acknowledgement}
\gdef\thesis@english@declarationTitle{Declaration}
\gdef\thesis@english@idTitle{ID}
\gdef\thesis@english@winter{Spring}
\gdef\thesis@english@summer{Fall}
\gdef\thesis@english@semester{%
  \thesis@{english@\thesis@season} \thesis@year}
\gdef\thesis@english@typeName{%
  \ifx\thesis@type\thesis@bachelors%
    Bachelor's Thesis%
  \else\ifx\thesis@type\thesis@masters%
    Master's Thesis%
  \else\ifx\thesis@type\thesis@doctoral%
    Doctoral Thesis%
  \else\ifx\thesis@type\thesis@rigorous%
    Rigorous Thesis%
  \else%
    <<Unknown thesis type (\thesis@type)>>%
  \fi\fi\fi\fi}
```

3.5.2.2 The `locale/mu/fithesis-english.def` file

This is the English locale file specific to the Masaryk University in Brno. It replaces the `universityName` placeholder with the correct value and defines the `declaration` and `idTitle` strings.

```
\ProvidesFile{fithesis/locale/mu/fithesis-english.def}[2015/06/26]
\gdef\thesis@english@universityName{Masaryk University}
\gdef\thesis@english@declaration{%
  Hereby I declare that this paper is my original authorial work,
  which I have worked out by my own. All sources, references and
  literature used or excerpted during elaboration of this work are
  properly cited and listed in complete reference to the due source.}

% Miscellaneous
\gdef\thesis@english@idTitle{UČO}
```

3.5.2.3 The `locale/mu/law/fithesis-english.def` file

This is the English locale file specific to the Faculty of Law at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and defines the `facultyLongName` required by the `\thesis@blocks@cover` and the `\thesis@blocks@titlePage` blocks.

```
\ProvidesFile{fithesis/locale/mu/law/fithesis-english.def}[2015/06/26]
\gdef\thesis@english@facultyName{Faculty of Law}
\gdef\thesis@english@facultyLongName{The Faculty of Law of the
  Masaryk University}
```

3.5.2.4 The `locale/mu/fsps/fithesis-english.def` file

This is the English locale file specific to the Faculty of Sports Studies at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `fieldTitle` string in accordance with the common usage at the faculty.

```
\ProvidesFile{fithesis/locale/mu/fsps/fithesis-english.def}[2015/06/26]

% Placeholders
\gdef\thesis@english@facultyName{Faculty of Sports Studies}

% Miscellaneous
\gdef\thesis@english@fieldTitle{Specialization}
```

3.5.2.5 The `locale/mu/fss/fithesis-english.def` file

This is the English locale file specific to the Faculty of Social Studies at the Masaryk University in Brno. It replaces the `facultyName` and `assignment` strings with the correct values.

```
\ProvidesFile{fithesis/locale/mu/fss/fithesis-english.def}[2015/06/26]

% Placeholders
```

```
\gdef\thesis@english@facultyName{Faculty of Social Studies}
\gdef\thesis@english@assignment{Replace this page with a copy
 of the official signed thesis assignment or the copy of the
 Statement of an Author or both, depending on the requirements of
 the respective department.}
```

3.5.2.6 The `locale/mu/econ/fithesis-english.def` file

This is the English locale file specific to the Faculty of Economics and Administration at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value.

```
\ProvidesFile{fithesis/locale/mu/econ/fithesis-english.def}[2015/06/26]
\gdef\thesis@english@facultyName{Faculty of Economics
 and Administration}
```

3.5.2.7 The `locale/mu/med/fithesis-english.def` file

This is the English locale file specific to the Faculty of Medicine at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` string with the common usage at the faculty. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-med.sty` style file.

```
\ProvidesFile{fithesis/locale/mu/med/fithesis-english.def}[2015/06/26]

% Miscellaneous
\gdef\thesis@english@abstractTitle{Annotation}

% Placeholders
\gdef\thesis@english@facultyName{Faculty of Medicine}

% Bibliographic entry
\gdef\thesis@english@bib@title{Bibliographic record}
\gdef\thesis@english@bib@pages{p}
```

3.5.2.8 The `locale/mu/fi/fithesis-english.def` file

This is the English locale file specific to the Faculty of Informatics at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the string in accordance with the requirements of the faculty. The file also defines the `advisorSignature` string required by the `\thesis@blocks@titlePage` block defined within the `style/mu/fithesis-fi.sty` style file.

```
\ProvidesFile{fithesis/locale/mu/fi/fithesis-english.def}[2015/06/26]

% Placeholders
\gdef\thesis@english@facultyName{Faculty of Informatics}
\gdef\thesis@english@assignment{Replace this page with a copy
 of the official signed thesis assignment and the copy of the
```

```
  Statement of an Author.}

% Others
\gdef\thesis@english@advisorSignature{Signature of Thesis
  \thesis@english@advisorTitle}
```

3.5.2.9 The `locale/mu/phil/fithesis-english.def` file

This is the English locale file specific to the Faculty of Arts at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value.

```
\ProvidesFile{fithesis/locale/mu/phil/fithesis-english.def}[2015/06/26]
\gdef\thesis@english@facultyName{Faculty of Arts}
```

3.5.2.10 The `locale/mu/ped/fithesis-english.def` file

This is the Slovak locale file specific to the Faculty of Education at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-ped.sty` style file.

```
\ProvidesFile{fithesis/locale/mu/ped/fithesis-english.def}[2015/06/26]

% Placeholders
\gdef\thesis@english@facultyName{Faculty of Education}

% Bibliographic entry
\gdef\thesis@english@bib@title{Bibliographic record}
\gdef\thesis@english@bib@pages{p}
```

3.5.2.11 The `locale/mu/sci/fithesis-english.def` file

This is the English locale file specific to the Faculty of Science at the Masaryk University in Brno. It defines the private macros required by the `\thesis@blocks@bibEntryEn` block defined within the `style/mu/fithesis-sci.sty` style file. It also replaces the `facultyName` placeholder with the correct value and redefines the `advisorTitle` string in accordance with the formal requirements of the faculty.

```
\ProvidesFile{fithesis/locale/mu/sci/fithesis-english.def}[2015/06/26]

% Placeholders
\gdef\thesis@english@facultyName{Faculty of Science}

% Miscellaneous
\global\let\thesis@english@advisorTitleEn=\thesis@english@bib@advisor

% Bibliographic entry
\gdef\thesis@english@bib@title{Bibliographic entry}
\global\let\thesis@english@bib@author\thesis@english@authorTitle
\gdef\thesis@english@bib@thesisTitle{Title of Thesis}
\gdef\thesis@english@bib@programme{Degree Programme}
```

```
\global\let\thesis@english@bib@field\thesis@english@fieldTitle
\gdef\thesis@english@bib@advisor{Supervisor}
\gdef\thesis@english@bib@academicYear{Academic Year}
\gdef\thesis@english@bib@pages{Number of Pages}
\global\let\thesis@english@bib@keywords\thesis@english@keywordsTitle
```

3.5.3 Czech locale files

3.5.3.1 The `locale/fithesis-czech.def` file

This is the base file of the Czech locale. It defines all the private macros mandated by the locale file interface.

`\thesis@czech@gender@koncovka`

The locale file also defines the `\thesis@czech@gender@koncovka` macro, which expands to the correct verb ending based on the value of the `\thesis@ifwoman` macro and the `\thesis@czech@typeName@akuzativ` containing the accusative case of the thesis type name.

```
\ProvidesFile{fithesis/locale/fithesis-czech.def}[2015/06/26]

% Pomocná makra
\gdef\thesis@czech@gender@koncovka{%
  \ifthesis@woman a\fi}

% Zástupné texty
\gdef\thesis@czech@universityName{Název univerzity}
\gdef\thesis@czech@facultyName{Název fakulty}
\gdef\thesis@czech@assignment{Místo tohoto listu vložte kopii
  oficiálního podepsaného zadání práce.}
\gdef\thesis@czech@declaration{Text prohlášení ...}

% Různé
\gdef\thesis@czech@fieldTitle{Obor}
\gdef\thesis@czech@advisorTitle{Vedoucí práce}
\gdef\thesis@czech@authorTitle{Autor}
\gdef\thesis@czech@abstractTitle{Shrnutí}
\gdef\thesis@czech@keywordsTitle{Klíčová slova}
\gdef\thesis@czech@thanksTitle{Poděkování}
\gdef\thesis@czech@declarationTitle{Prohlášení}
\gdef\thesis@czech@idTitle{ID}
\gdef\thesis@czech@winter{Jaro}
\gdef\thesis@czech@summer{Podzim}
\gdef\thesis@czech@semester{%
  \thesis@{czech@\thesis@season} \thesis@year}
\gdef\thesis@czech@typeName{%
  \ifx\thesis@type\thesis@bachelors%
    Bakalářská práce%
  \else\ifx\thesis@type\thesis@masters%
    Diplomová práce%
  \else\ifx\thesis@type\thesis@doctoral%
```

```
    Disertační práce%
  \else\ifx\thesis@type\thesis@rigorous%
    Rigorózní práce%
  \else%
    <<Neznámý typ práce (\thesis@type)>>%
  \fi\fi\fi\fi}
\gdef\thesis@czech@typeName@akuzativ{%
  \ifx\thesis@type\thesis@bachelors%
    Bakalářskou práci%
  \else\ifx\thesis@type\thesis@masters%
    Diplomovou práci%
  \else\ifx\thesis@type\thesis@doctoral%
    Disertační práci%
  \else\ifx\thesis@type\thesis@rigorous%
    Rigorózní práci%
  \else%
    <<Neznámý typ práce (\thesis@type)>>%
  \fi\fi\fi\fi}
```

3.5.3.2 The `locale/mu/fithesis-czech.def` file

This is the Czech locale file specific to the Masaryk University in Brno. It replaces the `universityName` placeholder with the correct value and defines the `declaration` and `idTitle` strings.

```
\ProvidesFile{fithesis/locale/mu/fithesis-czech.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@czech@universityName{Masarykova Univerzita}
\gdef\thesis@czech@declaration{Prohlašuji, že jsem
  \thesis@lower{czech@typeName@akuzativ} zpracoval%
  \thesis@czech@gender@koncovka\ samostatně a
  použil\thesis@czech@gender@koncovka\ jen prameny
  uvedené~v seznamu literatury.}

% Různé
\gdef\thesis@czech@idTitle{UČO}
```

3.5.3.3 The `locale/mu/law/fithesis-czech.def` file

This is the Czech locale file specific to the Faculty of Law at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value, defines the `facultyLongName` required by the `\thesis@blocks@cover` and the `\thesis@blocks@titlePage` blocks and replaces the `abstractTitle` string in accordance with the requirements of the faculty.

```
\ProvidesFile{fithesis/locale/mu/law/fithesis-czech.def}[2015/06/26]

% Různé
\gdef\thesis@czech@abstractTitle{Abstrakt}

```

```
% Zástupné texty
\gdef\thesis@czech@facultyName{Právnická fakulta}
\gdef\thesis@czech@facultyLongName{Právnická fakulta Masarykovy
  univerzity}
```

3.5.3.4 The `locale/mu/fsps/fithesis-czech.def` file

This is the Czech locale file specific to the Faculty of Sports Studies at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `fieldTitle` string in accordance with the common usage at the faculty.

```
\ProvidesFile{fithesis/locale/mu/fsps/fithesis-czech.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@czech@facultyName{Fakulta sportovních studií}

% Různé
\gdef\thesis@czech@fieldTitle{Specializace}
```

3.5.3.5 The `locale/mu/fss/fithesis-czech.def` file

This is the Czech locale file specific to the Faculty of Social Studies at the Masaryk University in Brno. It replaces the `facultyName` and `assignment` placeholders with the correct values.

```
\ProvidesFile{fithesis/locale/mu/fss/fithesis-czech.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@czech@facultyName{Fakulta sociálních studií}
\gdef\thesis@czech@assignment{Místo tohoto listu
  vložte kopie oficiálního podepsaného zadání práce nebo
  prohlášení autora školního díla nebo obojí~v závislosti na
  požadavcích příslušné katedry.}

```

3.5.3.6 The `locale/mu/econ/fithesis-czech.def` file

This is the Czech locale file specific to the Faculty of Economics and Administration at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value.

```
\ProvidesFile{fithesis/locale/mu/econ/fithesis-czech.def}[2015/06/26]
\gdef\thesis@czech@facultyName{Ekonomicko-správní fakulta}
```

3.5.3.7 The `locale/mu/med/fithesis-czech.def` file

This is the Czech locale file specific to the Faculty of Medicine at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` string in accordance with the common usage at the faculty. The file also defines the `bib@title` and `bib@pages`

strings required by the \thesis@blocks@bibEntry block defined within the style/mu/fithesis-med.sty style file.

```
\ProvidesFile{fithesis/locale/mu/med/fithesis-czech.def}[2015/06/26]

% Různé
\gdef\thesis@czech@abstractTitle{Anotace}

% Zástupné texty
\gdef\thesis@czech@facultyName{Lékařská fakulta}

% Bibliografický záznam
\gdef\thesis@czech@bib@title{Bibliografický záznam}
\gdef\thesis@czech@bib@pages{str}
```

3.5.3.8 The locale/mu/fi/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Informatics at the Masaryk University in Brno. It replaces the facultyName placeholder with the correct value and redefines the declaration string in accordance with the requirements of the faculty. The file also defines the advisorSignature string required by the \thesis@blocks@titlePage block defined within the style/mu/fithesis-fi.sty style file.

```
\ProvidesFile{fithesis/locale/mu/fi/fithesis-czech.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@czech@facultyName{Fakulta informatiky}
\gdef\thesis@czech@assignment{Místo tohoto listu
  vložte kopie oficiálního podepsaného zadání práce a
  prohlášení autora školního díla.}
\gdef\thesis@czech@declaration{%
  Prohlašuji, že tato \thesis@lower{czech@typeName} je mým
  původním autorským dílem, které jsem vypracoval%
  \thesis@czech@gender@koncovka\ samostatně. Všechny zdroje,
  prameny a literaturu, které jsem při vypracování
  používal\thesis@czech@gender@koncovka\ nebo z~nich
  čerpal\thesis@czech@gender@koncovka, v~práci řádně cituji
  s~uvedením úplného odkazu na příslušný zdroj.}

% Ostatní
\gdef\thesis@czech@advisorSignature{Podpis vedoucího}
```

3.5.3.9 The locale/mu/phil/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Arts at the Masaryk University in Brno. It replaces the facultyName placeholder with the correct value. It also redefines the declaration, typeName and typeName@akuzativ strings in accordance with the requirements of the faculty.

```
\ProvidesFile{fithesis/locale/mu/phil/fithesis-czech.def}[2015/06/26]

```

```
% Zástupné texty
\gdef\thesis@czech@facultyName{Filozofická fakulta}
\gdef\thesis@czech@declaration{%
  Prohlašuji, že jsem \thesis@lower{czech@typeName@akuzativ}
  vypracoval\thesis@czech@gender@koncovka\ samostatně~s využitím
  uvedené literatury.}

% Ostatní
\gdef\thesis@czech@typeName{%
  \ifx\thesis@type\thesis@bachelors%
    Bakalářská diplomová práce%
  \else\ifx\thesis@type\thesis@masters%
    Magisterská diplomová práce%
  \else\ifx\thesis@type\thesis@doctoral%
    Disertační práce%
  \else%
    <<Neznámý typ práce (\thesis@type)>>%
  \fi\fi\fi}
\gdef\thesis@czech@typeName@akuzativ{%
  \ifx\thesis@type\thesis@bachelors%
    Diplomovou práci%
  \else\ifx\thesis@type\thesis@masters%
    Diplomovou práci%
  \else\ifx\thesis@type\thesis@doctoral%
    Disertační práci%
  \else%
    <<Neznámý typ práce (\thesis@type)>>%
  \fi\fi\fi}
```

3.5.3.10 The `locale/mu/ped/fithesis-czech.def` file

This is the Czech locale file specific to the Faculty of Education at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-ped.sty` style file.

```
\ProvidesFile{fithesis/locale/mu/ped/fithesis-czech.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@czech@facultyName{Pedagogická fakulta}

% Bibliografický záznam
\gdef\thesis@czech@bib@title{Bibliografický záznam}
\gdef\thesis@czech@bib@pages{str}
```

3.5.3.11 The `locale/mu/sci/fithesis-czech.def` file

This is the Czech locale file specific to the Faculty of Science at the Masaryk University in Brno. It defines the private macros required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-sci.sty` style file. It also

replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` and `declaration` strings in accordance with the formal requirements of the faculty.

```
\ProvidesFile{fithesis/locale/mu/sci/fithesis-czech.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@czech@facultyName{Přírodovědecká fakulta}

% Ostatní
\gdef\thesis@czech@abstractTitle{Abstrakt}
\gdef\thesis@czech@declaration{%
  Prohlašuji, že jsem svoji \thesis@lower{czech@typeName@%
  akuzativ} vypracoval\thesis@czech@gender@koncovka\ samo%
  statně s~využitím informačních zdrojů, které jsou v~práci
  citovány.}

% Bibliografický záznam
\gdef\thesis@czech@bib@title{Bibliografický záznam}
\global\let\thesis@czech@bib@author\thesis@czech@authorTitle
\gdef\thesis@czech@bib@thesisTitle{Název práce}
\gdef\thesis@czech@bib@programme{Studijní program}
\global\let\thesis@czech@bib@field\thesis@czech@fieldTitle
\global\let\thesis@czech@bib@advisor\thesis@czech@advisorTitle
\gdef\thesis@czech@bib@academicYear{Akademický rok}
\gdef\thesis@czech@bib@pages{Počet stran}
\global\let\thesis@czech@bib@keywords\thesis@czech@keywordsTitle
```

3.5.4 Slovak locale files

3.5.4.1 The `locale/fithesis-slovak.def` file

This is the base file of the Slovak locale. It defines all the private macros mandated by the locale file interface.

`\thesis@slovak@gender@koncovka`

The locale file also defines the `\thesis@slovak@gender@koncovka` macro, which expands to the correct verb ending based on the value of the `\thesis@ifwoman` macro and the `\thesis@slovak@typeName@akuzativ` containing the accusative case of the thesis type name.

```
\ProvidesFile{fithesis/locale/fithesis-slovak.def}[2015/06/26]

% Pomocná makrá
\gdef\thesis@slovak@gender@koncovka{%
  \ifthesis@woman a\fi}

% Zástupné texty
\gdef\thesis@slovak@universityName{Názov univerzity}
\gdef\thesis@slovak@facultyName{Názov fakulty}
\gdef\thesis@slovak@assignment{Namiesto tejto stránky vložte kópiu
  oficiálneho podpísaného zadania práce.}
```

```
\gdef\thesis@slovak@declaration{Text prehlásenie ...}

% Rôzne
\gdef\thesis@slovak@fieldTitle{Odbor}
\gdef\thesis@slovak@advisorTitle{Vedúci práce}
\gdef\thesis@slovak@authorTitle{Autor}
\gdef\thesis@slovak@abstractTitle{Zhrnutie}
\gdef\thesis@slovak@keywordsTitle{Kľúčové slová}
\gdef\thesis@slovak@thanksTitle{Poďakovanie}
\gdef\thesis@slovak@declarationTitle{Prehlásenie}
\gdef\thesis@slovak@idTitle{ID}
\gdef\thesis@slovak@winter{Jar}
\gdef\thesis@slovak@summer{Jeseň}
\gdef\thesis@slovak@semester{%
  \thesis@{slovak@\thesis@season} \thesis@year}
\gdef\thesis@slovak@typeName{%
  \ifx\thesis@type\thesis@bachelors%
    Bakalárska práca%
  \else\ifx\thesis@type\thesis@masters%
    Diplomová práca%
  \else\ifx\thesis@type\thesis@doctoral%
    Dizertačná práca%
  \else\ifx\thesis@type\thesis@rigorous%
    Rigorózna práca%
  \else%
    <<Neznámy typ práce (\thesis@type)>>%
  \fi\fi\fi\fi}
\gdef\thesis@slovak@typeName@akuzativ{%
  \ifx\thesis@type\thesis@bachelors%
    Bakalársku prácu%
  \else\ifx\thesis@type\thesis@masters%
    Diplomovú prácu%
  \else\ifx\thesis@type\thesis@doctoral%
    Dizertačnú prácu%
  \else\ifx\thesis@type\thesis@rigorous%
    Rigoróznu prácu%
  \else%
    <<Neznámy typ práce (\thesis@type)>>%
  \fi\fi\fi\fi}
```

3.5.4.2 The `locale/mu/fithesis-slovak.def` file

This is the Slovak locale file specific to the Masaryk University in Brno. It replaces the `universityName` placeholder with the correct value and defines the `declaration` and `idTitle` strings.

```
\ProvidesFile{fithesis/locale/mu/fithesis-slovak.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@slovak@universityName{Masarykova Univerzita}
\gdef\thesis@slovak@declaration{%
```

```
  Prehlašujem, že som predloženú \thesis@lower{%
  slovak@typeName@akuzativ} vypracoval%
  \thesis@slovak@gender@koncovka\ samostatne len s~použitím
  uvedenej literatúry a prameňov.}

% Rôzne
\gdef\thesis@slovak@idTitle{UČO}
```

3.5.4.3 The `locale/mu/law/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Law at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value, defines the `facultyLongName` required by the `\thesis@blocks@cover` and the `\thesis@blocks@titlePage` blocks and replaces the `abstractTitle` string in accordance with the requirements of the faculty.

```
\ProvidesFile{fithesis/locale/mu/law/fithesis-slovak.def}[2015/06/26]

% Rôzne
\gdef\thesis@slovak@abstractTitle{Abstrakt}

% Zástupné texty
\gdef\thesis@slovak@facultyName{Právnická fakulta}
\gdef\thesis@slovak@facultyLongName{Právnická fakulta Masarykovej
  univerzity}
```

3.5.4.4 The `locale/mu/fsps/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Sports Studies at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `fieldTitle` string in accordance with the common usage at the faculty.

```
\ProvidesFile{fithesis/locale/mu/fsps/fithesis-slovak.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@slovak@facultyName{Fakulta športových štúdií}

% Rôzne
\gdef\thesis@slovak@fieldTitle{Špecializácie}
```

3.5.4.5 The `locale/mu/fss/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Social Studies at the Masaryk University in Brno. It replaces the `facultyName` and `assignment` strings with the correct values.

```
\ProvidesFile{fithesis/locale/mu/fss/fithesis-slovak.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@slovak@facultyName{Fakulta sociálnych štúdií}
\gdef\thesis@slovak@assignment{Namiesto tejto stránky vložte kópiu
```

```
oficiálneho podpísaného zadania práce alebo prehlásenie autora
školského diela alebo obidve~v závislosti na požiadavkách
príslušnej katedry.}
```

3.5.4.6 The `locale/mu/econ/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Economics and Administration at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value.

```
\ProvidesFile{fithesis/locale/mu/econ/fithesis-slovak.def}[2015/06/26]
\gdef\thesis@slovak@facultyName{Ekonomicko-správna fakulta}
```

3.5.4.7 The `locale/mu/med/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Medicine at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` string in accordance with the common usage at the faculty. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-med.sty` style file.

```
\ProvidesFile{fithesis/locale/mu/med/fithesis-slovak.def}[2015/06/26]

% Rôzne
\gdef\thesis@slovak@abstractTitle{Anotácie}

% Zástupné texty
\gdef\thesis@slovak@facultyName{Lekárska fakulta}

% Bibliografický zoznam
\gdef\thesis@slovak@bib@title{Bibliografický záznam}
\gdef\thesis@slovak@bib@pages{str}
```

3.5.4.8 The `locale/mu/fi/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Informatics at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `declaration` string in accordance with the requirements of the faculty. The file also defines the `advisorSignature` string required by the `\thesis@blocks@titlePage` block defined within the `style/mu/fithesis-fi.sty` style file.

```
\ProvidesFile{fithesis/locale/mu/fi/fithesis-slovak.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@slovak@facultyName{Fakulta informatiky}
\gdef\thesis@slovak@assignment{Namiesto tejto stránky vložte kópiu
 oficiálneho podpísaného zadania práce a prehlásenie autora
 školského diela.}
\gdef\thesis@slovak@declaration{%
 Prehlasujem, že táto \thesis@lower{slovak@typeName} je mojím
```

```
  pôvodným autorským dielom, ktoré som vypracoval%
  \thesis@slovak@gender@koncovka\ samostatne. Všetky zdroje,
  pramene a literatúru, ktoré som pri vypracovaní
  používal\thesis@slovak@gender@koncovka\ alebo z~nich
  čerpal\thesis@slovak@gender@koncovka, v~práci riadne citujem
  s~uvedením úplného odkazu na príslušný zdroj.}

% Rôzne
\gdef\thesis@slovak@advisorSignature{Podpis vedúceho}
```

3.5.4.9 The `locale/mu/phil/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Arts at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. It also defines the `declaration` string and redefines the `typeName` and `typeName@akuzativ` strings in accordance with the requirements of the faculty.

```
\ProvidesFile{fithesis/locale/mu/phil/fithesis-slovak.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@slovak@facultyName{Filozofická fakulta}
\gdef\thesis@slovak@declaration{%
  Prehlašujem, že som predloženú \thesis@lower{%
  slovak@typeName@akuzativ} vypracoval%
  \thesis@slovak@gender@koncovka\ samostatne na
  základe vlastných zistení a len s~použitím
  uvedenej literatúry a prameňov.}

% Rôzne
\gdef\thesis@slovak@typeName{%
  \ifx\thesis@type\thesis@bachelors%
    Bakalárska diplomová práca%
  \else\ifx\thesis@type\thesis@masters%
    Magisterská diplomová práca%
  \else\ifx\thesis@type\thesis@doctoral%
    Dizertačná práca%
  \else%
    <<Neznámy typ práce (\thesis@type)>>%
  \fi\fi\fi}
\gdef\thesis@slovak@typeName@akuzativ{%
  \ifx\thesis@type\thesis@bachelors%
    Diplomovú prácu%
  \else\ifx\thesis@type\thesis@masters%
    Diplomovú prácu%
  \else\ifx\thesis@type\thesis@doctoral%
    Dizertačnú prácu%
  \else%
    <<Neznámý typ práce (\thesis@type)>>%
  \fi\fi\fi}
```

3.5.4.10 The locale/mu/ped/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Education at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-ped.sty` style file.

```
\ProvidesFile{fithesis/locale/mu/ped/fithesis-slovak.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@slovak@facultyName{Pedagogická fakulta}

% Bibliografický zoznam
\gdef\thesis@slovak@bib@title{Bibliografický záznam}
\gdef\thesis@slovak@bib@pages{str}
```

3.5.4.11 The locale/mu/sci/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Science at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value.

```
\ProvidesFile{fithesis/locale/mu/sci/fithesis-slovak.def}[2015/06/26]

% Zástupné texty
\gdef\thesis@slovak@facultyName{Prírodovedecká fakulta}
```

3.6 Style files

Style files define the structure and the look of the resulting document. They live in the `style/` subtree and they are loaded during the main routine (see Section 3.1).

When creating a new style file, it is advisable to create one self-contained `dtx` file, which can contain several files to be extracted via the `docstrip` tool based on the respective `ins` file. A macro `\file{`⟨*filename*⟩`}` is available for the sectioning of the documentation of various files within the `dtx` file. For more information about `dtx` files and the `docstrip` tool, consult the `dtxtut`, `docstrip`, `doc` and `ltxdoc` manuals.

`\file`

3.6.1 Interface

The union of style files loaded via the style file inheritance scheme (see the definition of the `\thesis@requireStyle` macro in Section 3.2) should globally define at least one of the following macros:

`\thesis@preamble`

- `\thesis@preamble` – If autolayout is enabled, then this macro is expanded at the very beginning of the document.

`\thesis@postamble`

- `\thesis@postamble` – If autolayout is enabled, then this macro is expanded at the very end of the document.

3.6.2 Base style files

3.6.2.1 The `style/fithesis-base.sty` file

If inheritance is enabled for style files, then this file is always the first style file to be loaded, regardless of the value of the `\thesis@style` macro. This style file is currently a dummy file.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/fithesis-base}[2015/06/23]
```

3.6.2.2 The `style/mu/fithesis-base.sty` file

This is the base style file for theses written at the Masaryk University in Brno. When inheritance is enabled for style files, this file is always the second style file to be loaded right after `style/fithesis-base.sty`, regardless of the value of the `\thesis@style` macro.

```
\ProvidesPackage{fithesis/style/mu/fithesis-base}[2015/08/26]
\NeedsTeXFormat{LaTeX2e}
```

The file recognizes the following options:

- `10pt`, `11pt`, `12pt` – Sets the type size to 10, 11 or 12 points respectively.
- `oneside`, `twoside` – The document is going to be either single- or double-sided, respectively. In a double-sided document, headers, page numbering, margin notes and several other elements will be arranged based on the parity of the page. Blank pages will also be inserted prior the beginning of each chapter to ensure that it starts on a right-hand (odd-numbered) page. The `\ifthesis@twoside@` conditional is set to either `false` or `true`, respectively.

  `\ifthesis@twoside@`
- `onecolumn`, `twocolumn` – The document is going to be set in either a single column or in two columns, respectively.
- `draft`, `final` – Overful lines either are or aren't marked within the document, respectively, and graphics either aren't or are inserted into the document, respectively.
- `palatino`, `nopalatino` – The default roman and math font family is going to be either set to Palatino or left untouched, respectively. The `\ifthesis@palatino@` conditional is set to either `true` or `false`, respectively. The Palatino font is a part of the visual identity of the Faculty of Informatics at which the document class was created.

  `\ifthesis@palatino@`
- `color`, `monochrome` – Certain typographical elements either are or aren't going to be typeset in color, respectively. The `\ifthesis@color@` conditional is set to either `true` or `false`, respectively.

  `\ifthesis@color@`
- `table`, `oldtable` – If the `\ifthesis@color@` conditional is `true`, then the definition of the `tabular` and `tabularx` commands either are or aren't going to be altered to better match the style, respectively. The `\ifthesis@newtable@`

  `\ifthesis@newtable@`

conditional is set to either `true` or `false`, respectively.

The choice of the option name is deliberate – the redefinition of the table environments depends on the `xcolor` package, which needs to be loaded with the `table` option. Since so many other packages depend on the `xcolor` package and this style file is loaded at the very end of the preamble, there would either be a great chance of an option clash, or the option would have to be passed to the `xcolor` package before the preamble from the body of the `fithesis3` class thus breaking the encapsulation. Naming the option `table` forces the option to be processed by the `xcolor` package as well and it is therefore an elegant solution to the problem at hand.

`\thesis@blocks@tables`

- `lot`, `nolot` – `\listoftables` either is or isn't going to be included in the `\thesis@blocks@tables` block, respectively.

`\thesis@blocks@tables`

- `lof`, `nolof` – `\listoffigures` is or isn't going to be included in the `\thesis@blocks@tables` block, respectively.

`\thesis@blocks@cover` `\ifthesis@cover@`

- `cover`, `nocover` – The `\thesis@blocks@cover` either is going to expand to either the thesis cover or produces no output, respectively. The `\ifthesis@cover@` conditional is set to `false` or `true`, respectively.

```
\DeclareOption{10pt}{\def\thesis@ptsize{0}}
\DeclareOption{11pt}{\def\thesis@ptsize{1}}
\DeclareOption{12pt}{\def\thesis@ptsize{2}}
\newif\ifthesis@twoside@
\DeclareOption{oneside}{%
  \thesis@twoside@false\@twosidefalse\@mparswitchfalse}
\DeclareOption{twoside}{%
  \thesis@twoside@true \@twosidetrue \@mparswitchtrue}
\DeclareOption{onecolumn}{\@twocolumnfalse}
\DeclareOption{twocolumn}{\@twocolumntrue}
\DeclareOption{draft}{\setlength\overfullrule{5pt}}
\DeclareOption{final}{\setlength\overfullrule{0pt}}
\newif\ifthesis@color@
\DeclareOption{monochrome}{\thesis@color@false}
\DeclareOption{color}{\thesis@color@true}
\newif\ifthesis@palatino@
\DeclareOption{palatino}{\thesis@palatino@true}
\DeclareOption{nopalatino}{\thesis@palatino@false}
\newif\ifthesis@newtable@
\DeclareOption{table}{\thesis@newtable@true}
\DeclareOption{oldtable}{\thesis@newtable@false}
\DeclareOption{nolot}{\def\thesis@blocks@lot{}}
\DeclareOption{lot}{\let\thesis@blocks@lot\listoftables}
\DeclareOption{nolof}{\def\thesis@blocks@lof{}}
\DeclareOption{lof}{\let\thesis@blocks@lof\listoffigures}
\newif\ifthesis@cover@
\DeclareOption{nocover}{\thesis@cover@false}
\DeclareOption{cover}{\thesis@cover@true}
```

These are the default options:

```
\ExecuteOptions{12pt,twoside,final,monochrome,palatino,
  oldtable,lot,lof,nocover}
\ProcessOptions
```

The file loads the following packages:

- xcolor – Adds support for color manipulation.
- ifxetex – Used to detect the XƎTEX engine.
- ifluatex – Used to detect the LuaTEX engine.
- graphix – Adds support for the inclusion of graphics files.
- pdfpages – Adds support for the injection of PDF documents into the resulting document, namely the thesis assignment.
- hyperref – Adds support for the injection of metadata into the resulting PDF document.
- keyval – Adds support for parsing comma-delimited lists of key-value pairs.

```
\thesis@require{xcolor}
\thesis@require{graphicx}
\thesis@require{pdfpages}
\thesis@require{keyval}
\thesis@require{ifxetex}
\thesis@require{ifluatex}
```

`\ifthesis@xeluatex` Using the `\ifxetex` and `\ifluatex` conditionals, a compound `\ifthesis@xeluatex` conditional was constructed. This conditional can be used by subsequently loaded style files to test, whether either the XƎTEX or the LuaTEX engine is being used.

```
{\let\x\expandafter
\x\global\x\let\x\ifthesis@xeluatex\csname if%
  \ifxetex true\else
    \ifluatex\x\x\x t\x\x\x r\x\x\x u\x\x\x e%
    \else   f\x\x\x a\x\x\x l\x\x\x s\x\x\x e%
    \fi
  \fi\endcsname}
```

The following packages get only loaded, when the document is being typeset using the XƎTEX or LuaTEX engine:

- fontspec – Allows the selection of system-installed fonts.
- unicode-math – Allows the selection of system-installed mathematical fonts.

Under XƎTEX or LuaTEX, the TeX Gyre Pagella and TeX Gyre Pagella Math are also selected as the main text and math fonts.

```
\ifthesis@xeluatex
  \ifthesis@palatino@
```

```
    \thesis@require{fontspec}
    \thesis@require{unicode-math}
    \setmainfont[Ligatures=TeX]{TeX Gyre Pagella}
    \setmathfont[math-style=ISO,bold-style=ISO,vargreek-shape=TeX]%
      {texgyrepagella-math.otf}
  \fi
```

The following packages get only loaded, when the document is not being typeset using the XƎTEX or LuaTEX engine and the `\ifthesis@palatino@` conditional is `true`:

- `cmap` – Places an explicit `ToUnicode` map in the resulting PDF file, allowing for the extraction of the text from the document.
- `mathpazo` – Changes the default math font family to `mathpazo`.
- `tgpagella` – Changes the default roman font family to TEX Gyre Pagella.
- `lmodern` – Changes the default sans-serif and monotype font faces to Latin Modern instead of the default Computer Modern font family.
- `fontenc` – The font encoding is set to Cork.

```
\else
  \ifthesis@palatino@
    \RequirePackage[resetfonts]{cmap}
    \thesis@require{lmodern}
    \thesis@require{mathpazo}
    \thesis@require{tgpagella}
    \RequirePackage[T1]{fontenc}
  \fi
\fi
```

If the `\thesis@newtable@` and `\thesis@color@` conditionals are `true`, then the following package gets loaded:

- `tabularx` – Provides the `tabularx` environment, which enables the typesetting of tables with flexible-width columns.

Subsequently, the `tabular` and `tabularx` environments are redefined to better match the style of the given faculty.

The `\thesis@newtable@old` and `\endthesis@newtable@old` macros containing the original definition of the `tabular` environment are always defined and are available for subsequently loaded styles in case the typesetting of unaltered tables is required.

```
\let\thesis@newtable@old\tabular
\let\endthesis@newtable@old\endtabular
\ifthesis@newtable@\ifthesis@color@
  \thesis@require{tabularx}
  \thesis@require{booktabs}
  % The redefinition of ‘tabular‘
```

```
\renewenvironment{tabular}%
  {\rowcolors{1}{thesis@color@tableOdd}%
                {thesis@color@tableEven}%
   \thesis@newtable@old}%
  {\endthesis@newtable@old}
% The redefinition of ‘tabularx‘
\let\thesis@newtable@oldx\tabularx
\let\endthesis@newtable@oldx\endtabularx
\renewenvironment{tabularx}%
  {\rowcolors{1}{thesis@color@tableOdd}%
                {thesis@color@tableEven}%
   \thesis@newtable@oldx}%
  {\endthesis@newtable@oldx}
% Adjust the measurements
\setlength{\aboverulesep}{0pt}
\setlength{\belowrulesep}{0pt}
\setlength{\extrarowheight}{.75ex}
\fi\fi
```

The hyperref package is configured to support both roman and arabic page numbering in one document and to decorate hyperlinks with an underline instead of a rectangular box.

```
\thesis@require{hyperref}
\hypersetup{
  pdfborderstyle={/S/U/W 1}, % Less obtrusive borders
  plainpages=false}          % Multiple page numbering support
```

Clubs and widows are set to be infinitely bad.

```
\widowpenalty 10000
\clubpenalty  10000
```

`\thesis@color@setup` The file defines the `\thesis@color@setup{`⟨*colors*⟩`}` command, where *colors* is a comma-delimited list of key-value pairs as defined by the keyval package. The command can be invoked either by the subsequently loaded style files or by the user to define which colors will be used, when the `color` option is specified.

```
\def\thesis@color@setup#1{%
  \setkeys{thesis@color}{#1}}
```

The following key-value pairs are supported:

1. `{`⟨`links=`*color*⟩`}` – Sets the color of hyperref links to *color* and stores it under the name `thesis@color@links`. The default color of links is specified by the hyperref package.

2. `{`⟨`tableOdd=`*color*⟩`}` – Stores the color of the odd rows of the redefined `tabular` and `tabularx` environments under the name `thesis@color@tableOdd`.

3. `{`⟨`tableEven=`*color*⟩`}` – Stores the color of the even rows of the redefined `tabular` and `tabularx` environments under the name `thesis@color@tableEven`.

4. {⟨tableEmph=*color*⟩} – Stores the color of an emphasized cell in a table user under the name thesis@color@tableEmph. This color is meant to be used manually by the user.

```
\define@key{thesis@color}{links}{%
  \definecolor{thesis@color@links}#1
  \hypersetup{linkbordercolor=thesis@color@links}}
\define@key{thesis@color}{tableOdd}{%
  \definecolor{thesis@color@tableOdd}#1}
\define@key{thesis@color}{tableEven}{%
  \definecolor{thesis@color@tableEven}#1}
\define@key{thesis@color}{tableEmph}{%
  \definecolor{thesis@color@tableEmph}#1}
```

The file defines several blocks to be used in the redefinitions of the \thesis@preamble and \thesis@postable macros by the subsequently loaded style files.

\thesis@blocks@frontMatter

The \thesis@blocks@frontMatter macro sets up the style of the front matter of the thesis.

```
\def\thesis@blocks@frontMatter{%
  \thesis@blocks@clear
  \pagestyle{plain}
  \parindent 1.5em
  \setcounter{page}{1}
  \pagenumbering{roman}}
```

\thesis@blocks@clear

The \thesis@blocks@clear macro clears the current page. It also clears the next left-hand (even-numbered) page, when double-sided typesetting is enabled.

```
\def\thesis@blocks@clear{%
  \ifthesis@twoside@%
    \clearpage%
    \thispagestyle{empty}%
    \cleardoublepage%
  \else%
    \newpage%
  \fi}
```

\thesis@blocks@clearRight

The \thesis@blocks@clearRight macro clears the current page. It also clears the next right-hand (odd-numbered) page, when double-sided typesetting is enabled.

```
\def\thesis@blocks@clearRight{%
  \ifthesis@twoside@%
    \clearpage%
    \ifodd\value{page}%
      \thispagestyle{empty}%
      \hbox{}%
      \newpage%
    \fi%
  \else%
    \newpage%
  \fi}
```

s@blocks@facultyLogo@monochrome

The \thesis@blocks@facultyLogo@monochrome[⟨*options*⟩] macro typesets the \thesis@logopath\thesis@facultyLogo logo with the given *options* passed to \includegraphics.

```
\newcommand{\thesis@blocks@facultyLogo@monochrome}[1]%
  [width=40mm]{{%
    \edef\@path{\thesis@logopath\thesis@facultyLogo}%
    \includegraphics[#1]{\@path}}}
```

thesis@blocks@facultyLogo@color

The \thesis@blocks@facultyLogo@color[⟨*options*⟩] macro typesets either the \thesis@logopath\thesis@facultyLogo logo, if the \ifthesis@color@ conditional is false, or the \thesis@logopath\thesis@facultyLogo-color logo otherwise with the given *options* passed to \includegraphics.

```
\newcommand{\thesis@blocks@facultyLogo@color}[1]%
  [width=40mm]{{%
    \edef\@path{\thesis@logopath\thesis@facultyLogo%
      \ifthesis@color@-color\fi}%
    \includegraphics[#1]{\@path}}}
```

locks@universityLogo@monochrome

The \thesis@blocks@universityLogo@monochrome[⟨*options*⟩] macro typesets the \thesis@logopath\thesis@universityLogo logo with the given *options* passed to \includegraphics.

```
\newcommand{\thesis@blocks@universityLogo@monochrome}[1]%
  [width=40mm]{{%
    \edef\@path{\thesis@logopath\thesis@universityLogo}%
    \includegraphics[#1]{\@path}}}
```

esis@blocks@universityLogo@color

The \thesis@blocks@universityLogo@color[⟨*options*⟩] macro typesets either the \thesis@logopath\thesis@universityLogo logo, if the \ifthesis@color@ conditional is false, or the \thesis@logopath\thesis@universityLogo-color logo otherwise with the given *options* passed to \includegraphics.

```
\newcommand{\thesis@blocks@universityLogo@color}[1]%
  [width=40mm]{{%
    \edef\@path{\thesis@logopath\thesis@universityLogo%
      \ifthesis@color@-color\fi}%
    \includegraphics[#1]{\@path}}}
```

\thesis@blocks@cover

The \thesis@blocks@cover macro typesets the thesis cover. It is composed of three macros:

\thesis@blocks@cover@header

- \thesis@blocks@cover@header – The header of the cover page

\thesis@blocks@cover@content

- \thesis@blocks@cover@content – The content of the cover page

\thesis@blocks@cover@footer

- \thesis@blocks@cover@footer – The footer of the cover page

This allows the subsequently loaded style files to only redefine certain parts of the cover page.

```
\def\thesis@blocks@cover{%
  \ifthesis@cover@%
```

```
  \thesis@blocks@clear%
  \ifthesis@twoside@\@twosidefalse\fi % Temporarily disable twoside
  \begin{alwayssingle}%
    \thispagestyle{empty}%
    \begin{center}%
      \thesis@blocks@cover@header%
      \thesis@blocks@facultyLogo@monochrome\\[0.4in]%
      \let\footnotesize\small%
      \let\footnoterule\relax{}%
      \thesis@blocks@cover@content%
      \par\vfill%
      \thesis@blocks@cover@footer%
    \end{center}%
  \end{alwayssingle}%
  \ifthesis@twoside@\@twosidetrue\fi % Re-enable twoside
\fi}
```

The output of the `\thesis@blocks@cover@header` macro is controlled by the following conditionals:

1. `\ifthesis@blocks@cover@university@` – This conditional expression determines, whether the university name is going to be included in the header of the cover. The default value of this conditional is `true`.

2. `\ifthesis@blocks@cover@faculty@` – This conditional expression determines, whether the faculty name is going to be included in the header of the cover. The default value of this conditional is `true`.

3. `\ifthesis@blocks@cover@department@` – This conditional expression determines, whether the department name is going to be included in the header of the cover. The default value of this conditional is `false`.

4. `\ifthesis@blocks@cover@field@` – This conditional expression determines, whether the field of study is going to be included in the header of the cover. The default value of this conditional is `false`.

The sebsequently loaded style files can modify the value of these conditionals to alter the output of the `\thesis@blocks@cover@header` macro without altering its definition.

```
\newif\ifthesis@blocks@cover@university@
\thesis@blocks@cover@university@true
\newif\ifthesis@blocks@cover@faculty@
\thesis@blocks@cover@faculty@true
\newif\ifthesis@blocks@cover@department@
\thesis@blocks@cover@department@false
\newif\ifthesis@blocks@cover@field@
\thesis@blocks@cover@field@false

\def\thesis@blocks@cover@header{%
  {\sc\ifthesis@blocks@cover@university@%
```

```
        \thesis@titlePage@LARGE\thesis@@{universityName}\\%
   \fi\ifthesis@blocks@cover@faculty@%
        \thesis@titlePage@Large\thesis@@{facultyName}\\%
   \fi\ifthesis@blocks@cover@department@%
        \thesis@titlePage@large\thesis@department\\%
      \fi}
  \ifthesis@blocks@cover@field@%
    {\thesis@titlePage@large\vskip 1em%
      {\bf\thesis@@{fieldTitle}:} \thesis@field}%
  \fi\vskip 2em}
\def\thesis@blocks@cover@content{%
  {\thesis@titlePage@Huge\bf\thesis@TeXtitle\par\vfil}%
  \vskip 0.8in%
  {\thesis@titlePage@large\sc\thesis@@{typeName}}\\[0.3in]%
  {\thesis@titlePage@Large\bf\thesis@author}}
\def\thesis@blocks@cover@footer{%
  {\thesis@titlePage@large\thesis@place, \thesis@@{semester}}}
```

`\thesis@blocks@titlePage` The `\thesis@blocks@titlePage` macro typesets the thesis title page. It is composed of three macros:

- `\thesis@blocks@titlePage@header` – The header of the cover page
- `\thesis@blocks@titlePage@content` – The content of the cover page
- `\thesis@blocks@titlePage@footer` – The footer of the cover page

This allows the subsequently loaded style files to only redefine certain parts of the title page.

```
\def\thesis@blocks@titlePage{%
    \thesis@blocks@clear%
    \begin{alwayssingle}%
      \thispagestyle{empty}%
      \begin{center}%
        \thesis@blocks@titlePage@header%
        \thesis@blocks@facultyLogo@color\\[0.4in]%
        \let\footnotesize\small%
        \let\footnoterule\relax{}%
        \thesis@blocks@titlePage@content%
        \par\vfill%
        \thesis@blocks@titlePage@footer%
      \end{center}%
    \end{alwayssingle}}
```

The output of the `\thesis@blocks@titlePage@header` macro is controlled by the following conditionals:

1. `\ifthesis@blocks@titlePage@university@` – This conditional expression determines, whether the university name is going to be included in the header of the title page. The default value of this conditional is `true`.

2. \ifthesis@blocks@titlePage@faculty@ – This conditional expression determines, whether the faculty of study is going to be included in the header of the title page. The default value of this conditional is true.

3. \ifthesis@blocks@titlePage@department@ – This conditional expression determines, whether the department name is going to be included in the header of the title page. The default value of this conditional is false.

4. \ifthesis@blocks@titlePage@field@ – This conditional expression determines, whether the field of study is going to be included in the header of the title page. The default value of this conditional is false.

The sebsequently loaded style files can modify the value of these conditionals to alter the output of the \thesis@blocks@titlePage@header macro without altering its definition.

```
\newif\ifthesis@blocks@titlePage@university@
\thesis@blocks@titlePage@university@true
\newif\ifthesis@blocks@titlePage@faculty@
\thesis@blocks@titlePage@faculty@true
\newif\ifthesis@blocks@titlePage@department@
\thesis@blocks@titlePage@department@false
\newif\ifthesis@blocks@titlePage@field@
\thesis@blocks@titlePage@field@false

\def\thesis@blocks@titlePage@header{%
  {\sc\ifthesis@blocks@titlePage@university@%
        \thesis@titlePage@LARGE\thesis@@{universityName}\\%
   \fi\ifthesis@blocks@titlePage@faculty@%
        \thesis@titlePage@Large\thesis@@{facultyName}\\%
   \fi\ifthesis@blocks@titlePage@department@%
        \thesis@titlePage@large\thesis@department\\%
      \fi}
  \ifthesis@blocks@titlePage@field@%
    {\thesis@titlePage@large\vskip 1em%
      {\bf\thesis@@{fieldTitle}:} \thesis@field}%
  \fi\vskip 2em}
\let\thesis@blocks@titlePage@content=\thesis@blocks@cover@content
\let\thesis@blocks@titlePage@footer=\thesis@blocks@cover@footer
```

\thesis@blocks@tables

The \thesis@blocks@tables macro typesets the table of contents and optionally the \listoftables and the \listoffigures.

```
\def\thesis@blocks@tables{%
  \thesis@blocks@clear%
  \tableofcontents%
  \thesis@blocks@lot%
  \thesis@blocks@lof}
```

\thesis@blocks@declaration

The \thesis@blocks@declaration macro typesets the declaration text.

```
\def\thesis@blocks@declaration{%
```

```
  \thesis@blocks@clear%
  \begin{alwayssingle}%
    \chapter*{\thesis@@{declarationTitle}}%
    \thesis@declaration%
    \vskip 2cm%
    \hfill\thesis@author%
  \end{alwayssingle}}
```

`\thesis@blocks@thanks` The `\thesis@blocks@thanks` macro typesets the acknowledgement, if the `\thesis@thanks` macro is defined. Otherwise, the macro produces no output.

```
\def\thesis@blocks@thanks{%
  \ifx\thesis@thanks\undefined\else%
    \thesis@blocks@clear%
    \begin{alwayssingle}%
      \chapter*{\vspace*{\fill}\thesis@@{thanksTitle}}%
      \thesis@thanks%
    \end{alwayssingle}%
  \fi}
```

`\thesis@blocks@abstract` The `\thesis@blocks@abstract` macro typesets the abstract.

```
\def\thesis@blocks@abstract{%
  \begin{alwayssingle}%
    % Start the new chapter without clearing the right page
    {\def\cleardoublepage{}
    \chapter*{\thesis@@{abstractTitle}}}%
    \noindent\thesis@abstract%
    \par\vfil\null%
  \end{alwayssingle}}
```

`\thesis@blocks@abstractEn` The `\thesis@blocks@abstractEn` macro typesets the abstract in English. If the current locale is English, the macro produces no output.

```
\def\thesis@blocks@abstractEn{%
  \ifthesis@english\else%
    {\thesis@selectLocale{english}%
    \begin{alwayssingle}%
      % Start the new chapter without clearing the right page
      {\def\cleardoublepage{}%
      \chapter*{\thesis@english@abstractTitle}%
      \thesis@abstractEn}%
      \par\vfil\null%
    \end{alwayssingle}}%
  \fi}
```

`\thesis@blocks@keywords` The `\thesis@blocks@keywords` macro typesets the keywords.

```
\def\thesis@blocks@keywords{%
  \begin{alwayssingle}%
    % Start the new chapter without clearing the right page
    {\def\cleardoublepage{}%
    \chapter*{\thesis@@{keywordsTitle}}%
```

```
    \noindent\thesis@TeXkeywords}%
    \par\vfil\null%
  \end{alwayssingle}}
```

\thesis@blocks@keywordsEn

The \thesis@blocks@keywordsEn macro typesets the keywords in English. If the current locale is English, the macro produces no output.

```
\def\thesis@blocks@keywordsEn{%
  \ifthesis@english\else%
    {\thesis@selectLocale{english}%
    \begin{alwayssingle}%
      % Start the new chapter without clearing the right page
      {\def\cleardoublepage{}%
      \chapter*{\thesis@english@keywordsTitle}%
      \thesis@TeXkeywordsEn}%
      \par\vfil\null%
    \end{alwayssingle}}%
  \fi}
```

\thesis@blocks@assignment

The \thesis@blocks@assignment macro either:

- Produces no output, when the first expansion of \thesis@assignmentPDF yields an empty token list or when the \ifthesis@blocks@assignment@ conditional is false.
- Typesets a placeholder page to be replaced with the official thesis assignment, when \thesis@assignmentPDF is undefined and the \ifthesis@blocks@assignment@ conditional is true.
- Injects the PDF file(s) specified within the \thesis@assignmentPDF macro, when \thesis@assignmentPDF is defined, its first expansion yields a non-empty token list and the \ifthesis@blocks@assignment@ conditional is true.

\ifthesis@blocks@assignment@

The default value of the \ifthesis@blocks@assignment@ conditional is true.

```
\newif\ifthesis@blocks@assignment@
\thesis@blocks@assignment@true
\def\thesis@blocks@assignment{%
  \ifthesis@blocks@assignment@%
    \ifx\thesis@assignmentFiles\undefined%
      % Typeset a placeholder page.
      \thesis@blocks@clear%
      \begin{alwayssingle}%
        \thispagestyle{empty}%
        \addtocounter{page}{-\ifthesis@twoside@2\else1\fi}%
        \noindent\textit{\thesis@@{assignment}}%
      \end{alwayssingle}%
    \else%
      {\edef\@pdfList{\thesis@assignmentFiles}%
      \ifx\@pdfList\empty\else
        \let\ea\expandafter
```

```
        % Inject the specified PDF documents.
        \def\@inject##1,{\thesis@blocks@clear
          \def\@args{##1}\def\@relax{\relax}%
          \ifx\@args\@relax\else%
            % Trim leading spaces.
            \edef\@trimmed{\romannumeral-`\.##1}%
            \includepdf[pages=-]\@trimmed
            \ea\@inject\fi}%
        \ea\@inject\@pdfList,\relax,%
      \fi}%
    \fi%
  \fi}
```

`\thesis@blocks@mainMatter` The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis.

```
\def\thesis@blocks@mainMatter{%
  \thesis@blocks@clear
  \setcounter{page}{1}
  \pagenumbering{arabic}
  \pagestyle{thesisheadings}
  \parindent 1.5em\relax}
```

The rest of the file comprises redefinitions of LaTeX commands and private `rapport3` class macros altering the layout of the resulting document. Depending on the type size of 10, 11 or 12 points, either the `fithesis-10.clo`, `fithesis-11.clo` or `fithesis-12.clo` file is loaded from the `\thesis@stylepath mu` directory, respectively.

```
% Table of contents will contain sectioning commands up to
% \subsubsection
\setcounter{tocdepth}{4}

% Load the `fithesis-1*.clo` size option
\input\thesis@stylepath mu/fithesis-1\thesis@ptsize.clo\relax

\def\ps@thesisheadings{%
\def\chaptermark##1{%
\markright{%
\ifnum\c@secnumdepth >\m@ne
\thechapter.\ %
\fi ##1}}
\let\@oddfoot\@empty
\let\@oddhead\@empty
\def\@oddhead{\vbox{\hbox to \textwidth{%
\hfil{\sc\rightmark}}\vskip 4pt\hrule}}
\if@twoside
 \def\@evenhead{\vbox{\hbox to \textwidth{%
 {\sc\rightmark}\hfil}\vskip 4pt\hrule}}
\else
 \let\@evenhead\@oddhead
```

```
\fi
\def\@oddfoot{\hfil\PageFont\thepage}
\if@twoside
 \def\@evenfoot{\PageFont\thepage\hfil}%
\else
 \let\@evenfoot\@oddfoot
\fi
\let\@mkboth\markboth
}

% Redefines the style of the chapter headings
\renewcommand*\chapter{%
\if@twoside
 \clearpage
 \thispagestyle{empty}
 \cleardoublepage
\else
 \clearpage
\fi
\thispagestyle{plain}%
\global\@topnum\z@
\@afterindentfalse
\secdef\@chapter\@schapter}

% Redefines the style of part headings
\renewcommand*\part{%
\clearpage
\thispagestyle{empty}
\cleardoublepage
\thispagestyle{empty}%
\if@twocolumn%
 \onecolumn
 \@tempswatrue
\else
 \@tempswafalse
\fi
\hbox{}\vfil
\secdef\@part\@spart}

\newif\if@restonecol
\def\alwayssingle{%
  \@restonecolfalse\if@twocolumn\@restonecoltrue\onecolumn\fi}
\def\endalwayssingle{\if@restonecol\twocolumn\fi}

\renewcommand*\l@part[2]{%
  \ifnum \c@tocdepth >-2\relax
    \addpenalty{-\@highpenalty}%
    \addvspace{0.5em \@plus\p@}%
    \begingroup
      \setlength\@tempdima{3em}%
```

```
      \parindent \z@ \rightskip \@pnumwidth
      \parfillskip -\@pnumwidth
      {\leavevmode
       \normalfont \bfseries #1\hfil \hb@xt@\@pnumwidth{\hss #2}}\par
       \nobreak
         \global\@nobreaktrue
         \everypar{\global\@nobreakfalse\everypar{}}%
    \endgroup
    \addvspace{0.2em \@plus\p@}%
  \fi}

\renewcommand*\l@chapter[2]{%
  \ifnum \c@tocdepth >\m@ne
    \addpenalty{-\@highpenalty}%
    \vskip 1.0em \@plus\p@
    \setlength\@tempdima{1.5em}%
    \begingroup
      \parindent \z@ \rightskip \@pnumwidth
      \parfillskip -\@pnumwidth
      \leavevmode \bfseries
      \advance\leftskip\@tempdima
      \hskip -\leftskip
      #1\nobreak\hfil \nobreak\hb@xt@\@pnumwidth{\hss #2}\par
      \penalty\@highpenalty
    \endgroup
  \fi}

\renewcommand*\l@chapter{\@dottedtocline{1}{0em}{1.5em}}
\renewcommand*\l@section{\@dottedtocline{2}{1.5em}{2.3em}}
\renewcommand*\l@subsection{\@dottedtocline{3}{3.8em}{3.2em}}
\renewcommand*\l@subsubsection{\@dottedtocline{4}{7.0em}{3.8em}}
```

3.6.2.3 The `style/mu/fithesis-10.clo` file

This file is conditionally loaded by the `style/mu/base.sty` file to redefine the page geometry to match the type size of 10 points.

```
⟨*opt⟩
⟨*10pt⟩
\ProvidesFile{fithesis/style/mu/fithesis-10.clo}[2015/06/23]

\renewcommand{\normalsize}{\fontsize\@xpt{12}\selectfont%
\abovedisplayskip 10\p@ plus2\p@ minus5\p@
\belowdisplayskip \abovedisplayskip
\abovedisplayshortskip  \z@ plus3\p@
\belowdisplayshortskip  6\p@ plus3\p@ minus3\p@
\let\@listi\@listI}

\renewcommand{\small}{\fontsize\@ixpt{11}\selectfont%
\abovedisplayskip 8.5\p@ plus3\p@ minus4\p@
\belowdisplayskip \abovedisplayskip
```

```
\abovedisplayshortskip \z@ plus2\p@
\belowdisplayshortskip 4\p@ plus2\p@ minus2\p@
\def\@listi{\leftmargin\leftmargini
\topsep 4\p@ plus2\p@ minus2\p@\parsep 2\p@ plus\p@ minus\p@
\itemsep \parsep}}

\renewcommand{\footnotesize}{\fontsize\@viiipt{9.5}\selectfont%
\abovedisplayskip 6\p@ plus2\p@ minus4\p@
\belowdisplayskip \abovedisplayskip
\abovedisplayshortskip \z@ plus\p@
\belowdisplayshortskip 3\p@ plus\p@ minus2\p@
\def\@listi{\leftmargin\leftmargini %% Added 22 Dec 87
\topsep 3\p@ plus\p@ minus\p@\parsep 2\p@ plus\p@ minus\p@
\itemsep \parsep}}

\renewcommand{\scriptsize}{\fontsize\@viipt{8pt}\selectfont}
\renewcommand{\tiny}{\fontsize\@vpt{6pt}\selectfont}
\renewcommand{\large}{\fontsize\@xiipt{14pt}\selectfont}
\renewcommand{\Large}{\fontsize\@xivpt{18pt}\selectfont}
\renewcommand{\LARGE}{\fontsize\@xviipt{22pt}\selectfont}
\renewcommand{\huge}{\fontsize\@xxpt{25pt}\selectfont}
\renewcommand{\Huge}{\fontsize\@xxvpt{30pt}\selectfont}

⟨/10pt⟩
```

3.6.2.4 The `style/mu/fithesis-11.clo` file

This file is conditionally loaded by the `style/mu/base.sty` file to redefine the page geometry to match the type size of 11 points.

```
⟨*11pt⟩
\ProvidesFile{fithesis/style/mu/fithesis-11.clo}[2015/06/23]

\renewcommand{\normalsize}{\fontsize\@xipt{14}\selectfont%
\abovedisplayskip 11\p@ plus3\p@ minus6\p@
\belowdisplayskip \abovedisplayskip
\belowdisplayshortskip  6.5\p@ plus3.5\p@ minus3\p@
%\abovedisplayshortskip  \z@ plus3\@p
\let\@listi\@listI}

\renewcommand{\small}{\fontsize\@xpt{12}\selectfont%
\abovedisplayskip 10\p@ plus2\p@ minus5\p@
\belowdisplayskip \abovedisplayskip
\abovedisplayshortskip  \z@ plus3\p@
\belowdisplayshortskip  6\p@ plus3\p@ minus3\p@
\def\@listi{\leftmargin\leftmargini
\topsep 6\p@ plus2\p@ minus2\p@\parsep 3\p@ plus2\p@ minus\p@
\itemsep \parsep}}

\renewcommand{\footnotesize}{\fontsize\@ixpt{11}\selectfont%
\abovedisplayskip 8\p@ plus2\p@ minus4\p@
```

```
\belowdisplayskip \abovedisplayskip
\abovedisplayshortskip \z@ plus\p@
\belowdisplayshortskip 4\p@ plus2\p@ minus2\p@
\def\@listi{\leftmargin\leftmargini
\topsep 4\p@ plus2\p@ minus2\p@\parsep 2\p@ plus\p@ minus\p@
\itemsep \parsep}}

\renewcommand{\scriptsize}{\fontsize\@viiipt{9.5pt}\selectfont}
\renewcommand{\tiny}{\fontsize\@vipt{7pt}\selectfont}
\renewcommand{\large}{\fontsize\@xiipt{14pt}\selectfont}
\renewcommand{\Large}{\fontsize\@xivpt{18pt}\selectfont}
\renewcommand{\LARGE}{\fontsize\@xviipt{22pt}\selectfont}
\renewcommand{\huge}{\fontsize\@xxpt{25pt}\selectfont}
\renewcommand{\Huge}{\fontsize\@xxvpt{30pt}\selectfont}

⟨/11pt⟩
```

3.6.2.5 The `style/mu/fithesis-12.clo` file

This file is conditionally loaded by the `style/mu/base.sty` file to redefine the page geometry to match the type size of 12 points. The type dimensions defined by the file are stored in the following macros as well:

`\thesis@titlePage@normalsize` • `\thesis@titlePage@normalsize` – Equivalent to `\normalsize`

`\thesis@titlePage@small` • `\thesis@titlePage@small` – Equivalent to `\small`

`\thesis@titlePage@footnotesize` • `\thesis@titlePage@footnotesize` – Equivalent to `\footnotesize`

`\thesis@titlePage@scriptsize` • `\thesis@titlePage@scriptsize` – Equivalent to `\scriptsize`

`\thesis@titlePage@tiny` • `\thesis@titlePage@tiny` – Equivalent to `\tiny`

`\thesis@titlePage@large` • `\thesis@titlePage@large` – Equivalent to `\large`

`\thesis@titlePage@Large` • `\thesis@titlePage@Large` – Equivalent to `\Large`

`\thesis@titlePage@LARGE` • `\thesis@titlePage@LARGE` – Equivalent to `\LARGE`

`\thesis@titlePage@huge` • `\thesis@titlePage@huge` – Equivalent to `\huge`

`\thesis@titlePage@Huge` • `\thesis@titlePage@Huge` – Equivalent to `\Huge`

These macros can be used to typeset elements, whose size should remain constant regardless of the font size setting.

```
⟨*12pt⟩
\ProvidesFile{fithesis/style/mu/fithesis-12.clo}[2015/06/23]
⟨/12pt⟩

\def\thesis@titlePage@normalsize{\fontsize\@xiipt{14.5}%
\selectfont\abovedisplayskip 12\p@ plus3\p@ minus7\p@
\belowdisplayskip \abovedisplayskip
```

```
\abovedisplayshortskip  \z@ plus3\p@
\belowdisplayshortskip  6.5\p@ plus3.5\p@ minus3\p@
\let\@listi\@listI}

\def\thesis@titlePage@small{\fontsize\@xipt{13.6}\selectfont%
\abovedisplayskip 11\p@ plus3\p@ minus6\p@
\belowdisplayskip \abovedisplayskip
\abovedisplayshortskip  \z@ plus3\p@
\belowdisplayshortskip  6.5\p@ plus3.5\p@ minus3\p@
\def\@listi{\leftmargin\leftmargini %% Added 22 Dec 87
\parsep 4.5\p@ plus2\p@ minus\p@
            \itemsep \parsep
            \topsep 9\p@ plus3\p@ minus5\p@}}

\def\thesis@titlePage@footnotesize{\fontsize\@xpt{12}\selectfont%
\abovedisplayskip 10\p@ plus2\p@ minus5\p@
\belowdisplayskip \abovedisplayskip
\abovedisplayshortskip  \z@ plus3\p@
\belowdisplayshortskip  6\p@ plus3\p@ minus3\p@
\def\@listi{\leftmargin\leftmargini %% Added 22 Dec 87
\topsep 6\p@ plus2\p@ minus2\p@\parsep 3\p@ plus2\p@ minus\p@
\itemsep \parsep}}

\def\thesis@titlePage@scriptsize{\fontsize\@viiipt{9.5pt}\selectfont}
\def\thesis@titlePage@tiny{\fontsize\@vipt{7pt}\selectfont}
\def\thesis@titlePage@large{\fontsize\@xivpt{18pt}\selectfont}
\def\thesis@titlePage@Large{\fontsize\@xviipt{22pt}\selectfont}
\def\thesis@titlePage@LARGE{\fontsize\@xxpt{25pt}\selectfont}
\def\thesis@titlePage@huge{\fontsize\@xxvpt{30pt}\selectfont}
\def\thesis@titlePage@Huge{\fontsize\@xxvpt{30pt}\selectfont}

⟨*12pt⟩
\renewcommand{\normalsize}{\thesis@titlePage@normalsize}
\renewcommand{\small}{\thesis@titlePage@small}
\renewcommand{\footnotesize}{\thesis@titlePage@footnotesize}
\renewcommand{\scriptsize}{\thesis@titlePage@scriptsize}
\renewcommand{\tiny}{\thesis@titlePage@tiny}
\renewcommand{\large}{\thesis@titlePage@large}
\renewcommand{\Large}{\thesis@titlePage@Large}
\renewcommand{\LARGE}{\thesis@titlePage@LARGE}
\renewcommand{\huge}{\thesis@titlePage@huge}
\renewcommand{\Huge}{\thesis@titlePage@Huge}
⟨/12pt⟩
\let\@normalsize\normalsize
\normalsize

\if@twoside
   \oddsidemargin 0.75in
   \evensidemargin 0.4in
   \marginparwidth 0pt
```

```
\else
   \oddsidemargin 0.75in
   \evensidemargin 0.75in
   \marginparwidth 0pt
\fi
\marginparsep 10pt

\topmargin 0.4in

\headheight 20pt
\headsep 10pt
\topskip 10pt
\footskip 30pt

⟨*10pt⟩
\textheight = 43\baselineskip
\advance\textheight by \topskip
\textwidth 5.0truein
\columnsep 10pt
\columnseprule 0pt

\footnotesep 6.65pt
\skip\footins 9pt plus 4pt minus 2pt
\floatsep 12pt plus 2pt minus 2pt
\textfloatsep 20pt plus 2pt minus 4pt
\intextsep 12pt plus 2pt minus 2pt
\dblfloatsep 12pt plus 2pt minus 2pt
\dbltextfloatsep 20pt plus 2pt minus 4pt

\@fptop 0pt plus 1fil
\@fpsep 8pt plus 2fil
\@fpbot 0pt plus 1fil
\@dblfptop 0pt plus 1fil
\@dblfpsep 8pt plus 2fil
\@dblfpbot 0pt plus 1fil
\marginparpush 5pt

\parskip 0pt plus 1pt
\partopsep 2pt plus 1pt minus 1pt

⟨/10pt⟩
%
⟨*11pt⟩
\textheight = 39\baselineskip
\advance\textheight by \topskip
\textwidth 5.0truein
\columnsep 10pt
\columnseprule 0pt

\footnotesep 7.7pt
```

```
\skip\footins 10pt plus 4pt minus 2pt
\floatsep 12pt plus 2pt minus 2pt
\textfloatsep 20pt plus 2pt minus 4pt
\intextsep 12pt plus 2pt minus 2pt
\dblfloatsep 12pt plus 2pt minus 2pt
\dbltextfloatsep 20pt plus 2pt minus 4pt

\@fptop 0pt plus 1fil
\@fpsep 8pt plus 2fil
\@fpbot 0pt plus 1fil
\@dblfptop 0pt plus 1fil
\@dblfpsep 8pt plus 2fil
\@dblfpbot 0pt plus 1fil
\marginparpush 5pt

\parskip 0pt plus 0pt
\partopsep 3pt plus 1pt minus 2pt

⟨/11pt⟩
%
⟨*12pt⟩
\textheight = 37\baselineskip
\advance\textheight by \topskip
\textwidth 5.0truein
\columnsep 10pt
\columnseprule 0pt

\footnotesep 8.4pt
\skip\footins 10.8pt plus 4pt minus 2pt
\floatsep 14pt plus 2pt minus 4pt
\textfloatsep 20pt plus 2pt minus 4pt
\intextsep 14pt plus 4pt minus 4pt
\dblfloatsep 14pt plus 2pt minus 4pt
\dbltextfloatsep 20pt plus 2pt minus 4pt

\@fptop 0pt plus 1fil
\@fpsep 10pt plus 2fil
\@fpbot 0pt plus 1fil
\@dblfptop 0pt plus 1fil
\@dblfpsep 10pt plus 2fil
\@dblfpbot 0pt plus 1fil
\marginparpush 7pt

\parskip 0pt plus 0pt
\partopsep 3pt plus 2pt minus 2pt

⟨/12pt⟩
\@lowpenalty   51
\@medpenalty  151
\@highpenalty 301
```

```
\@beginparpenalty -\@lowpenalty
\@endparpenalty   -\@lowpenalty
\@itempenalty     -\@lowpenalty

\def\@makechapterhead#1{%
  {%
    \setlength\parindent{\z@}%
    \setlength\parskip  {\z@}%
    \ifnum
      \c@secnumdepth >\m@ne
      \par\nobreak
      \vskip 10\p@
    \fi
    \Large \ChapFont \thechapter{} \space #1\par
    \nobreak
    \vskip 20\p@
  }%
}

\def\@makeschapterhead#1{%
  {%
    \setlength\parindent{\z@}%
    \setlength\parskip  {\z@}%
    \Large \ChapFont #1\par
    \nobreak
    \vskip 20\p@
  }%
}

\def\chapter{%
   \clearpage
   \thispagestyle{plain}
   \global\@topnum\z@
   \@afterindentfalse
   \secdef\@chapter\@schapter
 }

\def\@chapter[#1]#2{%
  \ifnum \c@secnumdepth
    >\m@ne
    \refstepcounter{chapter}%
    \typeout{\@chapapp\space\thechapter.}%
    \addcontentsline{toc}{chapter}{\protect
    \numberline{\thechapter}\bfseries #1}
  \else%
    \addcontentsline{toc}{chapter}{\bfseries #1}
  \fi
  \chaptermark{#1}%
  \addtocontents{lof}%
  {\protect\addvspace{4\p@}}
```

```
  \addtocontents{lot}%
  {\protect\addvspace{4\p@}}
  \if@twocolumn
    \@topnewpage[\@makechapterhead{#2}]%
  \else
    \@makechapterhead{#2}%
    \@afterheading
  \fi
}

%\def\@schapter#1{\if@twocolumn \@topnewpage[\@makeschapterhead{#1}]%
%        \else \@makeschapterhead{#1}%
%              \markright{#1}
%              \@afterheading\fi}

\def\section{\@startsection {section}{1}{\z@}{-3.5ex plus-1ex minus
    -.2ex}{2.3ex plus.2ex}{\reset@font\large\bfseries}}
\def\subsection{\@startsection{subsection}{2}{\z@}{-3.25ex plus-1ex
    minus-.2ex}{1.5ex plus.2ex}{\reset@font\normalsize\bfseries}}
\def\subsubsection{\@startsection{subsubsection}{3}{\z@}{-3.25ex plus
    -1ex minus-.2ex}{1.5ex plus.2ex}{\reset@font\normalsize}}
\def\paragraph{\@startsection
    {paragraph}{4}{\z@}{3.25ex plus1ex minus.2ex}{-1em}{\reset@font
    \normalsize\bfseries}}
\def\subparagraph{\@startsection
     {subparagraph}{4}{\parindent}{3.25ex plus1ex minus
     .2ex}{-1em}{\reset@font\normalsize\bfseries}}

\setcounter{secnumdepth}{2}

\def\appendix{\par
  \setcounter{chapter}{0}%
  \setcounter{section}{0}%
  \def\@chapapp{\appendixname}%
  \def\thechapter{\Alph{chapter}}}

\leftmargini 2.5em
\leftmarginii 2.2em     % > \labelsep + width of '(m)'
\leftmarginiii 1.87em   % > \labelsep + width of 'vii.'
\leftmarginiv 1.7em     % > \labelsep + width of 'M.'
\leftmarginv 1em
\leftmarginvi 1em

\leftmargin\leftmargini
\labelsep .5em
\labelwidth\leftmargini\advance\labelwidth-\labelsep

⟨*10pt⟩
\def\@listI{\leftmargin\leftmargini \parsep 4\p@ plus2\p@ minus\p@%
\topsep 8\p@ plus2\p@ minus4\p@
```

```
\itemsep 4\p@ plus2\p@ minus\p@}

\let\@listi\@listI
\@listi

\def\@listii{\leftmargin\leftmarginii
   \labelwidth\leftmarginii\advance\labelwidth-\labelsep
   \topsep 4\p@ plus2\p@ minus\p@
   \parsep 2\p@ plus\p@ minus\p@
   \itemsep \parsep}

\def\@listiii{\leftmargin\leftmarginiii
    \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
    \topsep 2\p@ plus\p@ minus\p@
    \parsep \z@ \partopsep\p@ plus\z@ minus\p@
    \itemsep \topsep}

\def\@listiv{\leftmargin\leftmarginiv
     \labelwidth\leftmarginiv\advance\labelwidth-\labelsep}

\def\@listv{\leftmargin\leftmarginv
     \labelwidth\leftmarginv\advance\labelwidth-\labelsep}

\def\@listvi{\leftmargin\leftmarginvi
     \labelwidth\leftmarginvi\advance\labelwidth-\labelsep}
⟨/10pt⟩
%
⟨*11pt⟩
\def\@listI{\leftmargin\leftmargini \parsep 4.5\p@ plus2\p@ minus\p@
\topsep 9\p@ plus3\p@ minus5\p@
\itemsep 4.5\p@ plus2\p@ minus\p@}

\let\@listi\@listI
\@listi

\def\@listii{\leftmargin\leftmarginii
   \labelwidth\leftmarginii\advance\labelwidth-\labelsep
   \topsep 4.5\p@ plus2\p@ minus\p@
   \parsep 2\p@ plus\p@ minus\p@
   \itemsep \parsep}

\def\@listiii{\leftmargin\leftmarginiii
    \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
    \topsep 2\p@ plus\p@ minus\p@
    \parsep \z@ \partopsep \p@ plus\z@ minus\p@
    \itemsep \topsep}

\def\@listiv{\leftmargin\leftmarginiv
     \labelwidth\leftmarginiv\advance\labelwidth-\labelsep}

```

```
\def\@listv{\leftmargin\leftmarginv
     \labelwidth\leftmarginv\advance\labelwidth-\labelsep}

\def\@listvi{\leftmargin\leftmarginvi
     \labelwidth\leftmarginvi\advance\labelwidth-\labelsep}
⟨/11pt⟩
%
⟨*12pt⟩
\def\@listI{\leftmargin\leftmargini \parsep 5\p@ plus2.5\p@ minus\p@
\topsep 10\p@ plus4\p@ minus6\p@
\itemsep 5\p@ plus2.5\p@ minus\p@}

\let\@listi\@listI
\@listi

\def\@listii{\leftmargin\leftmarginii
   \labelwidth\leftmarginii\advance\labelwidth-\labelsep
   \topsep 5\p@ plus2.5\p@ minus\p@
   \parsep 2.5\p@ plus\p@ minus\p@
   \itemsep \parsep}

\def\@listiii{\leftmargin\leftmarginiii
    \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
    \topsep 2.5\p@ plus\p@ minus\p@
    \parsep \z@ \partopsep \p@ plus\z@ minus\p@
    \itemsep \topsep}

\def\@listiv{\leftmargin\leftmarginiv
     \labelwidth\leftmarginiv\advance\labelwidth-\labelsep}

\def\@listv{\leftmargin\leftmarginv
     \labelwidth\leftmarginv\advance\labelwidth-\labelsep}

\def\@listvi{\leftmargin\leftmarginvi
     \labelwidth\leftmarginvi\advance\labelwidth-\labelsep}
⟨/12pt⟩
⟨/opt⟩
```

3.6.3 The style files of the Faculty of Informatics

3.6.3.1 The `style/mu/fithesis-fi.sty` file

This is the style file for the theses written at the Faculty of Informatics at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty[1].

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-fi}[2015/06/27]
```

[1] See http://www.fi.muni.cz/docs/BP_DP_na_FI.pdf

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{FFD451},
  tableEmph={HTML}{FFD451},
  tableOdd={HTML}{FFF9E5},
  tableEven={HTML}{FFECB3}}
```

In case of rigorous and doctoral theses, the style file hides the thesis assignment in accordance with the formal requirements of the faculty.

```
\ifx\thesis@type\thesis@bachelors\else
\ifx\thesis@type\thesis@masters\else
  \thesis@blocks@assignment@false
\fi\fi
```

`\thesis@blocks@titlePage` The style file redefines the cover and title page footers to include the thesis advisor's name and signature in case of a rigorous thesis. Along with the macros required by the locale file interface, the locale files need to define the following macros:

`\thesis@advisorSignature`

- `\thesis@advisorSignature` – The label of the advisor signature field typeset in the case of rigorous theses

```
\def\thesis@blocks@titlePage@content{%
    {\thesis@titlePage@Huge\bf\thesis@TeXtitle\par\vfil}\vskip 0.8in
    {\thesis@titlePage@large\sc\thesis@@{typeName}\\[0.3in]}
    {\thesis@titlePage@Large\bf\thesis@author}
    % If this is a rigorous thesis, typeset the name of the
    % thesis advisor.
    \ifx\thesis@type\thesis@rigorous%
      {\thesis@titlePage@large\\[0.3in]
        {\bf\thesis@@{advisorTitle}:} \thesis@advisor}
    \fi}%
\def\thesis@blocks@titlePage@footer{%
  {\thesis@titlePage@large\thesis@place, \thesis@@{semester}
  % If this is a rigorous thesis, create space for the advisor's
  % signature
  \ifx\thesis@type\thesis@rigorous%
    \let\@A\relax\newlength{\@A}
      \settowidth{\@A}{\thesis@@{advisorSignature}}
      \setlength{\@A}{\@A+1cm}
    \hfill\raisebox{-0.5em}{\parbox{\@A}{
      \centering
      \rule{\@A}{1pt}\\
      \thesis@@{advisorSignature}
    }}
  \fi}}
```

`\thesis@blocks@declaration` The `\thesis@blocks@declaration` macro typesets the declaration text. Compared to the definition within the `style/mu/base.sty` file, this macro also typesets the advisor's name at the bottom of the page.

```
\def\thesis@blocks@declaration{%
  \thesis@blocks@clear%
  \begin{alwayssingle}%
    \chapter*{\thesis@@{declarationTitle}}%
    \thesis@declaration%
    \vskip 2cm%
    \hfill\thesis@author%
    \par\vfill%
    \textbf{\thesis@@{advisorTitle}:} \thesis@advisor%
    \par\vfil%
  \end{alwayssingle}}
```

All blocks within the autolayout preamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
\def\thesis@preamble{%
  \thesis@blocks@cover%
  \thesis@blocks@titlePage%
  \thesis@blocks@frontMatter%
    \thesis@blocks@assignment%
    \thesis@blocks@declaration%
    \thesis@blocks@thanks%
    \thesis@blocks@clearRight%
      \thesis@blocks@abstract%
      \thesis@blocks@keywords%
    \thesis@blocks@tables%
  \thesis@blocks@mainMatter}
```

3.6.4 The style files of the Faculty of Science

3.6.4.1 The `style/mu/fithesis-sci.sty` file

This is the style file for the theses written at the Faculty of Science at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty[2].

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-sci}[2015/06/27]
```

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{20E366},
  tableEmph={HTML}{8EDEAA},
  tableOdd={HTML}{EDF7F1},
  tableEven={HTML}{CCEDD8}}
```

The file freely uses Czech locale strings within the macros.

```
\thesis@requireLocale{czech}
```

The file loads the following packages:

- tikz – Used for dimension arithmetic.

[2] See http://www.sci.muni.cz/NW/predpisy/od/OD-2014-05.pdf

- geometry – Used for the modifications of the type area dimensions.

```
\thesis@require{tikz}
\thesis@require{changepage}
```

In case of rigorous and doctoral theses, the style file hides the thesis assignment in accordance with the formal requirements of the faculty.

```
\ifx\thesis@type\thesis@bachelors\else
\ifx\thesis@type\thesis@masters\else
  \thesis@blocks@assignment@false
\fi\fi
```

`\thesis@blocks@bibEntry` The `\thesis@blocks@bibEntry` macro typesets a bibliographical entry. Along with the macros required by the locale file interface, the locale files need to define the following macros:

`\thesis@czech@bib@title`
- `\thesis@czech@bib@title` – The title of the entire block

`\thesis@czech@bib@author`
- `\thesis@czech@bib@author` – The label of the author name entry

`\thesis@czech@bib@title`
- `\thesis@czech@bib@title` – The label of the title name entry

`\thesis@czech@bib@programme`
- `\thesis@czech@bib@programme` – The label of the programme name entry

`\thesis@czech@bib@field`
- `\thesis@czech@bib@field` – The label of the field of study name entry

`\thesis@czech@bib@advisor`
- `\thesis@czech@bib@advisor` – The label of the advisor name entry

`\thesis@czech@bib@academicYear`
- `\thesis@czech@bib@academicYear` – The label of the academic year entry

`\thesis@czech@bib@pages`
- `\thesis@czech@bib@pages` – The label of the number of pages entry

`\thesis@czech@bib@keywords`
- `\thesis@czech@bib@keywords` – The label of the keywords entry

```
\def\thesis@blocks@bibEntry{%
  \begin{alwayssingle}%
    {% Start the new chapter without clearing the right page
    {\def\cleardoublepage{}%
    \chapter*{\thesis@czech@bib@title}}%
    % Calculate the width of the columns
    \let\@A\relax\newlength{\@A}\settowidth{\@A}{{%
      \bf\thesis@czech@bib@author:}}
    \let\@B\relax\newlength{\@B}\settowidth{\@B}{{%
      \bf\thesis@czech@bib@thesisTitle:}}
    \let\@C\relax\newlength{\@C}\settowidth{\@C}{{%
      \bf\thesis@czech@bib@programme:}}
    \let\@D\relax\newlength{\@D}\settowidth{\@D}{{%
      \bf\thesis@czech@bib@field:}}
    % Unless this is a rigorous thesis, we will be typesetting the
    % name of the thesis advisor.
    \let\@E\relax\newlength{\@E}
      \ifx\thesis@type\thesis@rigorous%
```

```
      \setlength{\@E}{0pt}%
    \else%
      \settowidth{\@E}{{\bf\thesis@czech@bib@advisor:}}
    \fi%
  \let\@F\relax\newlength{\@F}\settowidth{\@F}{{%
    \bf\thesis@czech@bib@academicYear:}}
  \let\@G\relax\newlength{\@G}\settowidth{\@G}{{%
    \bf\thesis@czech@bib@pages:}}
  \let\@H\relax\newlength{\@H}\settowidth{\@H}{{%
    \bf\thesis@czech@bib@keywords:}}
  \let\@skip\relax\newlength{\@skip}\setlength{\@skip}{16pt}
  \let\@left\relax\newlength{\@left}\pgfmathsetlength{\@left}{%
    max(\@A,\@B,\@C,\@D,\@E,\@F,\@G,\@H)}
  \let\@right\relax\newlength{\@right}\setlength{\@right}{%
    \textwidth-\@left-\@skip}
  % Typeset the table
  \renewcommand{\arraystretch}{2}
  \noindent\begin{thesis@newtable@old}%
    {@{}p{\@left}@{\hskip\@skip}p{\@right}@{}}
    \textbf{\thesis@czech@bib@author:} &
      \noindent\parbox[t]{\@right}{
        \thesis@author\\
        \thesis@czech@facultyName,
        \thesis@czech@universityName\\
        \thesis@department
      }\\
    \textbf{\thesis@czech@bib@thesisTitle:}
      & \thesis@title \\
    \textbf{\thesis@czech@bib@programme:}
      & \thesis@programme \\
    \textbf{\thesis@czech@bib@field:}
      & \thesis@field \\
    % Unless this is a rigorous thesis, typeset the name of the
    % thesis advisor.
    \ifx\thesis@type\thesis@rigorous\else%
      \textbf{\thesis@czech@bib@advisor:}
        & \thesis@advisor \\
    \fi
    \textbf{\thesis@czech@bib@academicYear:}
      & \thesis@academicYear \\
    \textbf{\thesis@czech@bib@pages:}
      & \thesis@pages \\
    \textbf{\thesis@czech@bib@keywords:}
      & \thesis@TeXkeywords \\
  \end{thesis@newtable@old}}
\end{alwayssingle}}
```

`\thesis@blocks@bibEntryEn` The `\thesis@blocks@bibEntryEn` macro typesets a bibliographical entry in English. Along with the macros required by the locale file interface, the locale files need to define the following macros:

\thesis@english@bib@title
- \thesis@english@bib@title – The title of the entire block

\thesis@english@bib@author
- \thesis@english@bib@author – The label of the author name entry

\thesis@english@bib@title
- \thesis@english@bib@title – The label of the title name entry

\thesis@english@bib@programme
- \thesis@english@bib@programme – The label of the programme name entry

\thesis@english@bib@field
- \thesis@english@bib@field – The label of the field of study name entry

\thesis@english@bib@advisor
- \thesis@english@bib@advisor – The label of the advisor name entry

\thesis@english@bib@academicYear
- \thesis@english@bib@academicYear – The label of the academic year entry

\thesis@english@bib@pages
- \thesis@english@bib@pages – The label of the number of pages entry

\thesis@english@bib@keywords
- \thesis@english@bib@keywords – The label of the keywords entry

```
\def\thesis@blocks@bibEntryEn{%
  {\thesis@selectLocale{english}
  \begin{alwayssingle}
    % Start the new chapter without clearing the right page
    {\def\cleardoublepage{}%
    \chapter*{\thesis@english@bib@title}}%
    {% Calculate the width of the columns
    \let\@A\relax\newlength{\@A}\settowidth{\@A}{{%
      \bf\thesis@english@bib@author:}}
    \let\@B\relax\newlength{\@B}\settowidth{\@B}{{%
      \bf\thesis@english@bib@thesisTitle:}}
    \let\@C\relax\newlength{\@C}\settowidth{\@C}{{%
      \bf\thesis@english@bib@programme:}}
    \let\@D\relax\newlength{\@D}\settowidth{\@D}{{%
      \bf\thesis@english@bib@field:}}
    % Unless this is a rigorous thesis, we will be typesetting
    % the name of the thesis advisor.
    \let\@E\relax\newlength{\@E}
      \ifx\thesis@type\thesis@rigorous%
        \setlength{\@E}{0pt}%
      \else%
        \settowidth{\@E}{{\bf\thesis@english@bib@advisor:}}
      \fi%
    \let\@F\relax\newlength{\@F}\settowidth{\@F}{{%
      \bf\thesis@english@bib@academicYear:}}
    \let\@G\relax\newlength{\@G}\settowidth{\@G}{{%
      \bf\thesis@english@bib@pages:}}
    \let\@H\relax\newlength{\@H}\settowidth{\@H}{{%
      \bf\thesis@english@bib@keywords:}}
    \let\@skip\relax\newlength{\@skip}\setlength{\@skip}{16pt}
    \let\@left\relax\newlength{\@left}\pgfmathsetlength{\@left}{%
      max(\@A,\@B,\@C,\@D,\@E,\@F,\@G,\@H)}
    \let\@right\relax\newlength{\@right}\setlength{\@right}{%
      \textwidth-\@left-\@skip}
```

```
  % Typeset the table
  \renewcommand{\arraystretch}{2}
  \noindent\begin{thesis@newtable@old}%
    {@{}p{\@left}@{\hskip\@skip}p{\@right}@{}}
      \textbf{\thesis@english@bib@author:} &
        \noindent\parbox[t]{\@right}{
          \thesis@author\\
          \thesis@english@facultyName,
          \thesis@english@universityName\\
          \thesis@departmentEn
        }\\
      \textbf{\thesis@english@bib@thesisTitle:}
        & \thesis@titleEn \\
      \textbf{\thesis@english@bib@programme:}
        & \thesis@programmeEn \\
      \textbf{\thesis@english@bib@field:}
        & \thesis@fieldEn \\
      % Unless this is a rigorous thesis, typeset the name of the
      % thesis advisor.
      \ifx\thesis@type\thesis@rigorous\else%
        \textbf{\thesis@english@bib@advisor:}
          & \thesis@advisor \\
      \fi
      \textbf{\thesis@english@bib@academicYear:}
        & \thesis@academicYear \\
      \textbf{\thesis@english@bib@pages:}
        & \thesis@pages \\
      \textbf{\thesis@english@bib@keywords:}
        & \thesis@TeXkeywordsEn \\
    \end{thesis@newtable@old}}
  \end{alwayssingle}
}}
```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter front matter of the thesis. The front matter is typeset without any visible numbering, as mandated by the formal requirements of the faculty.

```
\def\thesis@blocks@frontMatter{%
  \pagestyle{empty}
  \parindent 1.5em
  \setcounter{page}{1}
  \pagenumbering{roman}}
```

`\thesis@blocks@cover` The `\thesis@blocks@cover` macro typesets the thesis cover.

```
\def\thesis@blocks@cover{%
  \ifthesis@cover@
    \thesis@blocks@clear
    \ifthesis@twoside@\@twosidefalse\fi % Temporarily disable twoside
    \begin{alwayssingle}
      \thispagestyle{empty}
```

```
    \begin{center}
    {\sc\thesis@titlePage@LARGE\thesis@czech@universityName\\%
        \thesis@titlePage@Large\thesis@czech@facultyName\\[0.3em]%
        \thesis@titlePage@large\thesis@department}
    \vfill
    {\bf\thesis@titlePage@Huge\thesis@czech@typeName}
    \vfill
    {\thesis@titlePage@large\thesis@place
     \ \thesis@year\hfill\thesis@author}
    \end{center}
  \end{alwayssingle}
  \ifthesis@twoside@\@twosidetrue\fi % Re-enable twoside
\fi}
```

`\thesis@blocks@titlePage` The `\thesis@blocks@titlePage` macro typesets the thesis title page. Depending on the value of the `\ifthesis@color@` conditional, the faculty logo is loaded from either `\thesis@logopath`, if `false`, or from `\thesis@logopath color/`, if `true`.

```
\def\thesis@blocks@titlePage{%
  \thesis@blocks@clear
  \ifthesis@twoside@\@twosidefalse\fi % Temporarily disable twoside
  \begin{alwayssingle}
    \thispagestyle{empty}
    % The top of the page
    \begin{adjustwidth}{-12mm}{}
      \begin{minipage}{30mm}
        \thesis@blocks@universityLogo@color[width=30mm]
      \end{minipage}\begin{minipage}{89mm}
        \begin{center}
          {\sc\thesis@titlePage@LARGE\thesis@czech@universityName\\%
              \thesis@titlePage@Large\thesis@czech@facultyName\\[0.3em]%
              \thesis@titlePage@normalsize\thesis@department}
          \rule{\textwidth}{2pt}\vspace*{2mm}
        \end{center}
      \end{minipage}\begin{minipage}{30mm}
        \thesis@blocks@facultyLogo@color[width=30mm]
      \end{minipage}
    \end{adjustwidth}
    % The middle of the page
    \vfill
    {\bf\thesis@titlePage@Huge\thesis@TeXtitle\\[0.8em]}
    {\thesis@titlePage@large\thesis@czech@typeName\\[1em]}
    {\bf\thesis@titlePage@LARGE\thesis@author}\\
    \vfill\noindent
    % The bottom of the page
    {\bf\thesis@titlePage@normalsize%
      % Unless this is a rigorous thesis, typeset the name of the
      % thesis advisor.
      \ifx\thesis@type\thesis@rigorous\else%
          \thesis@czech@advisorTitle: \thesis@advisor\hfill%
      \fi%
```

```
      \thesis@place\ \thesis@year}
  \end{alwayssingle}
  \ifthesis@twoside@\@twosidetrue\fi} % Re-enable twoside
```

All blocks within the autolayout postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file. The entire front matter is typeset as though the locale were Czech in accordance with the formal requirements of the faculty.

```
\def\thesis@preamble{%
  {\thesis@selectLocale{czech}%
  \thesis@blocks@cover%
  \thesis@blocks@frontMatter%
    \thesis@blocks@titlePage%
    \thesis@blocks@clearRight%
      \thesis@blocks@bibEntry%
      \thesis@blocks@bibEntryEn%
      \thesis@blocks@abstract%
      \thesis@blocks@abstractEn%
    \thesis@blocks@assignment%
    \thesis@blocks@thanks%
    \thesis@blocks@declaration%
    \thesis@blocks@tables}%
  \thesis@blocks@mainMatter}
```

3.6.5 The style files of the Faculty of Arts

3.6.5.1 The `style/mu/fithesis-phil.sty` file

This is the style file for the theses written at the Faculty of Arts at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty[3].

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-phil}[2015/06/27]
```

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{6FCEF2},
  tableEmph={HTML}{78CEF0},
  tableOdd={HTML}{EBF6FA},
  tableEven={HTML}{D0EBF5}}
```

The style file configures the title page header to include the department and the field name.

```
\thesis@blocks@titlePage@department@true
\thesis@blocks@titlePage@field@true
```

All blocks within the autolayout postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

[3] See http://is.muni.cz/auth/do/1421/4581421/Vzor_bakalarske_prace.pdf

```
\def\thesis@preamble{%
  \thesis@blocks@cover%
  \thesis@blocks@titlePage%
  \thesis@blocks@frontMatter%
    \thesis@blocks@declaration%
    \thesis@blocks@thanks%
    \thesis@blocks@tables%
  \thesis@blocks@mainMatter}
```

3.6.6 The style files of the Faculty of Education

3.6.6.1 The `style/mu/fithesis-ped.sty` file

This is the style file for the theses written at the Faculty of Education at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty[4].

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-ped}[2015/06/27]
```

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{FFA02F},
  tableEmph={HTML}{FFBB6B},
  tableOdd={HTML}{FFF1E0},
  tableEven={HTML}{FFDEB7}}
```

The style file configures the title page header to include the department name and the title page content to include advisor's name.

```
\thesis@blocks@titlePage@department@true
\def\thesis@blocks@titlePage@content{%
    {\thesis@titlePage@Huge\bf\thesis@TeXtitle\par\vfil}\vskip 0.8in
    {\thesis@titlePage@large\sc\thesis@@{typeName}\\[0.3in]}
    {\thesis@titlePage@Large\bf\thesis@author}
    % Typeset the name of the thesis advisor.
    {\thesis@titlePage@large\\[0.3in]
      {\bf\thesis@@{advisorTitle}:} \thesis@advisor}}
```

`\thesis@blocks@bibEntry`

The `\thesis@blocks@bibEntry` macro typesets a bibliographical entry. Along with the macros required by the locale file interface, the *locale* files need to define the following macros:

- `\thesis@`*locale*`@bib@title` – The title of the entire block
- `\thesis@`*locale*`@bib@pages` – The abbreviation of pages used in the bibliographical entry

```
\def\thesis@blocks@bibEntry{%
  \chapter*{\thesis@@{bib@title}}
  \noindent\thesis@upper{author@tail}, \thesis@author@head.
```

[4] See http://is.muni.cz/do/ped/VPAN/pokdek/Pokyn_dekana_c._1-2010__2_.pdf

```
\emph{\thesis@title}. \thesis@place: \thesis@@{universityName},
\thesis@@{facultyName}, \thesis@department, \thesis@year.
\thesis@pages\ \thesis@@{bib@pages}.
\thesis@@{advisorTitle}: \thesis@advisor}
```

All blocks within the autolayout postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
\def\thesis@preamble{%
  \thesis@blocks@cover%
  \thesis@blocks@titlePage%
  \thesis@blocks@frontMatter%
    \thesis@blocks@bibEntry%
    \thesis@blocks@clearRight%
      \thesis@blocks@abstract%
      \thesis@blocks@abstractEn%
      \thesis@blocks@keywords%
      \thesis@blocks@keywordsEn%
    \thesis@blocks@declaration%
    \thesis@blocks@thanks%
    \thesis@blocks@tables%
  \thesis@blocks@mainMatter}
```

3.6.7 The style files of the Faculty of Social Studies

3.6.7.1 The `style/mu/fithesis-fss.sty` file

This is the style file for the theses written at the Faculty of Social Studies at the Masaryk University in Brno. Because of the inexistence of faculty-wide formal requirements and recommendations with each department defining their own with varying degrees of rigour[5], this style is a mere skeleton, which is unlikely to satisfy the exact requirements of any department and will require modification by the user.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-fss}[2015/06/27]
```

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{58EDD7},
  tableEmph={HTML}{69D6C6},
  tableOdd={HTML}{E3F1EE},
  tableEven={HTML}{C5E3DF}}
```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis.

[5] See http://psych.fss.muni.cz/node/351, http://medzur.fss.muni.cz/informace-pro-studenty/pravidla-pro-diplomky/soubory/PravidlaprozaverecnepracenaKMSZ-ver.2-83.doc, http://soc.fss.muni.cz/?q=node/44, http://polit.fss.muni.cz/informace-pro-studenty/pol/, http://humenv.fss.muni.cz/studium/bakalarske-studium/pravidla-pro-vypracovani-bakalarske-prace

```
\def\thesis@blocks@frontMatter{%
  \pagestyle{plain}
  \parindent 1.5em
  \setcounter{page}{1}
  \pagenumbering{roman}}
```

All blocks within the autolayout preamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
\def\thesis@preamble{%
  \thesis@blocks@cover%
  \thesis@blocks@titlePage%
  \thesis@blocks@frontMatter%
    \thesis@blocks@clearRight%
      \thesis@blocks@abstract%
      \thesis@blocks@abstractEn%
      \thesis@blocks@keywords%
      \thesis@blocks@keywordsEn%
    \thesis@blocks@assignment%
    \thesis@blocks@declaration%
    \thesis@blocks@thanks%
    \thesis@blocks@tables%
  \thesis@blocks@mainMatter}
```

3.6.8 The style files of the Faculty of Law

3.6.8.1 The `style/mu/fithesis-law.sty` file

This is the style file for the theses written at the Faculty of Law at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty[6].

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-law}[2015/06/27]
```

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{CF86EB},
  tableEmph={HTML}{D39BE8},
  tableOdd={HTML}{F2EBF5},
  tableEven={HTML}{E5CCED}}
```

The style file configures the cover and title page headers to include only the faculty name and the department name. Along with the macros required by the locale file interface, the locale files need to define the following macros:

- `\thesis@`*locale*`@facultyLongName` – The name of the faculty combined with the name of the university.

```
\def\thesis@blocks@cover@header{%
  {\sc\thesis@titlePage@Large\thesis@@{facultyLongName}\\%
```

[6] See http://is.muni.cz/do/law/ud/predp/smer/S-07-2012.pdf

```
    \thesis@titlePage@large\thesis@department\\\vskip 2em}}
\let\thesis@blocks@titlePage@header=\thesis@blocks@cover@header
```

\thesis@blocks@frontMatter

The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis. The page numbering is arabic in accordance with the formal requirements of the faculty.

```
\def\thesis@blocks@frontMatter{%
  \thesis@blocks@clear
  \pagestyle{plain}
  \parindent 1.5em
  \setcounter{page}{1}
  \pagenumbering{arabic}}
```

\thesis@blocks@mainMatter

The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis. The page numbering doesn't reset at the beginning of the main thesis in accordance with the formal requirements of the faculty.

```
\def\thesis@blocks@mainMatter{%
  \thesis@blocks@clear
  \pagestyle{thesisheadings}
  \parindent 1.5em\relax}
```

All blocks within the autolayout preamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
\def\thesis@preamble{%
  \thesis@blocks@cover%
  \thesis@blocks@titlePage%
  \thesis@blocks@frontMatter%
    \thesis@blocks@declaration%
    \thesis@blocks@clearRight%
      \thesis@blocks@abstract%
      \thesis@blocks@abstractEn%
      \thesis@blocks@keywords%
      \thesis@blocks@keywordsEn%
    \thesis@blocks@thanks%
    \thesis@blocks@tables%
  \thesis@blocks@mainMatter}
```

All blocks within the autolayout postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
\def\thesis@postamble{%
  \thesis@blocks@assignment}
```

3.6.9 The style files of the Faculty of Economics and Administration

3.6.9.1 The `style/mu/fithesis-econ.sty` file

This is the style file for the theses written at the Faculty of Economics and Administration at the Masaryk University in Brno. It has been prepared in accordance

with the formal requirements published at the website of the faculty[7].

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-econ}[2015/06/27]
```

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{E68935},
  tableEmph={HTML}{E8B88B},
  tableOdd={HTML}{F5ECEB},
  tableEven={HTML}{EBD8D5}}
```

The file loads the following packages:

- tikz – Used for dimension arithmetic.
- geometry – Allows for modifications of the type area dimensions.

In addition to this, the type area width is set to 16 cm in accordance with the formal requirements of the faculty. This leads to overfull lines and is against the good conscience of the author of this style.

```
\thesis@require{tikz}
\thesis@require{geometry}
\geometry{top=25mm,bottom=20mm,left=25mm,right=25mm,includeheadfoot}
```

`\thesis@blocks@cover` The `\thesis@blocks@cover` macro typesets the thesis cover.

```
\def\thesis@blocks@cover{%
  \ifthesis@cover@
    \thesis@blocks@clear
    \begin{alwayssingle}
      \thispagestyle{empty}
      \begin{center}
      {\sc\thesis@titlePage@LARGE\thesis@@{universityName}\\%
          \thesis@titlePage@Large\thesis@@{facultyName}\\}
      \vfill
      {\bf\thesis@titlePage@Huge\thesis@@{typeName}}
      \vfill
      {\thesis@titlePage@large\thesis@place
       \ \thesis@year\hfill\thesis@author}
      \end{center}
    \end{alwayssingle}
  \fi}
```

The style file configures the title page header to include the name of the field of study and redefines the title page content not to include the author's name and the title page footer to include both the author's and advisor's name, the year and place of the thesis defense in accordance with the formal requirements of the faculty.

```
\thesis@blocks@titlePage@field@true
```

[7] See http://is.muni.cz/auth/do/econ/predpisy/smernice/prehled/45931363/Smernice2014-9.pdf

```
\def\thesis@blocks@titlePage@content{%
  {\thesis@titlePage@Huge\bf\thesis@TeXtitle}
  \ifthesis@english\else
    {\\[0.1in]\thesis@titlePage@Large\bf\thesis@TeXtitleEn}
  \fi {\\[0.3in]\thesis@titlePage@large\sc\thesis@@{typeName}\\}}
\def\thesis@blocks@titlePage@footer{%
  {\thesis@titlePage@large
    {% Calculate the width of the thesis author and advisor boxes
     \let\@A\relax\newlength{\@A}\settowidth{\@A}{{%
       \bf\thesis@@{advisorTitle}:}}
     \let\@B\relax\newlength{\@B}\settowidth{\@B}{\thesis@advisor}
     \let\@C\relax\newlength{\@C}\settowidth{\@C}{{%
       \bf\thesis@@{authorTitle}:}}
     \let\@D\relax\newlength{\@D}\settowidth{\@D}{\thesis@author}
    \let\@left\relax\newlength{\@left}\pgfmathsetlength{\@left}{%
      max(\@A,\@B)}
    \let\@right\relax\newlength{\@right}\pgfmathsetlength{\@right}{%
      max(\@C,\@D)}
    % Typeset the thesis author and advisor boxes
    \vskip 2in\begin{minipage}[t]{\@left}
      {\bf\thesis@@{advisorTitle}:}\\\thesis@advisor
    \end{minipage}\hfill\begin{minipage}[t]{\@right}
      {\bf\thesis@@{authorTitle}:}\\\thesis@author
    \end{minipage}}\\[4em]\thesis@place, \thesis@year}}
```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis. The page numbering is arabic as per the formal requirements and it is hidden. In case of double-sided typesetting, the geometry is altered according to the requirements of the faculty.

```
\def\thesis@blocks@frontMatter{%
  \thesis@blocks@clear
  % In case of double-sided typesetting, change the geometry
  \ifthesis@twoside@
    \newgeometry{top=25mm,bottom=20mm,left=35mm,
      right=15mm, includeheadfoot}
  \fi\pagestyle{empty}
  \parindent 1.5em
  \setcounter{page}{1}
  \pagenumbering{arabic}}
```

`\thesis@blocks@mainMatter` The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis. The page numbering doesn't reset at the beginning of the main thesis as per the formal requirements.

```
\def\thesis@blocks@mainMatter{%
  \thesis@blocks@clear
  \pagestyle{thesisheadings}
  \parindent 1.5em\relax}
```

`\thesis@blocks@toc` The `\thesis@blocks@toc` macro typesets the table of contents.

```
\def\thesis@blocks@toc{%
  \thesis@blocks@clear%
  \tableofcontents}
```

\thesis@blocks@tables The \thesis@blocks@tables macro optionally typesets the \listoftables and \listoffigures.

```
\def\thesis@blocks@tables{%
  \thesis@blocks@clear%
  \thesis@blocks@lot%
  \thesis@blocks@lof}
```

All blocks within the autolayout preamble that are not defined within this file are defined in the style/mu/fithesis-base.sty file.

```
\def\thesis@preamble{%
  \thesis@blocks@cover%
  \thesis@blocks@frontMatter%
    \thesis@blocks@titlePage%
    \thesis@blocks@assignment%
    \thesis@blocks@clearRight%
      \thesis@blocks@abstract%
      \thesis@blocks@abstractEn%
      \thesis@blocks@keywords%
      \thesis@blocks@keywordsEn%
    \thesis@blocks@declaration%
    \thesis@blocks@thanks%
    \thesis@blocks@toc%
  \thesis@blocks@mainMatter}
```

The style file defines the autolayout postamble as the list of tables and the list of figures. All blocks are defined in the style/mu/base.sty file, although some are redefined in this file.

```
\def\thesis@postamble{%
  \thesis@blocks@tables}
```

3.6.10 The style files of the Faculty of Medicine

3.6.10.1 The style/mu/fithesis-med.sty file

This is the style file for the theses written at the Faculty of Medicine at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the Department of Optometry and Orthoptics[8].

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-med}[2015/06/27]
```

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{F58E76},
  tableEmph={HTML}{FF9D85},
```

[8] See http://is.muni.cz/do/med/zpravyprac/Optometrie/NALEZITOSTI_ZAVERECNE_PRACE.doc

```
  tableOdd={HTML}{FFF5F6},
  tableEven={HTML}{FFDEDF}}
```

The file loads the following packages:

- tikz – Used for dimension arithmetic.
- geometry – Allows for modifications of the type area dimensions.
- setspace – Allows for line height modifications.

In addition to this, the type area width is set to 16 cm in accordance with the formal requirements of the faculty. This leads to overfull lines and is against the good conscience of the author of this style.

```
\thesis@require{tikz}
\thesis@require{geometry}
\thesis@require{setspace}
\geometry{top=25mm,bottom=20mm,left=25mm,right=25mm,includeheadfoot}
```

\thesis@blocks@cover

The \thesis@blocks@cover macro typesets the thesis cover.

```
\def\thesis@blocks@cover{%
  \ifthesis@cover@
    \thesis@blocks@clear
    \begin{alwayssingle}
      \thispagestyle{empty}
      \begin{center}
      {\sc\thesis@titlePage@LARGE\thesis@@{universityName}\\%
          \thesis@titlePage@Large\thesis@@{facultyName}\\}
      \vfill
      {\bf\thesis@titlePage@Huge\thesis@@{typeName}}
      \vfill
      {\thesis@titlePage@large\thesis@place
       \ \thesis@year\hfill\thesis@author}
      \end{center}
    \end{alwayssingle}
  \fi}
```

The style file redefines the title page content not to include the author's name and the title page footer to include both the author's and advisor's name, the field of study and the semester and place of the thesis defense in accordance with the requirements of the department.

```
\def\thesis@blocks@titlePage@content{%
  {\thesis@titlePage@Huge\bf\thesis@TeXtitle\\[0.3in]}%
  {\thesis@titlePage@large{\sc\thesis@@{typeName}}\\}}
\def\thesis@blocks@titlePage@footer{%
  {\thesis@titlePage@large
    {% Calculate the width of the thesis author and advisor boxes
     \let\@A\relax\newlength{\@A}\settowidth{\@A}{{%
       \bf\thesis@@{advisorTitle}:}}
     \let\@B\relax\newlength{\@B}\settowidth{\@B}{\thesis@advisor}
```

```
    \let\@C\relax\newlength{\@C}\settowidth{\@C}{{%
      \bf\thesis@@{authorTitle}:}}
    \let\@D\relax\newlength{\@D}\settowidth{\@D}{\thesis@author}
    \let\@E\relax\newlength{\@E}\settowidth{\@E}{{%
      \bf\thesis@@{fieldTitle}:}}
    \let\@F\relax\newlength{\@F}\settowidth{\@F}{\thesis@field}
   \let\@left\relax\newlength{\@left}\pgfmathsetlength{\@left}{%
     max(\@A,\@B)}
   \let\@right\relax\newlength{\@right}\pgfmathsetlength{\@right}{%
     max(\@C,\@D,\@E,\@F)}
   % Typeset the thesis author and advisor boxes
   \vskip 2in\begin{minipage}[t]{\@left}
     {\bf\thesis@@{advisorTitle}:}\\\thesis@advisor
   \end{minipage}\hfill\begin{minipage}[t]{\@right}
     {\bf\thesis@@{authorTitle}:}\\\thesis@author
       \\[1em]{\bf\thesis@@{fieldTitle}:}\\\thesis@field
   \end{minipage}}\\[4em]\thesis@place, \thesis@@{semester}}}
```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis. The page numbering is arabic in accordance with the formal requirements and it is hidden. In case of double-sided typesetting, the geometry is altered according to the requirements of the faculty.

```
\def\thesis@blocks@frontMatter{%
  \thesis@blocks@clear
  % In case of double-sided typesetting, change the geometry
  \ifthesis@twoside@
    \newgeometry{top=25mm,bottom=20mm,left=35mm,
      right=15mm, includeheadfoot}
  \fi\pagestyle{empty}
  \parindent 1.5em
  \setcounter{page}{1}
  \pagenumbering{arabic}}
```

`\thesis@blocks@bibEntry` The `\thesis@blocks@bibEntry` macro typesets a bibliographical entry. Along with the macros required by the locale file interface, the *locale* files need to define the following macros:

- `\thesis@`*locale*`@bib@title` – The title of the entire block
- `\thesis@`*locale*`@bib@pages` – The abbreviation of pages used in the bibliographical entry

```
\def\thesis@blocks@bibEntry{%
  \chapter*{\thesis@@{bib@title}}
  \noindent\thesis@upper{author@tail}, \thesis@author@head.
  \emph{\thesis@title}. \thesis@place: \thesis@@{universityName},
  \thesis@@{facultyName}, \thesis@department, \thesis@year.
  \thesis@pages\ \thesis@@{bib@pages}.
  \thesis@@{advisorTitle}: \thesis@advisor}
```

All blocks within the autolayout postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
\def\thesis@preamble{%
  \thesis@blocks@cover%
  \thesis@blocks@frontMatter%
    \thesis@blocks@titlePage%
    \onehalfspacing%
    \thesis@blocks@clearRight%
      \thesis@blocks@abstract%
      \thesis@blocks@abstractEn%
      \thesis@blocks@keywords%
      \thesis@blocks@keywordsEn%
    \thesis@blocks@bibEntry%
    \thesis@blocks@declaration%
    \thesis@blocks@thanks%
    \thesis@blocks@tables%
  \thesis@blocks@mainMatter}
```

3.6.11 The style files of the Faculty of Sports Studies

3.6.11.1 The `style/mu/fithesis-fss.sty` file

This is the style file for the theses written at the Faculty of Sports Studies at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty[9].

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fithesis/style/mu/fithesis-fss}[2015/06/27]
```

The file defines the color scheme of the respective faculty.

```
\thesis@color@setup{
  links={HTML}{93BCF5},
  tableEmph={HTML}{A8BDE3},
  tableOdd={HTML}{EBEFF5},
  tableEven={HTML}{D1DAEB}}
```

The style file configures the title page header to include the field name.

```
\thesis@blocks@titlePage@field@true
```

All blocks within the autolayout preamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
\def\thesis@preamble{%
  \thesis@blocks@cover%
  \thesis@blocks@titlePage%
  \thesis@blocks@frontMatter%
    \thesis@blocks@declaration%
    \thesis@blocks@thanks%
    \thesis@blocks@tables%
  \thesis@blocks@mainMatter}
```

[9] See http://www.fsps.muni.cz/~korvas/pokyny_k_zaverecne_praci.doc

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols

\. 1114
\@A 1675, 1676, 1677, 1678, 1680, 1727, 1751, 1792, 1816, 2076, 2083, 2162, 2172
\@B 1729, 1751, 1794, 1816, 2078, 2083, 2164, 2172
\@C 1731, 1751, 1796, 1816, 2079, 2085, 2165, 2174
\@D 1733, 1751, 1798, 1816, 2081, 2085, 2167, 2174
\@E 1737, 1739, 1741, 1751, 1802, 1804, 1806, 1816, 2168, 2174
\@F 1743, 1751, 1808, 1816, 2170, 2174
\@G 1745, 1751, 1810, 1816
\@H 1747, 1751, 1812, 1816
\@afterheading 1518, 1525
\@afterindentfalse 1170, 1495
\@arg 141, 142, 169, 170, 244, 245
\@args 1111, 1112
\@auxout 279
\@beginparpenalty 1462
\@chapapp 1503, 1545
\@chapter 1171, 1496, 1499
\@date 200, 201
\@dblfpbot 1396, 1424, 1452
\@dblfpsep 1395, 1423, 1451
\@dblfptop 1394, 1422, 1450
\@dottedtocline . 1226, 1227, 1228, 1229
\@empty 1140, 1141
\@endparpenalty 1463
\@english 154, 160
\@evenfoot 1152, 1154
\@evenhead 1145, 1148
\@fpbot 1393, 1421, 1449
\@fpsep 1392, 1420, 1448
\@fptop 1391, 1419, 1447
\@gobble 87, 318, 324
\@gobbletwo 330, 338
\@highpenalty . . . 1195, 1212, 1222, 1461
\@ifpackageloaded 289, 291
\@inject 1110, 1116, 1117
\@itempenalty 1464
\@ixpt 1241, 1287
\@left 1750, 1753, 1757, 1815, 1818, 1822, 2082, 2087, 2171, 2176
\@listI 1239, 1276, 1314, 1560, 1564, 1590, 1594, 1620, 1624
\@listi 1239, 1246, 1255, 1276, 1283, 1292, 1314, 1321, 1331, 1564, 1565, 1594, 1595, 1624, 1625
\@listii 1567, 1597, 1627
\@listiii 1573, 1603, 1633
\@listiv 1579, 1609, 1639
\@listv 1582, 1612, 1642
\@listvi 1585, 1615, 1645
\@locale 157, 159
\@lowpenalty 1459, 1462, 1463, 1464
\@makechapterhead . . . 1466, 1515, 1517
\@makeschapterhead . . . 1481, 1522, 1523
\@medpenalty 1460
\@mkboth 1156
\@month 184, 185
\@mparswitchfalse 811
\@mparswitchtrue 813
\@nobreakfalse 1205
\@nobreaktrue 1204
\@normalsize 1355
\@oddfoot 1140, 1150, 1154
\@oddhead 1141, 1142, 1148
\@p 1275
\@part 1186
\@path 935, 936, 939, 941, 944, 945, 948, 950
\@pdfList 1106, 1107, 1117
\@plus 1196, 1207, 1213
\@pnumwidth 1199, 1200, 1202, 1216, 1217, 1221
\@relax 1111, 1112
\@restonecolfalse 1190
\@restonecoltrue 1190
\@right 1752, 1757, 1759, 1817, 1822, 1824, 2084, 2089, 2173, 2178
\@schapter 1171, 1496, 1522
\@skip . 1749, 1753, 1757, 1814, 1818, 1822
\@spart 1186

\@startsection 1527, 1529, 1531, 1533, 1536
\@tempdima 1198, 1214, 1219
\@tempswafalse 1183
\@tempswatrue 1181
\@topnewpage 1515, 1522
\@topnum 1169, 1494
\@trimmed 1114, 1115
\@true 140, 142, 168, 170, 243, 245
\@twocolumnfalse 814
\@twocolumntrue 815
\@twosidefalse 811, 954, 1859, 1877
\@twosidetrue 813, 967, 1873, 1910
\@viiipt 1250, 1296, 1335
\@viipt 1259
\@vipt 1297, 1336
\@vpt 1260
\@xiipt 1261, 1298, 1309
\@xipt 1271, 1316
\@xivpt 1262, 1299, 1337
\@xpt 1234, 1278, 1326
\@xviipt 1263, 1300, 1338
\@xxpt 1264, 1301, 1339
\@xxvpt 1265, 1302, 1340, 1341
\@year 183, 187, 188, 191, 192
\@yearA 187, 191, 194
\@yearB 188, 192, 194
\\ . 959, 980, 982, 984, 993, 1003, 1022, 1024, 1026, 1662, 1667, 1680, 1760, 1762, 1764, 1766, 1768, 1770, 1775, 1778, 1780, 1782, 1825, 1827, 1829, 1831, 1833, 1835, 1840, 1843, 1845, 1847, 1863, 1864, 1886, 1887, 1897, 1898, 1899, 1953, 1956, 2013, 2014, 2057, 2058, 2071, 2072, 2088, 2090, 2091, 2146, 2147, 2157, 2158, 2177, 2179, 2180, 2181

\␣ 332, 518, 519, 572, 574, 586, 627, 698, 750, 752, 765, 1138, 1870, 1908, 1963, 2063, 2152, 2197

A

\abovedisplayshortskip 1237, 1244, 1253, 1275, 1281, 1290, 1312, 1319, 1329
\abovedisplayskip 1235, 1236, 1242, 1243, 1251, 1252, 1272, 1273, 1279, 1280, 1288, 1289, 1310, 1311, 1317, 1318, 1327, 1328
\aboverulesep 887
\addcontentsline 1504, 1507
\addpenalty 1195, 1212
\addtocontents 1510, 1512
\addtocounter 1102
\addvspace 1196, 1207, 1511, 1513
\advance 187, 188, 192, 1219, 1378, 1406, 1434, 1557, 1568, 1574, 1580, 1583, 1586, 1598, 1604, 1610, 1613, 1616, 1628, 1634, 1640, 1643, 1646
\Alph 1546
\alwayssingle 1189
\appendix 1542
\appendixname 1545
\arraystretch 1755, 1820
\AtBeginDocument 274
\AtEndDocument 275, 277
\AtEndPreamble 255

B

\baselineskip 1377, 1405, 1433
\begin 955, 957, 999, 1001, 1041, 1050, 1056, 1066, 1075, 1085, 1100, 1686, 1722, 1756, 1787, 1821, 1860, 1862, 1878, 1881, 1882, 1884, 1885, 1891, 2054, 2056, 2087, 2089, 2143, 2145, 2176, 2178
\begingroup 139, 167, 1197, 1215
\belowdisplayshortskip 1238, 1245, 1254, 1274, 1282, 1291, 1313, 1320, 1330
\belowdisplayskip 1236, 1243, 1252, 1273, 1280, 1289, 1311, 1318, 1328
\belowrulesep 888
\bf 988, 991, 994, 1030, 1661, 1663, 1668, 1728, 1730, 1732, 1734, 1741, 1744, 1746, 1748, 1793, 1795, 1797, 1799, 1806, 1809, 1811, 1813, 1867, 1897, 1899, 1902, 1952, 1954, 1957, 2060, 2069, 2071, 2077, 2080, 2088, 2090, 2149, 2157, 2163, 2166, 2169, 2177, 2179, 2180
\bfseries 1202, 1218, 1505, 1507, 1528, 1530, 1535, 1538

C

\c@secnumdepth 1137, 1471, 1500
\c@tocdepth 1194, 1211
\centering 1679
\ChapFont 1475, 1485
\chapter 1042, 1051, 1059, 1069, 1078, 1088, 1160, 1491, 1687, 1725, 1790, 1959, 2193
\chaptermark 1135, 1509
\ClassWarning 285
\cleardoublepage . . 918, 1058, 1068, 1077, 1087, 1164, 1177, 1724, 1789
\clearpage 916, 924, 1162, 1166, 1175, 1492
\clubpenalty 896
\columnsep 1380, 1408, 1436
\columnseprule 1381, 1409, 1437
\csname 70, 158, 159, 253, 301, 302, 312, 318, 324, 345, 844

D

\day 196
\dblfloatsep 1388, 1416, 1444
\dbltextfloatsep 1389, 1417, 1445
\DeclareOption 806, 807, 808, 810, 812, 814, 815, 816, 817, 819, 820, 822, 823, 825, 826, 827, 828, 829, 830, 832, 833
\def 10, 12, 15, 17, 19, 21, 23, 25, 27, 29, 31, 70, 72, 73, 74, 77, 78, 84, 85, 86, 88, 96, 97, 98, 99, 100, 103, 104, 106, 107, 109, 112, 115, 118, 121, 124, 127, 128, 130, 131, 133, 134, 136, 140, 141, 147, 152, 153, 154, 156, 168, 169, 175, 202, 204, 207, 208, 210, 213, 214, 216, 219, 220, 222, 225, 226, 228, 230, 231, 233, 234, 236, 237, 238, 240, 243, 244, 250, 251, 252, 256, 283, 286, 288, 290, 292, 299, 302, 312, 313, 314, 320, 326, 327, 328, 335, 341, 342, 806, 807, 808, 827, 829, 897, 908, 914, 922, 951, 978, 990, 995, 997, 1020, 1034, 1039, 1047, 1055, 1058, 1063, 1068, 1074, 1077, 1082, 1087, 1095, 1110, 1111, 1121, 1134, 1135, 1142, 1145, 1150, 1152, 1189, 1191, 1246, 1255, 1283, 1292, 1309, 1316, 1321, 1326, 1331, 1335, 1336, 1337, 1338, 1339, 1340, 1341, 1466, 1481, 1491, 1499, 1522, 1527, 1529, 1531, 1533, 1536, 1542, 1545, 1546, 1560, 1567, 1573, 1579, 1582, 1585, 1590, 1597, 1603, 1609, 1612, 1615, 1620, 1627, 1633, 1639, 1642, 1645, 1660, 1670, 1684, 1695, 1721, 1724, 1785, 1789, 1851, 1856, 1875, 1911, 1935, 1951, 1958, 1965, 1986, 1991, 2012, 2016, 2022, 2026, 2039, 2051, 2068, 2073, 2092, 2102, 2106, 2109, 2113, 2127, 2140, 2156, 2159, 2182, 2192, 2199, 2222
\define@key 13, 20, 24, 28, 76, 92, 95, 102, 105, 108, 111, 114, 117, 120, 123, 126, 129, 132, 135, 138, 151, 166, 199, 203, 206, 209, 212, 215, 218, 221, 224, 227, 236, 239, 242, 899, 902, 904, 906
\definecolor 900, 903, 905, 907

E

\ea 315, 316, 317, 318, 321, 322, 323, 324, 1108, 1116, 1117
\edef 187, 188, 191, 192, 194, 196, 200, 343, 935, 939, 944, 948, 1106, 1114
\else 7, 16, 34, 38, 41, 45, 49, 52, 56, 59, 64, 71, 81, 144, 150, 162, 172, 189, 247, 257, 260, 263, 331, 371, 373, 375, 377, 491, 493, 495, 497, 503, 505, 507, 509, 593, 595, 597, 603, 605, 607, 670, 672, 674, 676, 682, 684, 686, 688, 773, 775, 777, 783, 785, 787, 845, 847, 858, 919, 930, 1048, 1064, 1083, 1102, 1105, 1107, 1112, 1147, 1153, 1165, 1182, 1362, 1506, 1516, 1523, 1656, 1657, 1717, 1718, 1740, 1773, 1805, 1838, 1905, 2070
\emph 1961, 2195
\empty 22, 26, 30, 31, 32, 36, 43, 47, 260, 263, 1107
\end . 965, 966, 1009, 1010, 1046, 1053, 1062, 1072, 1081, 1091, 1104, 1694, 1783, 1784, 1848, 1849, 1871, 1872, 1884, 1890, 1891, 1893, 1894, 1909, 2064, 2065, 2089, 2091, 2153, 2154, 2178, 2181
\endalwayssingle 1191

\endcsname 70, 158, 164, 253, 301, 302, 312, 319, 325, 345, 849
\endgroup . 143, 145, 171, 173, 1206, 1223
\endtabular 868
\endtabularx 880
\endthesis@newtable@old 868, 877
\endthesis@newtable@oldx . . . 880, 885
\english 155
\evensidemargin 1360, 1364
\everypar 1205
\ExecuteOptions 834
\expandafter . . . 70, 86, 154, 156, 157, 158, 159, 183, 184, 197, 201, 301, 302, 315, 321, 330, 338, 345, 843, 1108
\extrarowheight 889

F

\fi 9, 18, 40, 54, 55, 61, 62, 63, 66, 67, 68, 71, 83, 146, 150, 164, 174, 193, 249, 262, 265, 276, 282, 297, 310, 311, 333, 339, 341, 379, 466, 499, 511, 599, 609, 645, 678, 690, 779, 789, 848, 849, 857, 865, 866, 890, 921, 929, 932, 940, 949, 954, 967, 968, 981, 983, 985, 989, 1023, 1025, 1027, 1031, 1054, 1073, 1092, 1102, 1116, 1118, 1119, 1120, 1139, 1149, 1155, 1167, 1184, 1190, 1191, 1208, 1224, 1366, 1474, 1508, 1519, 1525, 1659, 1669, 1683, 1720, 1742, 1776, 1807, 1841, 1859, 1873, 1874, 1877, 1907, 1910, 2066, 2072, 2098, 2155, 2188
\file *19*, *35*
\fill 1051
\floatsep 1385, 1413, 1441
\fontsize . . . 1234, 1241, 1250, 1259, 1260, 1261, 1262, 1263, 1264, 1265, 1271, 1278, 1287, 1296, 1297, 1298, 1299, 1300, 1301, 1302, 1309, 1316, 1326, 1335, 1336, 1337, 1338, 1339, 1340, 1341
\footins 1384, 1412, 1440
\footnoterule 961, 1005
\footnotesep 1383, 1411, 1439
\footnotesize 960, 1004, 1250, 1287, 1346
\footskip 1374

G

\gdef 177, 178, 179, 180, 186, 190, 279, 349, 350, 351, 353, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 368, 381, 382, 389, 391, 392, 397, 400, 404, 405, 410, 415, 418, 421, 422, 426, 427, 432, 435, 439, 442, 443, 447, 453, 455, 456, 458, 459, 460, 465, 469, 470, 471, 473, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 488, 500, 515, 516, 523, 527, 530, 531, 536, 539, 543, 544, 550, 554, 557, 560, 561, 565, 566, 569, 579, 583, 584, 590, 600, 613, 616, 617, 621, 624, 625, 632, 634, 635, 638, 639, 644, 648, 649, 650, 652, 655, 656, 657, 658, 659, 660, 661, 662, 663, 664, 665, 667, 679, 694, 695, 702, 706, 709, 710, 715, 718, 722, 723, 728, 732, 735, 738, 739, 743, 744, 747, 757, 761, 762, 770, 780, 793, 796, 797, 801
\geometry 2050, 2139
\global 194, 450, 454, 457, 461, 633, 636, 637, 640, 844, 1169, 1204, 1205, 1494

H

\hb@xt@ 1202, 1221
\hbox 927, 1142, 1145, 1185
\headheight 1371
\headsep 1372
\hfil . . 1143, 1146, 1150, 1152, 1202, 1221
\hfill 1045, 1678, 1690, 1870, 1906, 2063, 2089, 2152, 2178
\hrule 1143, 1146
\hskip 1220, 1757, 1822
\hss 1202, 1221
\Huge 1265, 1302, 1353
\huge 1264, 1301, 1352
\hypersetup 267, 892, 901

I

\if 35, 42, 46, 50, 57
\if@restonecol 1188, 1191
\if@twocolumn . . . 1179, 1190, 1514, 1522
\if@twoside 1144, 1151, 1161, 1358
\IfFileExists 284
\ifluatex 7, 846
\ifnum . . 185, 1137, 1194, 1211, 1470, 1500
\ifodd 925

\ifthesis@auto 241, 273
\ifthesis@blocks@assignment@ 47, 1093, 1096
\ifthesis@blocks@cover@department@ 973, 983
\ifthesis@blocks@cover@faculty@ 971, 981
\ifthesis@blocks@cover@field@ 975, 986
\ifthesis@blocks@cover@university@ 969, 979
\ifthesis@blocks@titlePage@department@ 1015, 1025
\ifthesis@blocks@titlePage@faculty@ 1013, 1023
\ifthesis@blocks@titlePage@field@ 1017, 1028
\ifthesis@blocks@titlePage@university@ 1011, 1021
\ifthesis@color@ . 36, 818, 869, 940, 949
\ifthesis@cover@ 36, 831, 952, 1857, 2052, 2141
\ifthesis@english 153, 1064, 1083, 2070
\ifthesis@loaded 15, 254, 257
\ifthesis@locale@inheritance 165, 305
\ifthesis@newtable@ 36, 824, 869
\ifthesis@palatino@ .. 36, 821, 851, 859
\ifthesis@style@inheritance . 137, 293
\ifthesis@twoside@ 36, 809, 915, 923, 954, 967, 1102, 1859, 1873, 1877, 1910, 2095, 2185
\ifthesis@woman 75, 466, 645
\ifthesis@xeluatex 38, 844, 850
\ifx 14, 32, 36, 43, 47, 71, 79, 142, 149, 159, 170, 245, 260, 263, 301, 329, 336, 341, 369, 371, 373, 375, 489, 491, 493, 495, 501, 503, 505, 507, 591, 593, 595, 601, 603, 605, 668, 670, 672, 674, 680, 682, 684, 686, 771, 773, 775, 781, 783, 785, 1048, 1097, 1107, 1112, 1656, 1657, 1666, 1674, 1717, 1718, 1738, 1773, 1803, 1838, 1905
\ifxetex 7, 845
\includegraphics 936, 941, 945, 950
\includepdf 1115
\input 287, 1132
\intextsep 1387, 1415, 1443
\itemsep 1248, 1257, 1285, 1294, 1323, 1333, 1562, 1571, 1577, 1592, 1601, 1607, 1622, 1631, 1637

K

\KV@thesis@abstract 230
\KV@thesis@abstractEn 233
\KV@thesis@declaration 73
\KV@thesis@thanks 237

L

\l@chapter 1210, 1226
\l@part 1193
\l@section 1227
\l@subsection 1228
\l@subsubsection 1229
\labelsep ... 1549, 1550, 1551, 1556, 1557, 1568, 1574, 1580, 1583, 1586, 1598, 1604, 1610, 1613, 1616, 1628, 1634, 1640, 1643, 1646
\labelwidth 1557, 1568, 1574, 1580, 1583, 1586, 1598, 1604, 1610, 1613, 1616, 1628, 1634, 1640, 1643, 1646
\language 345
\languagename 149, 150
\LARGE 1263, 1300, 1351
\Large 1262, 1299, 1350, 1475, 1485
\large 1261, 1298, 1349, 1528
\leavevmode 1201, 1218
\leftmargin .. 1246, 1255, 1283, 1292, 1321, 1331, 1555, 1560, 1567, 1573, 1579, 1582, 1585, 1590, 1597, 1603, 1609, 1612, 1615, 1620, 1627, 1633, 1639, 1642, 1645
\leftmargini 1246, 1255, 1283, 1292, 1321, 1331, 1548, 1555, 1557, 1560, 1590, 1620
\leftmarginii 1549, 1567, 1568, 1597, 1598, 1627, 1628
\leftmarginiii 1550, 1573, 1574, 1603, 1604, 1633, 1634
\leftmarginiv 1551, 1579, 1580, 1609, 1610, 1639, 1640
\leftmarginv 1552, 1582, 1583, 1612, 1613, 1642, 1643
\leftmarginvi 1553, 1585, 1586, 1615, 1616, 1645, 1646
\leftskip 1219, 1220
\let 101, 315, 321, 450, 454, 457, 461, 633, 636, 637, 640, 828, 830, 843, 844, 867, 868, 879, 880, 960, 961, 1004, 1005, 1032, 1033, 1108, 1140, 1141, 1148, 1154,

1156, 1239, 1276, 1314, 1355, 1564, 1594, 1624, 1675, 1727, 1729, 1731, 1733, 1737, 1743, 1745, 1747, 1749, 1750, 1752, 1792, 1794, 1796, 1798, 1802, 1808, 1810, 1812, 1814, 1815, 1817, 2015, 2076, 2078, 2079, 2081, 2082, 2084, 2162, 2164, 2165, 2167, 2168, 2170, 2171, 2173
\listoffigures 830
\listoftables 828
\LoadClass 2
\long 73, 74, 230, 231, 233, 234, 237, 238, 252
\lowercase 316

M

\m@ne 1137, 1211, 1471, 1501
\makeatletter 259, 303
\makeatother 281
\marginparpush 1397, 1425, 1453
\marginparsep 1367
\marginparwidth 1361, 1365
\markboth 1156
\markright 1136, 1524
\month 196

N

\NeedsTeXFormat 802, 805, 1649, 1707, 1926, 1943, 1979, 2005, 2041, 2129, 2214
\newcommand 69, 933, 937, 942, 946
\newcount 183, 184
\newgeometry 2096, 2186
\newif 75, 137, 165, 241, 254, 809, 818, 821, 824, 831, 969, 971, 973, 975, 1011, 1013, 1015, 1017, 1093, 1188
\newlength 1675, 1727, 1729, 1731, 1733, 1737, 1743, 1745, 1747, 1749, 1750, 1752, 1792, 1794, 1796, 1798, 1802, 1808, 1810, 1812, 1814, 1815, 1817, 2076, 2078, 2079, 2081, 2082, 2084, 2162, 2164, 2165, 2167, 2168, 2170, 2171, 2173
\newpage 920, 928, 931
\nobreak . . . 1203, 1221, 1472, 1476, 1486
\noexpand 279
\noindent . . . 1060, 1079, 1103, 1756, 1759, 1821, 1824, 1900, 1960, 2194
\normalfont 1202
\normalsize 1234, 1271, 1344, 1355, 1356, 1530, 1532, 1535, 1538
\null 1061, 1071, 1080, 1090
\numberline 1505

O

\oddsidemargin 1359, 1363
\onecolumn 1180, 1190
\onehalfspacing 2203
\overfullrule 816, 817

P

\p@ . 1196, 1207, 1213, 1235, 1237, 1238, 1242, 1244, 1245, 1247, 1251, 1253, 1254, 1256, 1272, 1274, 1279, 1281, 1282, 1284, 1288, 1290, 1291, 1293, 1310, 1312, 1313, 1317, 1319, 1320, 1322, 1324, 1327, 1329, 1330, 1332, 1473, 1477, 1487, 1511, 1513, 1560, 1561, 1562, 1569, 1570, 1575, 1576, 1590, 1591, 1592, 1599, 1600, 1605, 1606, 1620, 1621, 1622, 1629, 1630, 1635, 1636
\PageFont 1150, 1152
\pagenumbering 913, 1124, 1855, 1990, 2021, 2101, 2191
\pagestyle 910, 1125, 1852, 1987, 2018, 2024, 2098, 2104, 2188
\par . 963, 991, 1007, 1061, 1071, 1080, 1090, 1202, 1221, 1472, 1475, 1485, 1542, 1661, 1691, 1693, 1952
\paragraph 1533
\parbox 1678, 1759, 1824
\parfillskip 1200, 1217
\parindent 911, 1126, 1199, 1216, 1468, 1483, 1537, 1853, 1988, 2019, 2025, 2099, 2105, 2189
\parsep 1247, 1248, 1256, 1257, 1284, 1285, 1293, 1294, 1322, 1323, 1332, 1333, 1560, 1570, 1571, 1576, 1590, 1600, 1601, 1606, 1620, 1630, 1631, 1636
\parskip . . . 1399, 1427, 1455, 1469, 1484
\part 1174
\partopsep 1400, 1428, 1456, 1576, 1606, 1636
\penalty 1222
\pgfmathsetlength 1750, 1815, 2082, 2084, 2171, 2173

\ProcessOptions 836
\protect 1504, 1511, 1513
\ProvidesClass 1
\ProvidesFile 346, 380, 390, 394, 401, 409, 412, 423, 434, 436, 444, 462, 512, 524, 533, 540, 549, 551, 562, 580, 610, 618, 641, 691, 703, 712, 719, 727, 729, 740, 758, 790, 798, 1232, 1269, 1306
\ProvidesPackage 803, 804, 1650, 1708, 1927, 1944, 1980, 2006, 2042, 2130, 2215
\ps@thesisheadings 1134

R

\raisebox 1678
\refstepcounter 1502
\relax 87, 88, 183, 184, 301, 329, 336, 961, 1005, 1111, 1117, 1126, 1132, 1194, 1675, 1727, 1729, 1731, 1733, 1737, 1743, 1745, 1747, 1749, 1750, 1752, 1792, 1794, 1796, 1798, 1802, 1808, 1810, 1812, 1814, 1815, 1817, 2025, 2076, 2078, 2079, 2081, 2082, 2084, 2105, 2162, 2164, 2165, 2167, 2168, 2170, 2171, 2173
\renewcommand 1160, 1174, 1193, 1210, 1226, 1227, 1228, 1229, 1234, 1241, 1250, 1259, 1260, 1261, 1262, 1263, 1264, 1265, 1271, 1278, 1287, 1296, 1297, 1298, 1299, 1300, 1301, 1302, 1344, 1345, 1346, 1347, 1348, 1349, 1350, 1351, 1352, 1353, 1755, 1820
\renewenvironment 873, 881
\RequirePackage 3, 4, 5, 6, 8, 289, 860, 864
\RequirePackageWithOptions 291
\reset@font . 1528, 1530, 1532, 1534, 1538
\rightmark 1143, 1146
\rightskip 1199, 1216
\romannumeral 1114
\rowcolors 874, 882
\rule 1680, 1889

S

\sc 979, 993, 1021, 1143, 1146, 1662, 1863, 1886, 1953, 2013, 2057, 2072, 2146, 2158
\scriptsize 1259, 1296, 1347
\secdef 1171, 1186, 1496
\section 1527
\selectfont . . 1234, 1241, 1250, 1259, 1260, 1261, 1262, 1263, 1264, 1265, 1271, 1278, 1287, 1296, 1297, 1298, 1299, 1300, 1301, 1302, 1310, 1316, 1326, 1335, 1336, 1337, 1338, 1339, 1340, 1341
\setcounter 912, 1123, 1129, 1540, 1543, 1544, 1854, 1989, 2020, 2100, 2190
\setkeys 11, 898
\setlength 816, 817, 887, 888, 889, 1198, 1214, 1468, 1469, 1483, 1484, 1677, 1739, 1749, 1752, 1804, 1814, 1817
\setmainfont 854
\setmathfont 855
\settowidth 1676, 1727, 1729, 1731, 1733, 1741, 1743, 1745, 1747, 1792, 1794, 1796, 1798, 1806, 1808, 1810, 1812, 2076, 2078, 2079, 2081, 2162, 2164, 2165, 2167, 2168, 2170
\skip 1384, 1412, 1440
\small 960, 1004, 1241, 1278, 1345
\space 1475, 1503
\string 154, 158, 318, 324
\subparagraph 1536
\subsection 1529
\subsubsection 1128, 1531

T

\tableofcontents 1036, 2108
\tabular 867
\tabularx 879
\textbf 1692, 1758, 1765, 1767, 1769, 1774, 1777, 1779, 1781, 1823, 1830, 1832, 1834, 1839, 1842, 1844, 1846
\textfloatsep 1386, 1414, 1442
\textheight 1377, 1378, 1405, 1406, 1433, 1434
\textit 1103
\textwidth 1142, 1145, 1379, 1407, 1435, 1753, 1818, 1889
\the 187, 188, 191, 192, 196
\thechapter . 1138, 1475, 1503, 1505, 1546
\thepage 280, 1150, 1152
\thesis@ 312, 313, 367, 487, 666

\thesis@@ 72, 313, 980, 982, 988, 993, 996, 1022, 1024, 1030, 1042, 1051, 1059, 1078, 1103, 1662, 1668, 1671, 1676, 1681, 1687, 1692, 1953, 1957, 1959, 1961, 1962, 1963, 1964, 2013, 2057, 2058, 2060, 2072, 2077, 2080, 2088, 2090, 2146, 2147, 2149, 2158, 2163, 2166, 2169, 2177, 2179, 2180, 2181, 2193, 2195, 2196, 2197, 2198
\thesis@@lower 18, 326
\thesis@@upper 18, 327
\thesis@abstract 229, 1060
\thesis@abstractEn 232, 1070
\thesis@academicYear 11, 194, 1778, 1843
\thesis@advisor 235, 1668, 1692, 1775, 1840, 1906, 1957, 1964, 2078, 2088, 2164, 2177, 2198
\thesis@advisorSignature 59
\thesis@arg 78, 79
\thesis@assignmentFiles 239, 1097, 1106
\thesis@author 5, 84, 269, 994, 1045, 1663, 1690, 1760, 1825, 1870, 1899, 1954, 2063, 2081, 2090, 2152, 2167, 2179
\thesis@author@head . . 5, 86, 1960, 2194
\thesis@author@tail 5, 88
\thesis@autofalse 248
\thesis@autotrue 241, 246
\thesis@bachelors 6, 97, 101, 369, 489, 501, 591, 601, 668, 680, 771, 781, 1656, 1717
\thesis@basepath 12, 19, 23, 27, 33, 53, 60, 65
\thesis@blocks@abstract 1055, 1703, 1919, 1971, 1996, 2032, 2119, 2205
\thesis@blocks@abstractEn . . 1063, 1920, 1972, 1997, 2033, 2120, 2206
\thesis@blocks@assignment 1093, 1699, 1921, 2000, 2040, 2117
\thesis@blocks@assignment@false 1658, 1719
\thesis@blocks@assignment@true . 1094
\thesis@blocks@bibEntry 1721, 1917, 1958, 1969, 2192, 2209
\thesis@blocks@bibEntryEn . . 1785, 1918
\thesis@blocks@clear 909, 914, 953, 998, 1035, 1040, 1049, 1099, 1110, 1122, 1685, 1858, 1876, 2017, 2023, 2053, 2093, 2103, 2107, 2110, 2142, 2183
\thesis@blocks@clearRight 922, 1702, 1916, 1970, 1995, 2031, 2118, 2204
\thesis@blocks@cover . 36, 951, 1696, 1856, 1913, 1936, 1966, 1992, 2027, 2051, 2114, 2140, 2200, 2223
\thesis@blocks@cover@content 42, 962, 990, 1032
\thesis@blocks@cover@department@false 974
\thesis@blocks@cover@faculty@true 972
\thesis@blocks@cover@field@false . 976
\thesis@blocks@cover@footer 42, 964, 995, 1033
\thesis@blocks@cover@header 42, 958, 978, 2012, 2015
\thesis@blocks@cover@university@true 970
\thesis@blocks@declaration 1039, 1684, 1700, 1923, 1939, 1975, 2001, 2030, 2123, 2210, 2226
\thesis@blocks@facultyLogo@color 937, 1003, 1892
\thesis@blocks@facultyLogo@monochrome 933, 959
\thesis@blocks@frontMatter 908, 1698, 1851, 1914, 1938, 1968, 1986, 1994, 2016, 2029, 2092, 2115, 2182, 2201, 2225
\thesis@blocks@keywords . . . 1074, 1704, 1973, 1998, 2034, 2121, 2207
\thesis@blocks@keywordsEn 1082, 1974, 1999, 2035, 2122, 2208
\thesis@blocks@lof . 829, 830, 1038, 2112
\thesis@blocks@lot . 827, 828, 1037, 2111
\thesis@blocks@mainMatter . . 1121, 1706, 1925, 1942, 1978, 2004, 2022, 2038, 2102, 2126, 2213, 2229
\thesis@blocks@tables 36, 36, 1034, 1705, 1924, 1941, 1977, 2003, 2037, 2109, 2128, 2212, 2228
\thesis@blocks@thanks 1047, 1701, 1922, 1940, 1976, 2002, 2036, 2124, 2211, 2227
\thesis@blocks@titlePage 997, 1660, 1697, 1875, 1915, 1937, 1967, 1993, 2028, 2116, 2202, 2224
\thesis@blocks@titlePage@content . . 1006, 1032, 1660, 1951, 2068, 2156

\thesis@blocks@titlePage@department@false 1016
\thesis@blocks@titlePage@department@true 1933, 1950
\thesis@blocks@titlePage@faculty@true 1014
\thesis@blocks@titlePage@field@false 1018
\thesis@blocks@titlePage@field@true 1934, 2067, 2221
\thesis@blocks@titlePage@footer 1008, 1033, 1670, 2073, 2159
\thesis@blocks@titlePage@header 1002, 1020, 2015
\thesis@blocks@titlePage@university@true 1012
\thesis@blocks@toc 2106, 2125
\thesis@blocks@universityLogo@color 946, 1883
\thesis@blocks@universityLogo@monochrome 942
\thesis@color@false 819
\thesis@color@setup 897, 1651, 1709, 1928, 1945, 1981, 2007, 2043, 2131, 2216
\thesis@color@true 820
\thesis@cover@false 832
\thesis@cover@true 833
\thesis@czech@abstractTitle 479, 527, 554, 624
\thesis@czech@advisorSignature .. 579
\thesis@czech@advisorTitle 477, 637, 1906
\thesis@czech@assignment 471, 544, 566
\thesis@czech@authorTitle ... 478, 633
\thesis@czech@bib@academicYear *61*, 638, 1744, 1777
\thesis@czech@bib@advisor *61*, 637, 1741, 1774
\thesis@czech@bib@author *61*, 633, 1728, 1758
\thesis@czech@bib@field *61*, 636, 1734, 1769
\thesis@czech@bib@keywords *62*, 640, 1748, 1781
\thesis@czech@bib@pages *62*, 561, 617, 639, 1746, 1779
\thesis@czech@bib@programme *61*, 635, 1732, 1767
\thesis@czech@bib@thesisTitle 634, 1730, 1765
\thesis@czech@bib@title *61*, *61*, 560, 616, 632, 1725
\thesis@czech@declaration 473, 516, 569, 584, 625
\thesis@czech@declarationTitle .. 482
\thesis@czech@facultyLongName ... 531
\thesis@czech@facultyName 470, 530, 536, 543, 550, 557, 565, 583, 613, 621, 1761, 1864, 1887
\thesis@czech@fieldTitle 476, 539, 636
\thesis@czech@gender@koncovka 462, 465, 518, 519, 572, 574, 575, 586, 627
\thesis@czech@idTitle 483, 523
\thesis@czech@keywordsTitle . 480, 640
\thesis@czech@semester 486
\thesis@czech@summer 485
\thesis@czech@thanksTitle 481
\thesis@czech@typeName 488, 590, 1867, 1898
\thesis@czech@typeName@akuzativ 500, 600
\thesis@czech@universityName 469, 515, 1762, 1863, 1886
\thesis@czech@winter 484
\thesis@date *10*, 177, 196, 197
\thesis@day *10*, 180
\thesis@declaration 72, 1043, 1688
\thesis@def 69, 89, 90, 91, 94, 110, 113, 116, 119, 122, 125, 205, 211, 217, 223, 229, 232, 235
\thesis@department .. 110, 984, 1026, 1763, 1865, 1888, 1962, 2014, 2196
\thesis@departmentEn 113, 1828
\thesis@doctoral *6*, 99, 373, 493, 505, 595, 605, 672, 684, 775, 785
\thesis@empty 14, 71
\thesis@english@abstractTitle 359, 415, 1069
\thesis@english@advisorSignature . 432
\thesis@english@advisorTitle 357, 433
\thesis@english@advisorTitleEn .. 450
\thesis@english@assignment 351, 405, 427
\thesis@english@authorTitle . 358, 454
\thesis@english@bib@academicYear *63*, 459, 1809, 1842
\thesis@english@bib@advisor *63*, 450, 458, 1806, 1839

\thesis@english@bib@author *63*, 454, 1793, 1823
\thesis@english@bib@field *63*, 457, 1799, 1834
\thesis@english@bib@keywords *63*, 461, 1813, 1846
\thesis@english@bib@pages *63*, 422, 443, 460, 1811, 1844
\thesis@english@bib@programme *63*, 456, 1797, 1832
\thesis@english@bib@thesisTitle 455, 1795, 1830
\thesis@english@bib@title *63*, *63*, 421, 442, 453, 1790
\thesis@english@declaration . 353, 382
\thesis@english@declarationTitle . 362
\thesis@english@facultyLongName . 392
\thesis@english@facultyName 350, 391, 397, 404, 410, 418, 426, 435, 439, 447, 1826
\thesis@english@fieldTitle 356, 400, 457
\thesis@english@idTitle 363, 389
\thesis@english@keywordsTitle 360, 461, 1088
\thesis@english@semester 366
\thesis@english@summer 365
\thesis@english@thanksTitle 361
\thesis@english@typeName 368
\thesis@english@universityName 349, 381, 1827
\thesis@english@winter 364
\thesis@exists 283, 287, 290
\thesis@faculty 107, 131, 134, 309
\thesis@facultyLogo 131, 935, 939
\thesis@field 122, 988, 1030, 1770, 2170, 2180
\thesis@fieldEn 125, 1835
\thesis@head *18*, 87, 328, 334
\thesis@id 94
\thesis@input 286, 304, 306, 308
\thesis@keywords 217, 220, 270
\thesis@keywordsEn 223, 226
\thesis@load 254
\thesis@loadedfalse 254
\thesis@loadedtrue 258
\thesis@locale 147, 158, 260, 261, 313, 326, 327, 343, 344, 345
\thesis@locale@inheritance 165
\thesis@locale@inheritancefalse . 173
\thesis@locale@inheritancetrue 165, 171
\thesis@localepath ... 27, 304, 306, 308
\thesis@logopath . 19, 935, 939, 944, 948
\thesis@lower *18*, 314, 326, 517, 570, 585, 626, 696, 748, 763
\thesis@male 77, 79
\thesis@masters *6*, 98, 371, 491, 503, 593, 603, 670, 682, 773, 783, 1657, 1718
\thesis@month *10*, 179, 184
\thesis@newtable@false 826
\thesis@newtable@old 867, 876
\thesis@newtable@oldx 879, 884
\thesis@newtable@true 825
\thesis@pages *16*, *19*, 278, 280, 341, 1780, 1845, 1963, 2197
\thesis@palatino@false 823
\thesis@palatino@true 822
\thesis@parseAuthor *5*, 84, 93
\thesis@parseDate ... *10*, 175, 197, 201
\thesis@place 202, 996, 1671, 1869, 1908, 1961, 2062, 2091, 2151, 2181, 2195
\thesis@postamble *14*, *35*, 251, 275, 2039, 2127
\thesis@preamble *14*, *35*, 250, 274, 1695, 1911, 1935, 1965, 1991, 2026, 2113, 2199, 2222
\thesis@programme 116, 1768
\thesis@programmeEn 119, 1833
\thesis@ptsize 806, 807, 808, 1132
\thesis@require 266, 288, 837, 838, 839, 840, 841, 842, 852, 853, 861, 862, 863, 870, 871, 891, 1715, 1716, 2048, 2049, 2136, 2137, 2138
\thesis@requireLocale .. 299, 344, 1714
\thesis@requireStyle 264, 292
\thesis@requireWithOptions 290, 294, 295, 298
\thesis@rigorous *6*, 100, 375, 495, 507, 674, 686, 1666, 1674, 1738, 1773, 1803, 1838, 1905
\thesis@season *10*, 186, 190, 367, 487, 666
\thesis@selectLocale *19*, 261, 342, 1065, 1084, 1786, 1912
\thesis@slovak@abstractTitle 658, 706, 732
\thesis@slovak@advisorSignature . 757
\thesis@slovak@advisorTitle 656

\thesis@slovak@assignment 650, 723, 744
\thesis@slovak@authorTitle 657
\thesis@slovak@bib@pages ... 739, 797
\thesis@slovak@bib@title ... 738, 796
\thesis@slovak@declaration 652, 695, 747, 762
\thesis@slovak@declarationTitle . 661
\thesis@slovak@facultyLongName .. 710
\thesis@slovak@facultyName 649, 709, 715, 722, 728, 735, 743, 761, 793, 801
\thesis@slovak@fieldTitle ... 655, 718
\thesis@slovak@gender@koncovka 641, 644, 698, 750, 752, 753, 765
\thesis@slovak@idTitle 662, 702
\thesis@slovak@keywordsTitle 659
\thesis@slovak@semester 665
\thesis@slovak@summer 664
\thesis@slovak@thanksTitle 660
\thesis@slovak@typeName 667, 770
\thesis@slovak@typeName@akuzativ 679, 780
\thesis@slovak@universityName 648, 694
\thesis@slovak@winter 663
\thesis@style 134, 263, 264
\thesis@style@inheritance 137
\thesis@style@inheritancefalse .. 145
\thesis@style@inheritancetrue 137, 143
\thesis@stylepath 23, 294, 295, 298, 1132
\thesis@subdir 21, 25, 29, 31
\thesis@tail *18*, 88, 335, 340
\thesis@TeXkeywords ... 220, 1079, 1782
\thesis@TeXkeywordsEn . 226, 1089, 1847
\thesis@TeXtitle 208, 991, 1661, 1897, 1952, 2069, 2157
\thesis@TeXtitleEn 214, 2071
\thesis@thanks 237, 1048, 1052
\thesis@title 205, 208, 268, 1766, 1961, 2195
\thesis@titleEn 211, 214, 1831
\thesis@titlePage@footnotesize *52*, 1326, 1346
\thesis@titlePage@Huge *52*, 991, 1341, 1353, 1661, 1867, 1897, 1952, 2060, 2069, 2149, 2157
\thesis@titlePage@huge . *52*, 1340, 1352
\thesis@titlePage@LARGE *52*, 980, 1022, 1339, 1351, 1863, 1886, 1899, 2057, 2146
\thesis@titlePage@Large .. *52*, 982, 994, 1024, 1338, 1350, 1663, 1864, 1887, 1954, 2013, 2058, 2071, 2147
\thesis@titlePage@large .. *52*, 984, 987, 993, 996, 1026, 1029, 1337, 1349, 1662, 1667, 1671, 1865, 1869, 1898, 1953, 1956, 2014, 2062, 2072, 2074, 2151, 2158, 2160
\thesis@titlePage@normalsize *51*, 1309, 1344, 1888, 1902
\thesis@titlePage@scriptsize *52*, 1335, 1347
\thesis@titlePage@small *51*, 1316, 1345
\thesis@titlePage@tiny . *52*, 1336, 1348
\thesis@twoside@false 811
\thesis@twoside@true 813
\thesis@type 97, 369, 371, 373, 375, 378, 489, 491, 493, 495, 498, 501, 503, 505, 507, 510, 591, 593, 595, 598, 601, 603, 605, 608, 668, 670, 672, 674, 677, 680, 682, 684, 686, 689, 771, 773, 775, 778, 781, 783, 785, 788, 1656, 1657, 1666, 1674, 1717, 1718, 1738, 1773, 1803, 1838, 1905
\thesis@university 19, 104, 134, 295, 306, 308
\thesis@universityLogo .. 128, 944, 948
\thesis@upper .. *18*, 320, 327, 1960, 2194
\thesis@version 1, 271
\thesis@womanfalse 75, 80
\thesis@womantrue 82
\thesis@year *10*, 178, 183, 367, 487, 666, 1870, 1908, 1962, 2063, 2091, 2152, 2196
\thesislong 252
\thesissetup 10
\thispagestyle 917, 926, 956, 1000, 1101, 1163, 1168, 1176, 1178, 1493, 1861, 1879, 2055, 2144
\tiny 1260, 1297, 1348
\topmargin 1369
\topsep 1247, 1256, 1284, 1293, 1324, 1332, 1561, 1569, 1575, 1577, 1591, 1599, 1605, 1607, 1621, 1629, 1635, 1637
\topskip 1373, 1378, 1406, 1434
\twocolumn 1191
\typeout 1503

U

\undefined 149, 341, 1048, 1097
\uppercase 322

V

\value 925
\vbox 1142, 1145
\vfil 991, 1061, 1071, 1080, 1090, 1185, 1661, 1693, 1952
\vfill . . . 963, 1007, 1691, 1866, 1868, 1896, 1900, 2059, 2061, 2148, 2150
\vskip 987, 989, 992, 1029, 1031, 1044, 1143, 1146, 1213, 1473, 1477, 1487, 1661, 1689, 1952, 2014, 2087, 2176
\vspace 1051, 1889

W

\widowpenalty 895
\write 279

X

\x 843, 844, 846, 847

Y

\year 196

Z

\z@ 1169, 1199, 1216, 1237, 1244, 1253, 1275, 1281, 1290, 1312, 1319, 1329, 1468, 1469, 1483, 1484, 1494, 1527, 1529, 1531, 1534, 1576, 1606, 1636

Change History

v0.0
General: bachelor project of Daniel Marek under supervision of Petr Sojka 1
v0.0a
General: changes by Jan Pavlovič to allow fithesis being backend of docbook based system for thesis writing 1
v0.1
General: new release, documentation editing (CZ only, sorry) [PS] 1
v0.1a
General: minor documentation changes (CZ only, sorry) [PS] . . . 1
v0.1b
General: change of default size (11pt→12pt) [JP] 1
v0.1c
General: default values of \facultyname and \@thesissubtitle set for backward compatibility) [PS] 1
v0.1d
General: removed def schapter from fit1*.clo [JP] 1
v0.1e
General: add Brno to MU title [JP] . 1
v0.1f
General: add documentation for hyperref [JP] 1
v0.1g
General: change of default size (12pt→11pt) [JP] 1
v0.2.00
General: add sk lang [JP, Peter Cerensky] set default cls class to rapport3 [JP] 1
v0.2.01
General: add subsubsection to toc [JP] 1
v0.2.02
General: fix encoding bug [JP] 1
v0.2.03
General: fix title spacing [PS, JP] . . . 1
v0.2.04
General: fix SK declaration [Peter Cerensky, JP] 1
v0.2.05
General: add English abstract [JP] . . 1
v0.2.06
General: fix : behind Advisor [JP] . . 1

v0.2.07
General: escape all Czech letters [JP] babel is used instead of stupid package czech [JP] \MainMatter should be placed after \tablesofcontents [PS] . . 1
v0.2.08
General: add change of University name [JP] 1
v0.2.09
General: add EN version of University name [JP] 1
v0.2.10
General: fix EN name of Acknowledgement [JP] 1
v0.2.11
General: fix missing fi-logo.mf [JP,PS] 1
v0.2.12
General: Licence change to the LPPL [JP] 1
v0.2.12a
General: fork fithesis2 by Mr. Filipčík and Janoušek; cf. http://github.com/liskin/fithesis . . 1
v0.3.00
General: fi logo is no longer special-cased (added eps and PDF), \thesislogopath added to set the logo directory path, \thesiscolor added to enable colorful typo elements [VN] . . . 1
v0.3.01
General: documentation now uses babel and cmap packages. the entire file was transcoded into utf8, \thesiscolor was replaced by color class option, added PDF metadata stamping support [VN] 1
v0.3.02
General: PDF metadata stamping added for \thesistitle and \thesisstudent [VN] 1
v0.3.03
General: Small fixes (added \relax at \MainMatter), generating both fithesis.cls (obsolete, loading fithesis2.cls) and fithesis2.cls, minor doc edits, version numbering of .clo fixed, switch to utf8 and ensuring that .dtx compiles. Documentation adjusted to the status quo, added link to discussion forum (backport of v0.2.14) [PS] . 1
v0.3.04
General: Import the url package to allow for the use of \url within the documentation. (backport of v0.2.15@r13) [VN] 1
v0.3.05
General: Added support for change typesetting. Restructured the code to make it more amenable to literal programming. Added support for \CodelineIndex typesetting. Added information about the usage of fithesis1 and fithesis2 on the FI unix machines. (backport of v0.2.16) [VN]
Minor changes throughout the text, added a link to the the fithesis forums [PS] (backport of v0.2.15@r14:15) 1
v0.3.06
General: Added the colorx package and the base colors for each faculty. If the color option is specified, the tabular environment gets redefined and uses the faculty colors to color alternating table rows to improve readability. The hyperref links in the e-version are now likewise colored according to the chosen faculty, in this case regardless of the presence of the color option. Dropped the support for typesetting theses outside MU. [VN] . 1
v0.3.07
General: Replaced the \thesiswoman command with \thesisgender. [VN] 1
v0.3.08
General: Fixed a non-terminated \if condition. [VN] (backport of v0.2.18)

Fixed mostly documentation errors reported at the new fithesis discussion forum (-ti, eco→econ, implicit twocolumn, example extended (font setup), etc.). [PS] (backport of v0.2.17) . . 1

v0.3.09

General: A complete refactoring of the class. The class was decomposed into a base class, locale files and style files. [VN] 1

v0.3.10

General: Fixed a typo in the technical documentation. Updated the *Advanced usage* chapter of the user guide. The required packaged listed in Section 2.2 of the user guide are now always correct. Adjusted the footer spacing in the styles of econ and fi. Added *Advanced usage* chapter to the user guide. Added the description of basic options into the user guide. Added the `table` and `oldtable` options. Added the `type` field to the guide for completeness. [VN] 1

v0.3.11

General: Added hyphenation into the technical documentation. Fixed an unterminated group. Polished the text of the guide. Added the `palatino` and `nopalatino` options. Stylistic changes to the text of the technical documentation. `\thesis@subdir` is now robust against relative paths. Accounted for French spacing in the guide. Fixed the `thesis@english@facultyName` string. Documentation refinements. [VN] 1

v0.3.12

General: The subsections and subsubsections now use the correct `tocdepth`. [VN] 1

v0.3.13

General: Fixed an inconsistency in the example code. Removed an extraneous `\thesis@blocks@clear` block withing the definition of `\thesis@blocks@frontMatter` in the fss style file. Added comments, fixed clubs and widows and removed text overflows within the user guides. Adjusted the colors of various style files. Removed the trailing dot in the bibliographic identification within the med and ped style files. Fixed a typo within the technical documentation. Fixed the twoside alignment of the `\thesis@blocks@bibEntry` and the `\thesis@blocks@bibEntryEn` blocks within the sci style file. The `\thesis@blocks@assignment` block no longer clears a page when nothing is inserted. It is also no longer hardcoded to be hidden for rigorous theses. Instead, the `\ifthesis@blocks@assignment` conditional can be set either by the subsequently loaded style files or by the user. So far, only the fi and sci style files set the conditional. [VN] 1

v0.3.14

General: Updated the documentation. [VN] 1

v0.3.15

General: Renamed `\thesis@requireStyle` to `\thesis@requireWithOptions` and moved the style loader from the `\thesis@load` routine to a new `\thesis@requireStyle` macro to make the semantics of `\thesis@requireLocale` and `\thesis@requireStyle` more similar. Changed the `basepath`, `logopath`, `localepath` and `stylepath` keys to match the lower camelcasing of the rest of the keys. Added further description regarding the use of the `assignment` key. [VN] 1

v0.3.16

General: Clubs and widows are now set to be infinitely bad. The `assignment` key has weaker, but more robust semantics now. [VN] 1

v0.3.17

General: Changed a forgotten `\thesis@@lower{...}` invocation in the definition of `\thesis@czech@declaration` for the Faculty of Arts into `\thesis@@lower{czech@...}`, so that the macro always expands to the correct output regardless of the current locale. This is merely a matter of consistency, since the style file of the Faculty of Arts only uses Czech strings within the Czech locale. Removed an extraneous comment. Fixed a unit test. Fixed a changelog entry. [VN] 1

v0.3.18

General: A bulk of changes required to submit the document class to CTAN: Changed the structure of the output `fithesis3.ctan.zip` archive. Updated the license notice. Added a `README` file. Canonicalized a url within the user guides. Renamed the root directory from `fithesis3/` to `fithesis/`. Refactored the makefiles. Added developer example files. Renamed `docstrip.cfg` to `LICENSE.tex` to better describe its role. The `fithesis.dtx` file now generates a `VERSION.tex` file containing the version of the package, when it's being typeset. Flattened the `logo/` directory structure. [VN] 1

v0.3.19

General: Updated the license. Added the `fithesis-` prefix to locale files. Proofread and updated the documentation. Encapsulated the `localeInheritance` and `styleInheritance` setters. Added the `\thesis@selectLocale{...}`, which acts as a replacement for `\def\thesis@locale{...}`, which also switches hyphenation patterns. The macro definitions inside locale files are now global to account for the fact that it now makes sense to include locale files on-site (and therefore possibly inside a group) using the `\thesis@selectLocale`. The class files are now generated using the XeTeX engine, which preserves the characters outside ASCII. [VN] 1

v0.3.20

General: Removed an extraneous `\hypersetup` option to eliminate a warning. Performed several minor Makefile updates. Updated the technical documentation. [VN] 1

v0.3.21

General: Fixed an invalid font name. [VN] 1